MIL-S-63540/1A
AMENDMENT 1
1 August 1986

MILITARY SPECIFICATION SHEET

STUD, SELF-LOCKING, FLUSH HEAD,
RIBBED CLINCH TYPE

This amendment forms a part of MIL-S-63540/1A, dated 31 March 1986, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 6

INSTALLATION PROCEDURES:

Delete subparagraph identifications "a, b, b, c" and substitute "a, b, c, d".

PAGE 7

TABLE IV, Title: Add "(Reference)"

TABLE IV, next to "T THREAD SIZE" column: Add column for "SHEET THICKNESS MIN" as noted below:
".040" for all thread sizes ".086-56 UNC" through ".190-32 UNF";
".062" for thread size ".250-20 UNC"; and ".093" for thread size ".313-18 UNC".

TABLE IV: Remove "(Ref)" from all column headings.

TABLE IV, "Anvil Countersink Diameter" and "Anvil Hole Diameter" columns: Delete "-" sign and insert "to" between values.

Custodians:
Army - AR
Navy - MC
Air Force - 99

Review activities:
Army - AT, ME
Air Force - 11, 82
DLA - IS

User activities:
Army - ER
Navy - OS, SH
NSA - NS

Preparing activity:
Army - AR

Agent:
DLA - IS

(Project 5307-0449)

AMSC N/A

FSC 5307

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:04Z
Check the source to verify that this is the current version before use.