MIL-C-50513B (AR)
27 February 1981
SUPERSEDING
MIL-C-50513A (MU)
23 July 1973

MILITARY SPECIFICATION

CARTRIDGE, IGNITION, M2A2
PARTS FOR, LOADING, ASSEMBLING AND PACKING

This specification is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not covered by the drawings and provides quality assurance provisions for the parts, loading, assembling and packing of one type of ignition cartridge designated as Cartridge, Ignition, M2A2 for the 4.2 Inch Mortar.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for propsals form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-B-117	- Bags, Interior Packing
MIL-P-223	- Powder, Black
MIL-B-2427	- Boxes, Ammunition, Packing, Wood, Nailed

FSC: 1315

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

MIL-A-48078 - Ammunition, Standard, Quality Assurance Provisions, General Specification for
MIL-F-50449 - Filler, Sheet Form (For Use In Ammunition Containers)

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)

DRAWINGS (See 6.4)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

8796522 - Marking Diagram and Sealing for Wood Packing Boxes
9252205 - Cartridge, Ignition, M2A2

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids, or request or proposal, shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 0-190 - Code of Federal Regulations Title 49 (Revised as of January 1 1968)

The Department of Transportation Regulations are now a part of the Code of Federal Regulations (1968 Edition and revisions) available from the Superintendent of Documents, US Government Printing Office, Washington, D.C. 20402. Orders for the above publications should cite "49 CFR 0-190 (Revised as of 1 January 1968).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on drawing (dwg.) 9252205 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Moisture content of black powder. The moisture content of black powder at the loading station, at the time of loading, shall not exceed 0.50 percent when determined as specified in 4.5.1.

3.4 Functioning sensitivity

3.4.1 Non-functioning. The assembly shall not function under an applied energy value of 4 inch ounces minimum (min.) when tested as specified in 4.5.2.1.

3.4.2 Functioning. The assembly shall function under an applied energy value of 640 inch ounces maximum (max.) when tested as specified in 4.5.2.2.

3.5 Proving ground. The assembly shall function on first attempt with no audible hang fire when tested as specified in 4.5.4.

3.6 Gross weight of assembly. The gross weight of the assembly shall be 368 grains min.

3.7 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.8 Workmanship

3.8.1 Parts and assemblies. The parts and assemblies shall be free from burrs, chips, dirt, grease and other foreign material. The cleaning method used shall not be

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent. Surface coatings shall be continuous except for a few light scratches not exposing base material.

3.8.2 Packaging. The packaging shall be free from foreign material. The paperboard boxes shall be assembled without undue binding and no flap shall project beyond the edge of the box when closed

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First article inspection
b. Quality conformance inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Number	Drawing	Quantity
Body assembly	9254841	25
Primer and body assembly	9252692	25
Cap	9282887	25
Cap, crimp	9278190	25
Tube, insert	9242579	25
Cartridge, Ignition, M2A2	9252205	111

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-50513B(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
	Cartridge, Ignition, M2A2 and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body Assembly (dwg. 9254841)				
	Examination for defects	25		3.2	4.4.2.1
	Primer and Body Assembly (dwg. 9252692)				
	Examination for defects	25		3.2	4.4.2.2
	Cap (dwg. 9282887)				
	Examination for defects	25		3.2	4.4.2.3
	Cap, Crimp (dwg. 9278190)				
	Examination for defects	25		3.2	4.4.2.4
	Tube, Insert (dwg. 9242579)				
	Examination for defects	25		3.2	4.4.2.5
	Cartridge, Ignition, M2A2 (dwg. 9252205)				
	Examination for defects	111		3.2	4.4.2.6
	Gross weight	111		3.6	Test

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-50513B(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	Cartridge, Ignition, M2A2 and Components				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Weight of charge	10		3.2	Test
	Moisture content	1		3.3	4.5.1
	Leak test	100		3.2	4.5.3
	Non-functioning	25		3.4.1	4.5.2.1
	Functioning	25		3.4.2	4.5.2.2
	Proving Ground	50		3.5	4.5.4

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots shall contain the following items of one lot interfix from one manuafacturer:

a. Inert components and assemblies
b. Primers
c. Black powder

4.4.2 Examination. See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Body Assembly				9254841
					NEXT HIGHER ASSEMBLY
					9252205
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter of body, max.		0.40%	3.2	Gage
102	Wall thickness		0.40%	3.2	Gage
103	Crimp or knurl missing or incomplete		0.40%	3.2	Visual
104	Head loose		0.40%	3.2	Visual/Manual
105	Wad missing or loose		0.40%	3.2	Visual/Manual
Minor					
201	Diameter of flange, max.		0.65%	3.2	Gage
202	Overall length, min.		0.65%	3.2	Gage
203	Protective finish missing or damaged exposing base metal (as applicable)		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-50513B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9252692
4.4.2.2	Primer and Body Assembly				NEXT HIGHER ASSEMBLY 9252205
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Primer above flush		100%	3.2	Gage
Major					
101	Primer loose or missing		100%	3.2	Visual/Manual
102	Lacquer missing or applied improperly		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.8.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-50513B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Cap		9282887
			NEXT HIGHER ASSEMBLY
			9252205

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Body diameter		0.40%	3.2	Gage
102	Groove missing		0.40%	3.2	Visual
Minor					
201	Overall length		0.65%	3.2	Gage
202	Flange thickness		0.65%	3.2	Gage
203	Flange diameter, min.		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-50513B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Cap, Crimp				9278190
					NEXT HIGHER ASSEMBLY
					9252205
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Length		0.65%	3.2	Gage
202	Inside diameter		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-50513B (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Tube, Insert	1 OF 1	9242579
			NEXT HIGHER ASSEMBLY 9252205

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
102	Wall thickness		0.40%	3.2	Gage
103	Outside diameter		0.40%	3.2	Gage
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-50513B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9252205
4.4.2.6	Cartridge, Ignition, M2A2				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Component punctured, loose or missing allowing charge to escape		100%	3.2	Visual/Manual
2	Non-functioning			3.4.1	4.4.3.1/4.5.2.1
Major					
101	Liner missing		100%	3.2	Visual
102	Lacquer missing or inadequate		0.40%	3.2	Visual
103	Moisture content of black powder	*		3.3	4.5.1
104	Functioning			3.4.2	4.4.3.1/4.5.2.2
105	Leak test			3.2	4.4.3.2/4.5.3
106	Proving Ground			3.5	4.4.3.3/4.5.4
107	Weight of charge		0.25%	3.2	Test
108	Gross weight		100%	3.6	Test
Minor					
201	Small outside diameter, max.		0.65%	3.2	Gage
202	Overall length, max.		0.65%	3.2	Gage
203	Marking misleading, missing or unidentifiable		0.65%	3.2	Visual
204	Evidence of poor workmanship		0.65%	3.8.1	Visual

NOTES: One assembly from each eight hours of production shall be selected. If the sample after analysis fails to comply with the applicable requirement the eight hours of production represented by the sample shall be rejected.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET		DRAWING NUMBER
4.4.2.7	Paperboard Box, Prior to Closing		1 OF 1		NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Number of cartridges incorrect		0.40%	5.1	Visual
Minor					
201	Box punctured, cut or torn		0.65%	5.1	Visual
202	Evidence of poor workmanship		0.65%	3.8.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Sealed Barrier Bag				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Heat seal test (if applicable)	*	4.0%	5.1	Test
102	Bag punctured, cut or torn		0.40%	5.1	Visual
Minor					
201	Marking missing, misleading or unidentifiable (if applicable)		0.65%	5.1	Visual
202	Evidence of poor workmanship		0.65%	3.8.2	Visual

NOTES: *Samples shall be selected at random from each lot at inspection level S-4 under MIL-STD-105 or at inspection level I for use under miltilevel sampling plan CSP-M of MIL-STD-]235.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Sealed Wood Packing Box	1 OF 1	NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Box broken, board loose or protruding nail		0.40%	5.2	Visual
102	Contents exposed		0.40%	5.2	Visual
103	DOD symbol missing or incorrect		0.40%	5.2	Visual
104	Strapping, missing, broken or loose		0.40%	5.2	Visual
Minor					
201	Contents loose		0.65%	5.2	Visual
202	Marking misleading, missing or unidentifiable		0.65%	5.2	Visual
203	Car seal missing, unsealed or improperly positioned		0.65%	5.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance tables.

4.4.3.1 Non-functional/functioning. The following sampling plan will apply with the sample tested as specified in 4.5.2. An independent sample shall be selected for each of the non-functioning, functioning tests.

4.4.3.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified, the sampling plan shall be in accordance with MIL-STD-105, Table IIA, Code Letter L and an AQL of 0.065 percent for non-functioning and an AQL of 0.25 percent for functioning.

4.4.3.1.2 After three consecutive lots have complied with the criteria specified in 4.4.3.1.1, the sampling plan shall be in accordance with MIL-STD-105, Table IIA, Code Letter K and an AQL of 0.10 percent for non-functioning and an AQL of 0.40 percent for functioning. In the event that a single lot fails to comply with the non-functioning requirement the sampling shall revert to 4.4.3.1.1. In the event that three consecutive lots fail to comply with the functioning requirement the sampling shall revert to 4.4.3.1.1.

4.4.3.2 Leak test. The following sampling plan will apply with the sample tested as specified in 4.5.3.

4.4.3.2.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified, the sampling plan shall be in accordance with MIL-STD-105, Table IIA, Code Letter H and an AQL of 0.25 percent.

4.4.3.2.2 After three consecutive lots have complied with the criteria specified in 4.4.3.2.1, the sampling plan shall be in accordance with MIL-STD-105, Table IIA, Code Letter F and an AQL of 0.65 percent. In the event that three consecutive lots fail to comply with the requirements the sampling shall revert to 4.4.3.2.1.

4.4.3.3 Proving ground. The following sampling plan will apply with the sample tested as specified in 4.5.4.

4.4.3.3.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified, the sampling plan shall be in accordance with MIL-STD-105, Table IIA, Code Letter K and an AQL of 0.40 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

4.4.3.3.2 After three consecutive lots have complied with the criteria specified in 4.4.3.3.1, the sampling plan shall be in accordance with MIL-STD-105, Table IIA, Code Letter H and an AQL of 1.0 percent. In the event that three consecutive lots fail to comply with the requirements the sampling shall revert to 4.4.3.3.1.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection

4.5.1 Moisture content of black powder. The moisture content of the black powder shall be determined in accordance with the procedure specified in MIL-P-223.

4.5.2 Functioning sensitivity

4.5.2.1 Non-functioning. The ignition cartridge shall be assembled to a test fixture so that the firing pin will strike the sensitive end of the primer. A 1.98 plus or minus .02 ounce (oz.) steel ball shall be dropped on the firing pin from a height of 2 inches (in.) min. The height of drop shall be measured as the height from the top of the pin to the bottom of the ball.

4.5.2.2 Functioning. The procedure used shall be as specified in 4.5.2.1 except that a steel ball of 20 minus 0.2 lbs. shall be dropped on the firing pin from a height of 2 in. max.

4.5.3 Leak test. The ignition cartridge shall be assembled to a test fixture so that all the joints are subjected to an externally applied pressure of 3 plus or minus 0.5 pounds per square inch (psi.). Pressure source shall be cut off and observations made for pressure drop during a 5 sec. period after stabilization. The maximum amount of pressure loss in stabilization shall be determined in the initial calibration of the equipment. Pressure drop shall not exceed 0.25 psi.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

4.5.4 Proving ground. This test shall be performed at a government proving ground. The ignition cartridge shall be assembled to a M329A1 projectile and obturator mechanism loaded to a weight of 26.00 plus or minus .01 lbs. (without extension). The ballistic sample shall be fired at the ten increment charge. Each round in the sample shall contain a 5 increment bag charge and a 5 increment bundle. The rounds shall be fired from a 4.2" mortar for which the round is standard at an elevation of 900 mils. Individual muzzle velocities and standard deviation of the lot shall be recorded and reported for information purposes.

5. PACKAGING

5.1 Packaging requirements

5.1.1 Level A. Twenty five ignition cartridges shall be packaged in a paperboard box of the kind as is used for shotgun shells. Each box shall then be packaged in a MIL-B-117, Type I, Style I, Class E barrier bag. The bag shall be closed by means of heat sealing. Corners of the box shall be blunted prior to bagging and excess air shall be exhausted from the bag prior to sealing.

5.1.2 Level C. Ignition cartridges shall be packaged in a paperboard box of the kind as is used for shotgun shells.

5.2 Packing

5.2.1 Level A. Pack forty paperboard boxes in a MIL-B-2427, Grade A, Type I, Class 1 nailed wood box. All inside surfaces of the box shall be lined with MIL-F-50449, Type I or II, filler, sheet form.

5.2.2 Level C. The packaged ignition cartridges shall be packed in accordance with Code of Federal Regulations Title 49 CFR 0-190.

5.3 Marking

5.3.1 Level A. Each unit box shall be labeled, printed or stamped and each barier bag printed or stamped with the following information:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

25-CARTRIDGE, IGNITION, M2A2
LOT (MFR SYMBOL NO.)
LOADED (MO/YR)

All letters shall be upper case. Size shall be min. 1/4 inch. Ink shall be black, waterproof, commercial grade. Label paper shall be gummed and white in color. Labels shall be applied to the side or end of the box. Exterior wooden boxes shall be marked in accordance with dwg. 8796522. The DOT marking shall be "SMALL ARMS AMMUNITION".

5.3.2 Level C. Unit and exterior boxes shall be marked in accordance with the manufacturers' standard requirements. The DOT marking shall be "SMALL ARMS AMMUNITION."

6. NOTES

6.1 Intended use. The components covered by this specification is intended for use on the 4.2 Inch, Smoke M328, HE M329, Illum. M335 and CS, Tactical XM630.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment for design approval. See MIL-A-48078. Submit designs as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, NJ 07801.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
ARMY-AR

Preparing Activity:
ARMY-AR

Project Number: 1315-A354

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-50513B Cartridge, Ignition, M2A2 Parts for LAP

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament R & D Command
ATTN: DRDAR-QAR
Dover, New Jersey 07801

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.