MILITARY SPECIFICATION

CHARGE ASSEMBLY, DEMOLITION, M183 WITH CHARGE, DEMOLITION M112, PARTS FOR, LOADING, ASSEMBLY, AND PACKING

1. SCOPE

1.1 This specification covers the parts for, loading, assembling and packing for one type of demolition item, designated as Charge Assembly, Demolition, M183, with Charge, Demolition, M112, Assembly.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116	-	Preservation, Methods of
MIL-A-2550	-	Ammunition and Special Weapons; General Specification for
MIL-L-10547	-	Liners, Case, and Sheet, Overwrap, Water-Vaporproof or Waterproof, Flexible

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	-	Quality Assurance Terms and Definitions

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:28Z
Check the source to verify that this is the current version before use.

MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

U.S. ARMY MUNITIONS COMMAND

9216416 - Charge Assembly, Demolition, M183, with Charge, Demolition, M112, Assembly
8883618 - Box, Packing, Ammunition, for Charge Assembly, Demolition, M37 or M183
8796522 - Marking Diagram and Sealing

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 71-90 - Interstate Commerce Commission Rules and Regulations for the Transportation of Explosives and Other Dangeous Articles

(The Interstate Commerce Commission Regulations are now a part of the Code of Federal Regulations (1949 Edition and revisions) available from the Superintendent of Documents, Government Printing Office, Washington 25, D.C. Orders for the above publications should cite "49 CFR 71-90 (latest revisions)".)

3. REQUIREMENTS

3.1 Material.-Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 The charge assembly, demolition M183, shall comply with all the requirements specified on Drawing (dwg.) 9216416 and all drawings referenced thereon, and with all requirements specified in applicable specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:28Z
Check the source to verify that this is the current version before use.

3.3 Workmanship.-All parts and assemblies shall be fabricated and loaded in a thorough workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, and other foreign matter. Charges shall be free of breaks, cracks and other defects. Colors shall be uniform. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with identification and date of changes thereto.
c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.
d. Number of items in the lot.
e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:28Z
Check the source to verify that this is the current version before use.

4.2 Inspection provisions

4.2.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer in one unchanged process using the same materials and methods in accordance with the same drawings, same drawing revisions, same specifications and the same specification revisions and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of the inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each lot of demoliton charge assemblies shall contain:

a. Parts or sub-assemblies from not more than one lot interfix number from one manufacturer.
b. Demolition blocks from not more than one lot interfix number from one manufacturer.
c. Priming assemblies from not more than one lot interfix number from one manufacturer.
d. Bag assemblies from not more than one lot interfix number from one manufacturer.
e. Carrying case assemblies from not more than one lot interfix number from one manufacturer.

4.2.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.2.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:28Z
Check the source to verify that this is the current version before use.

each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system.

4.2.2.1 Loading assembly (see dwg. 9204248 covering a detail of dwg. 9216416)

Categories	Defects	Method of Inspection	Code No. (See 6.2)
Critical:	None defined		
Major:	None defined		
Minor:	AQL 1.50 Percent		
201.	Sides warped or wrinkled	Visual	01001
202.	Cut, puncture, tear or burn through	Visual	01002
203.	Marking missing, incomplete, improper or unidentifiable	Visual	01003
204.	Evidence of poor workmanship (see 3.3)	Visual	01004

4.2.2.2 Bag assembly (see dwg. 8861111 covering a detail of dwg. 9216416)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	None defined		
Minor:	AQL 1.50 Percent		
201.	Cut, puncture or tear	Visual	02001
202.	Stitch or seam loose or open	Visual	02002
203.	Assembly or any component damaged, missing or mislocated	Visual	02003

4.2.2.3 Demolition block bag assembly (see dwg. 9216417 covering a detail of dwg. 9216416)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:28Z
Check the source to verify that this is the current version before use.

Major:		AQL 0.65 Percent	
101.	Filler missing or improperly assembled in bag	Visual	03001
102.	Separators or fillers missing or improperly assembled in bag	Visual	03002
103.	Incorrect quantity of demolition blocks	Visual	03003
104.	Cord untied or improperly tied	Visual	03004

Minor: None defined

4.2.2.4 Charge Assembly, Demolition, M183 with Charge, Demolition, M112, Assembly (see dwg. 9216416)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 Percent		
101.	Priming assembly missing	Visual	04001
102.	Demolition block bag assembly missing	Visual	04002
103.	Tight coils or kinks in priming assembly	Visual	04003
Minor:	AQL 4.00 Percent		
201.	Marking missing, incomplete, improper or unidentifiable	Visual	04004
202.	Cut, puncture or tear	Visual	04005
203.	Trace assembled improperly	Visual	04006
204.	Strap improperly tied	Visual	04007
205.	Components loose in carrying case	Visual/Manual	04008
206.	Loader's lot number missing	Visual	04009
207.	Date of loading missing or incorrect	Visual	04010
208.	Evidence of poor workmanship (see 3.3)	Visual	04011

4.2.2.5 Box, packing prior to closing (see dwg. 8883618)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:28Z
Check the source to verify that this is the current version before use.

Major:	AQL 1.00 Percent		
101.	Incorrect number of assemblies	Visual	05001
102.	Assembly or component improperly inserted	Visual	05002
103.	Improper type of assembly or component	Visual	05003
104.	Case liner split or cracked	Visual	05004
105.	Case liner not sealed	Visual	05005
Minor:	AQL 0.65 Percent		
201.	Filler missing or improperly assembled	Visual	05006

4.2.2.6 Box, packing, marking, closing, sealing and strapping (see dwgs. 8796522 and 8883618)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 1.00 Percent		
101.	I.C.C. marking missing, incorrect improper or illegible	Visual	06001
102.	Descriptive nomenclature missing, incorrect, improper or illegible	Visual	06002
103.	Strapping improper	Visual	06003
104.	Car seal missing, or improperly positioned or improperly sealed	Visual	06004
105.	Contents loose when box is tilted	Visual/Manual	06005
106.	Board, broken or split	Visual	06006
107.	Box damaged, so that its contents are exposed or liable to become exposed	Visual	06007
Minor:	None defined		

4.3 Testing

4.3.1 Heat seal test of case liner (see dwg. 8883618), Major Defect, Code No. 05007.-A sample of five packed and sealed case liners shall be selected from each lot for this test. If any sealed case liner fails to comply with the requirement specified, the lot shall be rejected. The test shall be performed as specified in MIL-P-116 or MIL-L-10547.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:28Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packing.-Packing for levels A, B and C shall be as specified on drawing 8883618.

5.2 Marking.-Marking of all packaging and packing shall comply with drawings 8883618 and 8796522.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. These code numbers are also used to correlate the characteristics cited on Equipment Lists with the inspections listed in this specification. In addition, they should be cited as references on drawings of equipment designs submitted by the contractor to the Government for approval (see 6.3.5).

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the inspection Equipment Lists (EL) referenced on the applicable ET in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Inspection equipment lists (EL).-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:28Z
Check the source to verify that this is the current version before use.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all the information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finishes, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculations or clarifications will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category A, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable five digit code number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:28Z
Check the source to verify that this is the current version before use.

letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND15. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

6.4 Supersession data.-This specification includes the requirements of PA-PD-2888, dated 1 October 1966.

Custodian:
Army-MU

Preparing activity:
Army-MU

Project Number: 1375-A-065

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:28Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION		
ORGANIZATION	CITY AND STATE	
CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:28Z
Check the source to verify that this is the current version before use.