MILITARY SPECIFICATION

ROCKET, 762MM, HE, WARHEAD SECTION: M144

LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of warhead section, designated as Rocket, 762MM, HE, Warhead Section: M144.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550	-	Ammunition and Special Weapons, General Specification for
MIL-I-45607	-	Inspection Equipment, Acquisition, Maintenance and Disposition of
MIL-P-116	-	Preservation, Methods of

STANDARDS

MILITARY

FSC: 1340

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:39Z
Check the source to verify that this is the current version before use.

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109	-	Quality Assurance Terms and Definitions
MIL-STD-1168	-	Lot Numbering of Ammunition
MIL-STD-1235	-	Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

U.S. ARMY MUNITIONS COMMAND

8831168	-	Warhead, Section, 762MM Rocket, HE: M144
8881082	-	Shipping and Storage Cntr, Warhead Section, M473 and M473A1 for 762MM Warheads Pkg and Mkg.

PUBLICATIONS

ARMY

ET-8831168	-	Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:39Z
Check the source to verify that this is the current version before use.

CODE OF FEDERAL REGULATIONS

Title 49 - Transportation, Parts 171-179

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. Orders should specify, "49 CFR 171-179 (latest revision)".)

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts.-The parts shall comply with all requirements specified on Drawing (Dwg.) J-8831168, all associated drawings, and with all requirements specified in applicable specifications.

3.3 Serial Number.-A serial number shall be marked on each forward assembly and rear assembly to assure the same forward assembly will be reassembled to the rear assembly it was removed from prior to loading.

3.4 Stability of bag and filler assembly.-The foaming plastic bag shall expand and achieve a uniform firm set when tested as specified in 4.4.1.

3.5 Barrier Bag, heat-sealed seam test.-The heat-sealed seam may evidence partial separation within the first two (2) minutes of the test. No additional separation permitted in the heat-sealed area during the final three (3) minutes of the test. The test shall be performed as specified in 4.4.2.

3.6 Workmanship.-All parts and assemblies shall be fabricated, loaded and assembled in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust, and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required marking and stamping shall be neat and sharply defined.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:39Z
Check the source to verify that this is the current version before use.

3.7 Submission of results of contractor-conducted examinations and tests.-The contractor shall forward copies of the results of any of his examinations or tests to the designated address as required by the contract. (see 6.4).

3.8 First article testing.-This specification makes provisions for first article testing. Submission of first article quantity by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with identification and date of changes thereto.
c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.
d. Number of items in the lot.
e. Date submitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:39Z
Check the source to verify that this is the current version before use.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First article inspection.

4.2.1 Submission.-The contractor shall submit a sample of two (2) assemblies to a Government approved facility as designated by the contracting officer for testing in accordance with the provisions of 4.2.2 (See 6.1). All parts and materials shall be the same as will be used in production and shall be obtained from the same source of supply. Prior to submission, the sample shall be inspected by the contractor to the degree necessary to assure that it conforms to the requirements of the contract. First article inspection shall also apply when a lapse in production exceeds ninety (90) days.

4.2.2 Inspections to be performed.-Assemblies and components will be subjected by the Government to any or all the examinations or tests specified in this specification and any or all requirements of the applicable drawings.

4.2.3 Rejection.-If any assembly or component fails to comply with any of the applicable requirements, the first article quantity shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component in the sample to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article quantity or portion thereof. Until a first article quantity is accepted, the contractor is in no way authorized by the Government to resume regular production unless otherwise directed by the Contracting Officer.

4.3 Inspection provisions.

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision and complies with the provisions

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:39Z
Check the source to verify that this is the current version before use.

for submission of product as specified in MIL-STD-105. Changes to process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each inspection lot shall contain:

a. Metal parts assembly of one lot interfix number from one manufacturer.
b. Grenades from one lot interfix number from one manufacturer.
c. Warhead fuzes of one lot interfix number from one manufacturer.

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (See 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Bag (See Dwg. 8798070 covering a detail of Dwg 8798065).

Categories	Defects	Method of Inspection	Defect Code (See 6.2)
Critical: None defined			
Major: None defined			

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:39Z
Check the source to verify that this is the current version before use.

Minor	AQL 2.50 Percent		
201.	Length of closing flap	Gage	01001
202.	Angle improper	Gage	01002
203.	Small radius	Gage	01003
204.	Large radius	Gage	01004
205.	Evidence of poor workmanship (See 3.6)	Visual	01005

4.3.2.2 Bag and filler assembly (See dwg. 8798065 covering a detail of dwg. 8831168).

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	AQL 0.65 Percent		
101.	Cut or tear	Visual	02001
102.	Stitch broken or missing	Visual	02002
103.	Filler missing	Visual	02003
Minor	AQL 0.65 Percent		
201.	Evidence of poor workmanship (see 3.6)	Visual	02004

4.3.2.3 Assembly, prior to installing forward assembly (See dwg. 8831168).

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	AQL 1.00 Percent		
101.	Bag and filler assembly missing	Visual	03001
102.	Cable missing	Visual	03002
103.	Crimp sleeve of cable inadequate	Visual	03003
104.	Bulkhead plate loose	Visual	03004
105.	Cover sheet missing	Visual	03005
106.	Locking screw loose or missing	Manual-Visual	03006
Minor	AQL 0.65 Percent		
201.	Evidence of poor workmanship (See 3.6)	Visual	03007

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:39Z
Check the source to verify that this is the current version before use.

4.3.2.4 Assembly (See dwg. 8831168).

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	AQL 1.00 Percent		
101.	Weight	Balance	04001
102.	Concentricity and perpendicularity at first datum (base end) with mounting holes	Gage	04002
103.	Concentricity and perpendicularity at second datum with mounting holes	Gage	04003
104.	Concentricity and perpendicularity at third datum with mounting holes	Gage	04004
105.	Concentricity and perpendicularity at fourth datum with mounting holes	Gage	04005
106.	Concentricity and perpendicularity at fifth datum with mounting holes	Gage	04006
107.	Hardware bag torn	Visual	04007
108.	Hardware bag improperly secured	Visual	04008
Minor	AQL 1.50 Percent		
201.	Bare spots on exterior surface except for slight scratches	Visual	04009
202.	Marking, misleading or unidentifiable	Visual	04010
203.	Nose loose	Manual	04011
204.	Evidence of poor workmanship (See 3.6)	Visual	04012

4.3.2.5 Shipping and Storage Contr, Warhd Sect: M473 and M473A1 for 762MM Warheads Pkg and Mkg, prior to assembly of sides, ends, and top (See dwg. 8881082).

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:39Z
Check the source to verify that this is the current version before use.

Major	AQL 1.00 Percent		
101.	Nose strap missing	Visual	05001
102.	Bolt missing	Visual	05002
103.	Desicant bags missing or insecure	Visual	05003
104.	Barrier bag assembly torn or perforated	Visual	05004
105.	Humidity indicator missing	Visual	05005
106.	Bracket support loose	Visual	05006
107.	Fuze container missing	Visual	05007
Minor	AQL 1.50 Percent		
201.	Pad loose	Manual	05008
202.	Nose strap loose	Visual	05009
203.	Evidence of poor workmanship (See 3.6)	Visual	05010

4.3.2.6 Shipping and Storage Contr, Warhd Sect: M473 and M473A1 for 762MM Warheads Bkg and Mkg. (see dwg. 8881082).

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	AQL 0.65 Percent		
101.	Sides ends or top improperly assembled	Visual	06001
102.	Quicklock missing	Visual	06002
103.	Hardware missing or damaged	Visual	06003
Minor	AQL 2.5 Percent		
201.	Marking misleading or unidentifiable	Visual	06004
202.	Wood damaged or loose	Visual	06005
203.	Socket head screw key missing	Visual	06006
204.	Car seal missing or improperly secured	Visual	06007
205.	Evidence of poor workmanship (See 3.6)	Visual	06008

4.3.3 Testing

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:39Z
Check the source to verify that this is the current version before use.

4.3.3.1 Stability of bag and filler assembly (See 3.4 and dwg. 8798065), Major defect, Code No. 07001.-One (1) bag and filler assembly shall be selected from each batch of twenty-five (25) or less, prepared and subjected to this test. The filler for each batch shall be homogeneous and mixed at one time. Batches over twenty-five (25) shall be qualified by selecting one sample from each twenty-five (25) or portion thereof produced. If the foaming plastic fails to achieve requirements specified in 3.3, the batch represented by the failing sample shall be rejected and a sample from the next batch stored at -80°F shall be similarily tested. The test shall be performed as specified in 4.4.1.

4.3.3.2 Barrier bag, heat-sealed seam test (see 3.5 and dwg. 8881082) Major defect, Code No. 08001.-Sampling for this test shall be one coupon approximately 6" X 12" of barrier bag material, heat-sealed at the beginning of each lot, and one coupon heat-sealed at the end of each lot. If the heat-sealed sample at the beginning of the lot fails to meet the heat-sealed seam test requirement, production shall not begin until a satisfactory heat-seal has been accomplished. If the heat-sealed seam test fails on the sample heat-sealed at the end of the lot, the entire lot shall be rejected and all items in that lot shall be re-heat-sealed, including sample coupon. If second (2nd) heat-sealed seam test fails, entire lot shall be rejected. The test shall be performed as specified in 4.4.2.

4.3.3.3 Longitudinal center of gravity (see dwg. 8831168) Major defect, Code No. 09001.-Each warhead assembly shall be subjected to this test. If any warhead assembly fails to comply with the applicable requirement, the warhead assembly shall be classed defective and removed from the lot. The test shall be performed as specified in 4.4.3 using equipment in accordance with 4.3.4.

4.3.3.4 Lateral Center of gravity (See dwg. 8831168) Major Defect, Code No. 10001.-Each warhead assembly shall be subjected to this test. If any warhead assembly fails to comply with the applicable requirement, the warhead assembly shall be classed defective and removed from the lot. The test shall be performed as specified in 4.4.4 using equipment in accordance with 4.3.4.

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:39Z
Check the source to verify that this is the currentversion before use.

4.3.3.5 Check test for deterioration of bag and filler assembly, Major defect Code No. 11001.-If a batch, or portion thereof, has been stored for more than two (2) months, the test described in 4.4.1 shall be made prior to use in assembly. Sampling as in 4.3.3.1. If any bag and filler assembly fails to comply with requirements specified in 3.4, the lot represented by the sample tested shall not be used in production.

4.3.4 Inspection equipment.-Equipment Tabulation (ET) number 8831168 and Equipment Lists (EL's) referenced thereon identify the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3. Supply and maintenance of the equipment listed on the EL's shall be in accordance with MIL-I-45607.

4.3.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of this specification may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey, and whenever inspection equipment drawings are needed.

4.4 Test methods and procedures.

4.4.1 Stability of bag and filler assembly.-The sample selected shall be allowed to stand at room temperature (70-90°F) for not less than four (4) hours. It shall then be examined visually. This is a destructive test. Parts so tested shall not be returned to the lot.

4.4.2 Barrier bag, heat-sealed seam test.-The heat-sealed seam test shall be performed as specified in MIL-P-116, Section 4.4.4. Equipment shall be as specified on the Equipment List.

4.4.3 Longitudinal Center of gravity.-The loaded warhead assembly shall be mounted in a fixture listed on the Equipment list and tested for conformance to drawing requirements. This is a non-destructive test. Assemblies so tested shall be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:39Z
Check the source to verify that this is the currentversion before use.

4.4.4 Lateral center of gravity.-The loaded warhead assembly shall be mounted in a fixture listed on the Equipment List and tested for conformance to drawing requirements. This is a non-destructive test. Assemblies so tested shall be returned to the lot.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packing.

5.1.1 Level A.-Warhead Section, M144, shall be packed in accordance with Drawing 8881082.

5.2 Marking.-Marking shall be in accordance with Drawing 8881082 and Code of Federal Regulations, Title 49, Parts 171-179.

5.3 Shipping.-When assemblies from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.
c. Provisions for submission of first article samples.

6.2 Inspection code numbers.-The five-digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. These code numbers are also used to correlate the characteristics cited on Equipment Lists with the inspections listed in this specification. These code numbers shall be listed on drawings of equipment designs submitted by the contractor (see 6.3.5).

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the referenced Equipment Lists (EL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:39Z
Check the source to verify that this is the currentversion before use.

6.3.1 Equipment lists.-Equipment lists indicate the availability of inspection equipment designs by showing in the "Part Number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the "Part Number" column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications: Mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an equipment list references mandatory Army Designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, with the approval of the Government, design alternate inspection equipment to facilitate his operations. Such contractor-prepared designs (see 6.3.4) or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate, and operate an item of inspection equipment. This requires the the necessary views, dimensions, materials, finishes, notes and operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:39Z
Check the source to verify that this is the current version before use.

conform to Specification MIL-D-1000, Category E, Form 3. Legibility and reproducibility shall permit conventional making of clearly understandable, high-contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor design.-All submitted designs shall contain a reference to the applicable 5-digit code number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND13. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract. Submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished, normally, within one month after receipt.

6.4 Submission of results of contractor-conducted examinations and tests.-Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND3.

6.5 Supersession Data.-This specification includes the requirements of, and supersedes, Purchase Description PA-PD-1913 (Rev 1), dated 1 July 1960

Custodian:
Army-MU

Preparing activity:
Army-MU

Project Number: 1340-A

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:39Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
PICATINNY ARSENAL
DOVER, NEW JERSEY 07801

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

COMMANDING OFFICER
United States Army
Picatinny Arsenal
ATTN: SMUPA-ND
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:39Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:39Z
Check the source to verify that this is the current version before use.