MIL-S-4243C
AMENDMENT 2

22OCT82
Superseding
AMENDMENT 1
dated 29 May 1973

MILITARY SPECIFICATION
SHAVER, RIVET HEAD, PORTABLE, PNEUMATIC, MICROMETER ADJUSTMENT

This amendment forms a part of Military Specification MIL-S-4243C, dated 6 April 1965, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Para 1.2, Class 2, Change "1-1/8" to "3/4".

PAGE 2

Para 2.1:

1. Under "SPECIFICATIONS - Federal":

   (a) Delete QQ-P-416, TT-E-489, and TT-P-636 along with their titles.

   (b) Add:

   "QQ-N-290 Nickel Plating (Electrodeposited).

   QQ-C-320 Chrominum Plating (Electrodeposited).

   PPP-P-40 Packaging and Packing of Hand Tools."

2. Under "SPECIFICATIONS - Military", delete MIL-P-12829 along with its title.

3. Under "STANDARDS", add

   "Federal
   FED-STD-H28 Screw Thread
   Standards for
   Federal Services"

FSC 5130

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:27Z
Check the source to verify that this is the current version before use.

'ara 2.2:

.. Delete references to "National Bureau of Standards" publications
)f "Handbook H28".

2. Add:

(a) "OCCUPATIONAL SAFETY AND HEALTH ACT (OSHA) OF 1970
Occupational Safety and Health Administration Standards
(Applications for copies should be addressed to the
Superintendent of Documents, U.S. Government Printing
Office, Washington, D.C. 20402)."

(b) "AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)
S5.1 - Test Code for Measurement of Sound From Pneumatic Equipment
(Application for copies should be addressed to the American National
Standards Institute Inc., 1430 Broadway, New York, NY 10018)."

Add paragraph as follows:

"3.3.1 Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable."

id paragraph as follows:

"3.5.2 Safety standards. The equipment specified herein shall be in compliance with the applicable safety standards as specified in OSHA.

3.5.3 Sound pressure level. The sound pressure level shall not exceed 90Dba."

Para 3.12.1, on third line, delete "(see 6.2)" and insert ".".

In top right location on page, showing Figure 4, delete the table in its entirety and insert the following table:

Nominal Size A Diam	Carbide Tip Blank Size (Inches)	Required for Shaver Class 1	Class 2
5/16	1/8 X 1/4 X 5/16	X	X
3/8	1/8 X 1/4 X 3/8	X	X
7/16	1/8 X 1/4 X 7/16	X	X
1/2	1/8 X 1/4 X 1/2	X	X
9	1/8 X 1/4 X 9/16		X
5,	1/8 X 1/4 X 5/8		X
3/4	1/8 X 1/4 X 3/4		X

Source: https://assist.dla.mil -- Downloaded: 20260-17T03:27Z
Check the source to verify that this is the current version before use.

PAGE 10

Para 3.17, delete last sentence and insert "The carrying case shall have a handle that can be folded down, a hinged lid, and a latch for securing the lid in a closed position."

PAGE 11

Para 3.19, first line, delete "substantial" and insert "in compliance with dimensions".

Para 3.21, delete "Handbook H28" and insert "FED-STD-H28".

Para 3.22.1, delete first sentence and insert "Unpainted surfaces, except aluminum or magnesium, shall be either nickel plated in accordance with QQ-N-290, Class 1, Grade G, or chrome plated in accordance with QQ-C-320, Class 1, Type I or II, to a minimum thickness of 0.002 inches.

Para 3.22.3, delete entire paragraph and insert:

"3.22.3 Painting. The carrying case shall be painted inside and outside of a color that is optional to the producer."

PAGE 15

Para 4.5.2.1, delete entire paragraph and insert:

"4.5.2.1 Type II shavers. The type II shavers shall shave one (1) each of both mild ferrous and non-ferrous rivets of upset shank diameter sizes of 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, and 3/4 inches without stalling or chattering to determine compliance with 3.10."

Para 4.5.3, last sentence, delete "7/8" and insert "3/4".

After para 4.5.6, insert the following:

"4.5.7 Sound pressure level test. Sound pressure level test shall be conducted in accordance with the applicable provisions of ANSI S5.1, except as modified herein. The sound pressure level shall not exceed 90 decibels on the A weighted scale at any microphone location measured at an unobstructed distance of one meter.

4.5.7.1 Acoustical calibration. The entire instrumetation system shall be calibrated before each test series allowing a minimum instrument warm-up period of 5 minutes if transistorized and 1/2 hour if vacuum tube. Recalibration shall be performed if any instrument adjustment is necessary during progress of the test. All instrumentation (except microphone) and test personnel shall be as remotely located as practicable so that the measured data will be unaffected by a nonstationary observer."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:27Z
Check the source to verify that this is the current version before use.

TABLE XII. Instructions for testing of the end item

ara 5.1, third line, delete "MIL-P-12829" and insert "PPP-P-40."

nto para 6.2, add the following:

"i. Levels of preservation, packaging, packing and marking required see Section 5)."

dd paragraphs as follows:

"6.3 Rivets. Simulated rivets for compliance with requirements of .5.2.1, 4.5.3, and 4.5.4 may be manufactured from rod stock. Since he bucked end is the end to be shaved, the head shapes of these imulated rivets are optional to the manufacturer.

6.4 Item identification. The part number applicable to the item equired will be identified as follows:

M4243- -

Use 1 for Type I
2 for Type II

Use 1 for Class 1
or 2 for Class 2

6.5 Specification peculiarities. The peculiarieties involved with the .tems required by this specification are such as to limit usage by organizations)n equipment other than military; therefore, conversion of this specification .nto Commercial Item Descriptions (CID's) is unlikely to be feasible."

Custodians:
Air Force - 99
Navy - AS

Review Activity:
Army - GL

Preparing Activity:
Air Force - 84

Project Number:
5130-0299

Source: https://assist.dla.mil -- Downloaded: 20260-17T03:27Z
Check the source to verify that this is the current version before use.