NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND
MIL-PRF-6106/11C(USAF)
19 December 1989
SUPERSEDING
MIL-R-6106/11B(USAF)
17 MARCH 1986

PERFORMANCE SPECIFICATION SHEET

RELAY, ELECTROMAGNETIC, NORMALLY CLOSED, CONTINUOUS DUTY, 60 AMP, 3PST, ENVIRONMENTALLY SEALED

This specification is approved for use by the Department of the Air Force, and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the relay described herein shall consist of this specification and the latest issue of MIL-PRF-6106.





FIGURE 1. Relay, outline drawing.

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:22Z
Check the source to verify that this is the current version before use.



CIRCUIT 002 & 004 CIRCUIT 001 & 003

INCHES	mm	INCHES	mm	INCHES	mm
.005	0.13	.250	6.35	1.74	44.20
.010	0.25	.309	7.86	1.890	48.01
.02	0.51	.375	9.53	1.900	48.26
.028	0.71	.440	11.18	2.000	50.80
.032	0.81	.530	13.46	2.115	53.72
.063	1.60	.600	15.24	2.313	58.75
.148	3.76	.625	15.88	2.40	60.96
.186	4.72	1.000	25.40	2.500	63.50
.240	6.10	1.375	35.19	3.032	77.01

NOTES.
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.031 (0.79 mm)
4. Weights include cover, barriers, and terminal hardware.
5. When using relay at rated 60 amps, the use of lugs per Burndy part number YAEV6C-G8 or equal is recommended.
6. Terminal temperature rise under continuous current conditions is 95°C maximum.

FIGURE 1. Relay, outline drawing - Continued.

Source: https://assist.dla.mil -- Downloaded: 202610-17T06:22Z
Check the source to verify that this is the current version before use.

TABLE I Dash number and operating characteristics

Dash no	Type	Coil data: Coil	Nominal: Volts	Nominal: Freq	Nominal: Res	Maximum: Volts	Maximum: Ampere: Inrush	Maximum: Ampere: Steady state	Max pickup voltage 1/: Normal 1/	Max pickup voltage 1/: High Temp Test	Max pickup voltage 1/: Cont Current Test	Hold voltage 1/	Drop out voltage 1/	Time milliseconds - maximum: Operate 2/	Time milliseconds - maximum: Release 3/	Time milliseconds - maximum: Bounce: Main: NO	Main: NC	Auxiliary: NO	Auxiliary: NC
-001	I	X1, X2	28	DC	-	29	1 25	25	17	20	21 5	7 0	1 5	25	25	-	2	-	-
-002	I	X1, X2	28	DC	-	29	1 25	25	17	20	21 5	7 0	1 5	25	25	-	2	2	2
-003	I	X1, X2	115	400	-	124	.4	1	95	95	100	40	10	25	35	-	2	-	-
-004	I	X1, X2	115	400	-	124	4	1	85	95	100	40	10	25	35	-	2	2	2

1/ Over the temperature range. 2/ With nominal coil voltage. 3/ From nominal coil voltage.

TABLE II Rated contact load (amperes per pole) (case grounded).

Type of load	Life operating cycles x 10^3	28 V dc 1/: Main: NO	Main: NC	Auxiliary: NO	Auxiliary: NC	115 V ac, 1 phase 1/: Main: 400 Hz	Main: 60 Hz	Auxiliary: 400 Hz	Auxiliary: 60 Hz	115/200 V ac, 3 phase 1/: Main: 400 Hz	Main: 60 Hz	Auxiliary: 400 Hz	Auxiliary: 60 Hz
Resistive	100	-	-	3	3	60	-	3	-	60	-	-	-
Inductive	100	-	-	1 5	1 5	50	-	1.5	-	60	-	-	-
Motor	100	-	-	-	-	40	-	-	-	40	-	-	-
Lamp		-	-	5	5	20	-	5	-	20	-	-	-
Transfer load 2/													
Mechanical life reduced current	200	-	-	75	75	15	-	75	-	15	-	-	-
Minimum 3/ current	50	-	-	Per spec		4	-	-	-	4	-	-	-

1/ Absence of value indicates relay is not rated for that application

2/ Transfer load indicates relay suitable for transfer between unsynchronized ac power supplies at rating.

3/ Minimum current to be conducted at +71°C. Number of minimum current cycles following continuous current test - 5000.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:22Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Weight: 001 and 002 - 10 ounces maximum.
003 and 004 - 11 ounces maximum.

Temperature range -65°C to +71°C.

Maximum altitude rating. 50,000 feet 1/.

Shock g-level: 1/2 sine, 25 g's.

Duration: 6 to 9 ms.

Maximum duration contact opening: 1 ms.

Vibration-sinusoidal: See table III.

TABLE III. Vibration-sinusoidal.

Dash No.	Vibration level					
	5-10 Hz	10-55 Hz	55-400 Hz	400-800 Hz	800 - 2000 Hz	
					-55°C and 25°C	+71°C
-001	.08 DA	.06 DA	10 g's	10 g's	10 g's	7 g's
-002			10 g's	8 g's	8 g's	7 g's
-003			10 g's	10 g's	10 g's	7 g's
-004			10 g's	8 g's	8 g's	7 g's

Vibration (random): Not applicable.

Acceleration 15 g's.

Seal

Applicable specification MIL-STD-202, method 112, test condition C, procedure IV.

Leak rate: 6×10^{-4} STD cc/s 2/.

Terminal strength:

Applicable specification: MIL-STD-202, method 211, test condition E.

Torque 25 pound-inches.

Insulation resistance, initial: 200 megohms minimum

After life or enviromental tests: 100 megohms minimum.

1/ Application range can be extended to 80,000 feet by suitably encapsulating the terminals.
2/ During the test, pressure shall be reduced below 10 microns for a minimum of 10 seconds.

Source: https://assist.dla.mil -- Downloaded: 20261O-17T06:22Z
Check the source to verify that this is the current version before use.

Dielectric withstanding voltage (sea level): 2 to 5 seconds.

	Initial		After life tests	
	28 V dc	115 V ac	28 V dc	115 V ac
Coil to case	1250	1500	1000	1125
Auxiliary contacts	1250	1250	1000	1000
Across open power contacts	---	1250	---	625
All other points	1800	1800	1350	1350

Dielectric withstanding voltage (altitude): 1 minute.

	28 V dc	115 V ac
Coil to case	500	500
Auxiliary contacts	500	500
All other points	700	700

Maximum contact drop, initial: .150 volt.

After life test: .200 volt.

Overload current 3/: 320 amperes.

Rupture current: 400 amperes.

Duty rating: Continuous.

RFI specification (applicable to coil circuits of ac operated relays): MIL-STD-461 and MIL-STD-462.

Part number: M6106/11- (dash number from table I).

TABLE IV. Qualification by similarity.

Dash number	Loads						Dynamics 1/			Environmental 2/		
	Type I			Type I ER								
	A	B	C	D	E	F	A	X	Y	A	B	C
-001	4						2			4		
-002	4 2/						2			4		
-003		1						1			1	
-004		1 2/						1			1	

1/ All units must be tested, reference the appendix of MIL-R-6106, construction, internal.
2/ Test unit with auxiliary contacts, reference the appendix of MIL-R-6106, construction, internal.

3/ Number of rupture cycles after minimum current test - 5.

Source: https://assist.dla.mil -- Downloaded: 202610-17T06:22Z
Check the source to verify that this is the current version before use.

Custodian:
Air Force - 85

Review activities:
Air Force - 11, 99
DLA - ES

Preparing activity
Air Force - 85

Agent:
DLA - ES

(Project 5945-F703-03)

Source: https://assist.dla.mil -- Downloaded: 202640-17T06:22Z
Check the source to verify that this is the current version before use.