INCH-POUND

MIL-PRF-6106/11G
29 August 2025
SUPERSEDING
MIL-PRF-6106/11F
24 July 2020

PERFORMANCE SPECIFICATION SHEET

RELAY, ELECTROMAGNETIC, NORMALLY CLOSED, CONTINUOUS DUTY, 60 AMP, 3PST, ENVIRONMENTALLY SEALED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the relay described herein shall consist of this specification and the latest issue of MIL-PRF-6106.





FIGURE 1. Relay, outline drawing.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:22Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm	Inches	mm
.005	0.13	.250	6.35	1.74	44.20
.010	0.25	.309	7.86	1.890	48.01
.02	0.51	.375	9.53	1.900	48.26
.028	0.71	.440	11.18	2.000	50.80
.032	0.81	.530	13.46	2.115	53.72
.063	1.60	.600	15.24	2.313	58.75
.148	3.76	.625	15.88	2.40	60.96
.186	4.72	1.000	25.40	2.500	63.50
.240	6.10	1.375	35.18	3.032	77.01

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.031 (0.79 mm).
4. Weights include cover, barriers, and terminal hardware.
5. When using relay at rated 60 amps, the use of lugs per Burndy part number YAEV6C-G8 or equal is recommended.
6. Terminal temperature rise under continuous current conditions is 95°C maximum.

FIGURE 1. Relay, outline drawing - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:22Z
Check the source to verify that this is the current version before use.

TABLE I. Dash number and operating characteristics.

Dash no.	Type	Coil data												Time milliseconds-maximum					
		Coil	Nominal			Maximum			Max pickup voltage 1/			Hold voltage 1/	Drop out voltage 1/	Operate 2/	Release 3/	Bounce			
			Volts	Freq	Res	Volts	Ampere		Normal 1/	High temp test	Cont current test					Main		Auxiliary	
							Inrush	Steady state								NO	NC	NO	NC
-001	1	X1, X2	28	DC	-	29	1.25	.25	17	20	21.5	7.0	1.5	25	25	-	2	-	-
-002	1	X1, X2	28	DC	-	29	1.25	.25	17	20	21.5	7.0	1.5	25	25	-	2	2	2
-003	1	X1, X2	115	400	-	124	.71	.1	85	95	100	40	10	55	35	-	2	-	-
-004	1	X1, X2	115	400	-	124	.71	.1	85	95	100	40	10	55	35	-	2	2	2

1/ Over the temperature range 2/ With nominal coil voltage 3/ From nominal coil voltage

TABLE II. Rated contact load (amperes per pole) (case grounded).

Type of load	Life operating cycles $x10^3$	28 V dc 1/				115 V ac, 1 phase 1/				115/200 V ac, 3 phase 1/			
		Main		Auxiliary		Main		Auxiliary		Main		Auxiliary	
		NO	NC	NO	NC	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz
Resistive	100	-	-	3	3	60	-	3	-	60	-	-	-
Inductive	100	-	-	1.5	1.5	60	-	1.5	-	60	-	-	-
Motor	50	-	-	-	-	40	-	-	-	40	-	-	-
Lamp		-	-	.5	.5		-	.5	-		-	-	-
Transfer load 2/		-	-				-		-		-	-	-
Mechanical life reduced current	200	-	-	.75	.75	15	-	.75	-	15	-	-	-
Mixed loads 3/	50	-	-	Per spec		4	-	-	-	4	-	-	-

1/ Absence of value indicates relay is not rated for that application.
2/ Transfer load indicates relay suitable for transfer between unsynchronized ac power supplies at rating.
3/ Mixed loads to be conducted at +71°C. Number of mixed loads cycles following continuous current test - 5000.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:22Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Weight: 001 and 002: 10 ounces maximum.
003 and 004: 11 ounces maximum.

Temperature range: -55°C to +71°C.

Maximum altitude rating: 50,000 feet. 1/

Shock g-level: .5 sine, 25 g's.

Duration: 6 to 9 ms.

Maximum duration contact opening: 1 ms.

Vibration-sinusoidal: See table III.

TABLE III. Vibration-sinusoidal.

Dash No.	Vibration level					
	5-10 Hz	10-55 Hz	55-400 Hz	400-800 Hz	800 - 2000 Hz	
					-55°C and 25°C	+71°C
-001	.08 DA	.06 DA	10 g's	10 g's	10 g's	7 g's
-002			10 g's	8 g's	8 g's	7 g's
-003			10 g's	10 g's	10 g's	7 g's
-004			10 g's	8 g's	8 g's	7 g's

Vibration (random): Not applicable.

Acceleration: 15 g's.

Seal:

Applicable specification: MIL-STD-202-112, test condition C, procedure IV.

Leak rate: $6x10^{-4}$ std cc/s.

Strength of terminals and mounting studs:

Torque:

Main terminals: 24 inch-pounds maximum, 18 inch-pounds recommended installation torque.

Auxiliary terminals: 4.4 inch-pounds maximum, 3.3 inch-pounds recommended installation torque.

Insulation resistance, initial: 200 megohms minimum.

After life or environmental tests: 100 megohms minimum.

1/ Application range can be extended to 80,000 feet by suitably encapsulating the terminals.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:22Z
Check the source to verify that this is the current version before use.

Dielectric withstanding voltage (sea level): 2 to 5 seconds.

	Initial		After life tests	
	28 V dc	115 V ac	28 V dc	115 V ac
Coil to case	1,250	1,500	1,000	1,125
Auxiliary contacts	1,250	1,250	1,000	1,000
Across open power contacts	1,250	1,250	625	625
All other points	1,800	1,800	1,350	1,350

Dielectric withstanding voltage (altitude): 1 minute.

	28 V dc	115 V ac
Coil to case	500	500
Auxiliary contacts	500	500
All other points	700	700

Maximum contact drop, initial: .150 volt.

After life test: .200 volt.

Overload current: 320 amperes (ac). 1/

Rupture current: 400 amperes (ac).

Duty rating: Continuous.

RFI specification (applicable to coil circuits of ac operated relays): MIL-STD-461.

Part number. M6106/11- (dash number from table I).

Qualification by similarity: See MIL-PRF-6106.

Referenced documents. In addition to MIL-PRF-6106, this document references the following:

MIL-STD-202-112 MIL-STD-461

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

1/ Number of rupture cycles after mixed loads test: 5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:22Z
Check the source to verify that this is the current version before use.

Custodians:
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-2025-036)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:22Z
Check the source to verify that this is the current version before use.