NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND

MIL-PRF-6106/13D
AMENDMENT 3
10 July 1999
SUPERSEDING
AMENDMENT 2
26 May 1989

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, 25 AMPERE, 3PST, NO, WITH 2 AMPERE,
1PDT AUXILIARY CONTACTS, HERMETICALLY SEALED,
PERMANENT MAGNET DRIVE, TYPE I

This amendment forms a part of MIL-PRF-6106/13D, dated 26 November1986, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 6

* FIGURE 5, delete “Silicone Rubber Gasket AMS 3332 Shore Hardness 20 ±5 Thickness .050 ±.005” and substitute “See Note 6”

* FIGURE 5, delete “Finish: Gold Plate MIL-G-45204 Type II, Class I All Pins Except Polarizing Pin-Underplating, Nickel 50 to 150 Microinches Thick” and substitute “See note 5”

* Add a Note 5, “5. Socket pin terminals shall provide the operational, environmental, and interface characteristics to provide a reliable interconnect to gold-plated contacts. Terminals shall be gold plated, except the polarizing pin. One system for gold plating that may be used is ASTM B488, type 3, class 1.25 with a nickel underplate of 50 to 150 microinches thick. The gold plating system shall enable the product to meet the performance requirements of this specification and shall be approved by the qualifying activity.”

* Add a Note 6, “6. Gasket shall provide a reliable seal between the relay and mating socket that will meet the environmental, operational, and interface requirements of the relay with the mating socket. The gasket shall have shore hardness 20 ±5, thickness .050 ±.005. Gasket material according to AMS 3332 has been considered acceptable.”

PAGE 9

Shock G-level: Delete "200 G, 100 G for -006 and -009 only" and substitute "200 G, 100 G for -006, -009, and -018 only".

Vibration - sinusoidal, delete in its entirety and substitute:

"Vibration - sinusoidal:

G-level: 30 G, 20 G for -006, -009, and -018 only.

Frequency range: 10 to 3,000 Hz."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.

Vibration - random, delete in its entirety and substitute:

"Vibration - random:

Applicable standard: MIL-STD-202, method 214.

Test condition: IG, IE for -006, -009, and -018 only.

Power spectral density: 0.4 G^2/Hz, 50 to 2,000 Hz (0.2 G^2/Hz for -006, -009, and -018 only).

Duration: 15 minutes, each plane."

PAGE 11

Footnote 4/, delete in its entirety and substitute: "For -005, -006, and -017, relays shall be tested to group A, type I, ER screening requirements only, additional life testing is not required. The alternate low level method shall be used."

The margins of this amendment are marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-1058-04)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.