INCH-POUND


MIL-PRF-6106/13F
17 November 2011
SUPERSEDING
MIL-PRF-6106/13E
10 November 2000

PERFORMANCE SPECIFICATION

RELAY, ELECTROMAGNETIC, 25 AMPERE, 3PST, NO, WITH 2 AMPERE 1PDT AUXILIARY CONTACTS, HERMETICALLY SEALED, PERMANENT MAGNET DRIVE, TYPE I

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the relays described herein shall consist of this specification sheet and MIL-PRF-6106.



RAISED VERTICAL FLANGE MOUNT I AND TERMINAL LAYOUT
FOR -001, -002, -003, -005, -007, -008, -016 AND -017

FIGURE 1. Relay, outline drawing.


Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	Mm
.000	0.00	.150	3.81	.625	15.88
.001	0.03	.156	3.96	.630	16.00
.002	0.05	.234	5.94	.937	23.80
.003	0.08	.300	7.62	1.010	25.65
.020	0.51	.312	7.92	1.025	26.04
.040	1.02	.395	10.03	1.396	35.46
.062	1.57	.432	10.97	1.446	36.73
.093	2.36	.450	11.43	1.718	43.64
.117	2.97	.600	15.24		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.010 (0.25 mm).

FIGURE 1. Relay, outline drawing - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.




RAISED VERTICAL FLANGE MOUNT 2 AND TERMINAL LAYOUT FOR -004

Inches	mm	Inches	mm	Inches	mm
.000	0.00	.150	3.81	.600	15.24
.001	0.03	.156	3.96	.625	15.88
.002	0.05	.234	5.94	.630	16.00
.020	0.51	.300	7.62	.937	23.80
.040	1.02	.312	7.92	1.010	25.65
.062	1.57	.395	10.03	1.025	26.04
.093	2.36	.432	10.97	1.396	35.46
.117	2.97	.450	11.43	1.446	36.73
				1.718	43.64

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.010 (.25 mm).

FIGURE 2. Relay, outline drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.




HORIZONTAL FLANGE MOUNT 3 AND TERMINAL LAYOUT FOR –006, -009 AND –018.

Inches	mm	Inches	mm	Inches	mm
.001	0.03	.150	3.81	.625	15.88
.002	0.05	.234	5.94	.630	16.00
.003	0.08	.300	7.62	.937	23.80
.040	1.02	.312	7.92	1.010	25.65
.062	1.57	.432	10.97	1.025	26.04
.093	2.36	.450	11.43	1.396	35.46
.117	2.97	.600	15.24	1.446	36.73
				1.718	43.64

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.010 (.25 mm).

FIGURE 3. Relay, outline drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.




NO MOUNT 4 AND TERMINAL LAYOUT FOR -010, -011, -012, -013, -014, AND -015.

Inches	mm	Inches	mm
.001	0.03	.234	5.94
.002	0.05	.300	7.62
.003	0.08	.432	10.97
.062	1.57	.450	11.43
.093	2.36	.600	15.24
.117	2.97	.630	16.00
.150	3.81	1.010	25.65
		1.025	26.04

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.010 (.25 mm).

FIGURE 4. Relay, outline drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.



SOLDER PIN TERMINALS


Inches	mm	Inches	mm	Inches	mm
.000	0.00	.020	0.51	.250	6.35
.001	0.03	.040	1.02	.270	6.86
.002	0.05	.050	1.27	.300	7.62
.003	0.08	.062	1.57	.375	9.52
.005	0.13	.093	2.36	.625	15.88

NOTES:


1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.010 (0.25 mm).
4. Hook terminals will accept (1) one number 12 AWG stranded wire.
5. Socket pin terminals shall provide the operational, environmental, and interface characteristics to provide a reliable interconnect to gold-plated contacts. Terminals shall be gold plated, except the polarizing pin. One system for gold plating that may be used is ASTM B488, type 3, class 1.25 with a nickel underplate of 50 to 150 microinches thick. The gold plating system shall enable the product to meet the performance requirements of this specification and shall be approved by the qualifying activity.
6. Gasket shall provide a reliable seal between the relay and mating socket that will meet the environmental, operational, and interface requirements of the relay with the mating socket. The gasket shall have shore hardness 20 ±5, thickness .050 ±.005. Gasket material according to SAE-AMS3332 has been considered acceptable.

FIGURE 5. Relay, termination styles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.



MOUNTING HOLE LAYOUT FOR FIGURE 1




MOUNTING HOLE LAYOUT FOR FIGURES 2 AND 3

Inches	mm	Inches	mm
.001	0.03	.218	5.54
.005	0.13	.312	7.92
.062	1.57	.625	15.88
.156	3.96	1.062	26.97
.172	4.37	1.406	35.71


NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.010 (.25 mm).

FIGURE 6. Relay, mounting hole layouts.


Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.



CIRCUIT DIAGRAM
MONOSTABLE
FOR -003,-004,
-012 AND -013
SEE NOTE 3



CIRCUIT DIAGRAM
POLARIZED MONOSTABLE
FOR -007,-008,
-014,-015,-016,-017 AND -018
SEE NOTES 2 AND 3



CIRCUIT DIAGRAM
POLARIZED MONOSTABLE
FOR -001,-002,
-005,-006,-009,
-010 AND -011
SEE NOTE 2

NOTES:

1. There shall be affixed to the relay a suitable legible circuit diagram that identifies each terminal location specified.
2. DC versions of this relay must not operate or be damaged by reverse polarity, semiconductors shall not be used for this purpose.
3. Coil polarity not applicable to AC versions -003, -004, -012, and -013.
4. When semiconductors are required, JANTX or equivalent screened semiconductors shall be used. Relays using suppression devices shall continue to operate should the suppression circuit be in a failure mode. Diodes shall have a peak inverse voltage of 600 V dc minimum.

FIGURE 7. Relay, circuit diagrams.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Coil data:

Coil data: See table I.

Duty rating: Continuous.

Operational data:

Rated contact load: See table II.

Operate time: See table I.

Release time: See table I.

Physical:

Dimensions and configuration: See figure 1 through 6.

Weight (maximum): 0.18 pound, 81.64 grams.

Thermal type: See figure 5 and table I.

Strength of terminals and mounting studs: Applicable.

Terminal solderability: Applicable to solder pin and solder hook terminals only.

ENVIRONMENTAL CHARACTERISTICS:

Temperature range: -70°C to +125°C. 1/

Maximum altitude: 300,000 feet.

Shock g-level: 200 g, 100 g for -006, -009, and -018 only. 2/

Duration: 6 ms.

Maximum duration contact opening: Deleted.

Vibration-sinusoidal: 2/

G level: 30 g, 20 g for -006, -009, and -018 only.

Frequency range: 10 to 3,000 Hz.

Vibration (random): 2/

Applicable standard: MIL-STD-202, method 214.

Test condition: IG, IE for -006, -009, and -018 only.

1/ For full rated load, maximum temperature, and altitude use no. 12 wire or larger. Solder hook relays are to be mounted to limit mounting bracket temperature to 160°C for dc units and 135°C for ac units.

2/ There shall be no opening of closed auxiliary contacts in excess of 1 ms, no closure or bridging of open auxiliary contacts in excess of 100 µs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.

Power spectral density: 0.4 G^2/Hz, 50 to 2,000 Hz (0.2 G^2/Hz) for -006, -009, and -018 only.

Duration: 15 minutes, each plane.

Acceleration: 15 g's. 2/

ELECTRICAL CHARACTERISTICS:

Insulation resistance, initial: 100 megohms.

After life or environmental tests: 50 megohms.

Dielectric withstanding voltage (seal level): 2 to 5 seconds.

	Initial	After life tests
Coil to case	1,000 V rms	1,000 V rms
Auxiliary contacts	1,000 V rms	750 V rms
All other points	1,250 V rms	1,000 V rms

Dielectric withstanding voltage (altitude): 1 minute. 3/

	80,000 feet	300,000 feet
Coil to case	350 V rms	500 V rms
Auxiliary contacts	350 V rms	500 V rms
All other points	350 V rms	500 V rms

Maximum contact drop, initial: 0.150 volt.

After life test: 0.175 volt.

Overload current: 50 amperes dc, 80 amperes ac.

Rupture current: 60 amperes dc, 100 amperes ac.

RFI specification (applicable to coil circuits of ac operated relays): MIL-STD-461.

Part Number: M6106/13-(dash number from table I).

Qualification by similarity: See MIL-PRF-6106.

3/ Dielectric rating may be improved by suitable insulation of terminals and wiring after installation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.

TABLE I. Mounting, termination, and operating characteristics.

Dash No.	Coil terminal	Coil data									Time (milliseconds) (max)						Terminals	Mount figure
		Nominal			Maximum		Max pickup voltage			Drop out voltage	Hold voltage	Operate 2/	Release 3/	Bounce				
														Main		Aux		
		Volts	Freq Hz	Res	Volts	Amp	Normal 1/	High temp test	Cont. curr test					NO	NC	NO	NC	
-001	DC	28	DC	-	29	.12	18	19.8	22.5	1.5	7.0	15	15	1.0	-	4	4	Solder-hook	1
-002																		Socket plug-in	1
-005 4/																		Solder pin	1
-006 4/																		Solder pin	3
-009																		Solder-hook	3
-010																		Solder pin	4
-011																		Socket plug-in	4
-003	AC	115	400	-	122	.04	90	95	103	5	30	20	50	1.0	-	4	4	Solder-hook	1
-004																		Socket plug-in	2
-012																		Solder pin	4
-013																		Socket-plug-in	4
-007 5/	DC	28	DC	-	29	.12	18	19.8	22.5	1.5	7.0	15	15	1.0	-	4	4	Solder-hook	1
-008 5/																		Socket plug-in	1
-014 5/																		Solder pin	4
-015 5/																		Socket plug-in	4
-016 5/																		Solder pin	1
-017 4/ 5/																		Solder pin	1
-018 5/																		Solder-hook	3

1/ Over temperature range.
2/ With nominal coil voltage.
3/ From nominal coil voltage.
4/ For -005, -006, and -017, relays shall be tested to group A, type 1, ER screening requirements only, additional life testing, is not required. The alternate low level method shall be used.
5/ Coil suppression (transient voltage back EMF) 42 V dc maximum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.

TABLE II. Rated contact load (amperes per pole) (case grounded).

Type of load	Life operating cycles x 10^3	28 V dc				115 V ac, 1 phase				115/200 V ac, 3 phase 1/			
		Main		Aux		Main		Aux		Main		Aux	
		NO	NC	NO	NC	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	50 Hz	400 Hz	60 Hz
Resistive 2/	50	25		2	2	25		2		25			
Inductive	10	12		1	1								
Inductive	20					15		1		15			
Motor	50	10				10				10			
Lamp	50	5		.5	.5	5		.5		5			
Transfer load 3/													
Mechanical life reduced current	200	6				6				6			
Intermediate current	Applicable per specification (main contacts only)												
Mixed loads	Applicable per specification												

1/ Absence of value indicates relay is not rated for 3 phase application.
2/ For full rated load, maximum temperature, and altitude use no. 12 wire or larger. Solder hook relays to be mounted to limit mounting bracket temperature to 160°C for dc units and 135°C for ac units.
3/ Transfer load indicates relay suitable for transfer between unsynchronized ac power supplies at rating indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Referenced documents. In addition to MIL-PRF-6106, this document references the following:

ASTM-B488 SAE-AMS3332 MIL-STD-202 MIL-STD-461

Custodian:
Air Force - 85
DLA-CC

Preparing activity:
DLA - CC

(Project 5945-2011-063)

Review activities:
Air Force - 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.