INCH-POUND

MIL-PRF-6106/20C
AMENDMENT 1
19 July 2001

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, MAGNETIC LATCH, 25 AMPERES, SPDT, HERMETICALLY SEALED

This amendment forms a part of MIL-PRF-6106/20C, dated 10 November 2000, and is approved for use by all Departments and Agencies of the Department of Defense.

The attached insertable replacement page is listed below and is a replacement for the stipulated page. When the new page has been entered in the document, insert the amendment as the cover sheet to the specification.

Replacement page	Page replaced
5	5

Custodians:
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-1137-01)

Review activities:
Air Force - 99

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:25Z
Check the source to verify that this is the current version before use.

Maximum contact drop, initial: 0.150 volt.

After life test: 0.175 volt.

Overload current: 50 amperes dc, 80 amperes ac, 400 Hz.

Rupture current: 60 amperes dc, 100 amperes ac, 400 Hz.

Duty rating: Continuous.

Part or Identifying Number (PIN): M6106/20- (plus dash number from table I). Example: M6106/20-001.

Qualification by similarity: See MIL-PRF-6106.

TABLE I. Dash numbers and characteristics.

Dash numbers	Coil data								Time-milliseconds maximum 1/				Term-inal type	Mount-ing style
	Coil	Nominal		Max		Max pick-up voltage			Ope-rate	Re-set	Bounce			
											Main			
		Volts (V dc) 2/	Res Ω ±10%	Volts	Amp	Nom-inal 3/	High temp test	Cont cur-rent test			NO	NC		
-001	X1-X2 Y1-Y2	28	600	29	.050	18	19.8	22.5	10	10	1.0	1.0	Solder hook	RVFM
-002	X1-X2 Y1-Y2	28	600	29	.050	18	19.8	22.5	10	10	1.0	1.0	Plug-in	RVFM
-003	X1-X2 Y1-Y2	28	600	29	.050	18	19.8	22.5	10	10	1.0	1.0	Solder hook	HFM

1/ With nominal coil voltage.
2/ Caution: Use of any coil voltage less than nominal coil voltage will compromise the operation of the relay.
3/ Over temperature range.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:25Z
Check the source to verify that this is the current version before use.