INCH-POUND

MIL-PRF-6106/20C
AMENDMENT 2
15 November 2002
SUPERSEDING
AMENDMENT 1
19 July 2001

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, MAGNETIC LATCH, 25 AMPERES, SPDT, HERMETICALLY SEALED

This amendment forms a part of MIL-PRF-6106/20C, dated 10 November 2000, and is approved for use by all Departments and Agencies of the Department of Defense.

The attached insertable replacement page is listed below and is a replacement for the stipulated page. When the new page has been entered in the document, insert the amendment as the cover sheet to the specification.

Replacement page	Page replaced
5	5

PAGE 7

* Add paragraph at top of page: "Suspension of inspection. Group B and Group C inspections may be suspended at the discretion of the qualifying activity."

The margins of this amendment are marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-1194-21)

Review activities:
Air Force - 99

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:25Z
Check the source to verify that this is the current version before use.

Maximum contact drop, initial: 0.150 volt.

After life test: 0.175 volt.

Overload current: 50 amperes dc, 80 amperes ac, 400 Hz.

Rupture current: 60 amperes dc, 100 amperes ac, 400 Hz.

Duty rating: Continuous.

Part or Identifying Number (PIN): M6106/20- (plus dash number from table I). Example: M6106/20-001.

Qualification by similarity: See MIL-PRF-6106.

TABLE I. Dash numbers and characteristics.

Dash numbers	Coil data								Time-milliseconds maximum 1/				Term-inal type	Mount-ing style
	Coil	Nominal		Max		Max pick-up voltage			Ope-rate	Re-set	Bounce			
		Volts (V dc) 2/	Res Ω ±10%	Volts	Amp	Nom-inal 3/	High temp test	Cont cur-rent test			Main			
											NO	NC		
-001	X1-X2 Y1-Y2	28	600	29	.050	18	19.8	22.5	10	10	1.0	1.0	Solder hook	RVFM
-002	X1-X2 Y1-Y2	28	600	29	.050	18	19.8	22.5	10	10	1.0	1.0	Plug-in	RVFM
-003	X1-X2 Y1-Y2	28	600	29	.050	18	19.8	22.5	10	10	1.0	1.0	Solder hook	HFM

1/ With nominal coil voltage.
2/ Caution: Use of any coil voltage less than nominal coil voltage will compromise the operation of the relay.
3/ Over temperature range.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:25Z
Check the source to verify that this is the current version before use.