INCH-POUND

MIL-R-6106/14C
10 November 2000
SUPERSEDING
MIL-R-6106/14B
10 March 1989

MILLITARY SPECIFICATION SHEET

RELAY, ELECTRIC, PERMANENT DRIVE, 50 AMP, SPDT (DB) DOUBLE MAKE DOUBLE BREAK AUXILIARY CONTACTS (5 AMP), HERMETICALLY SEALED

Inactive for new design after 10 March 1989. No superseding specification sheet.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the relay described herein shall consist of this specification and the latest issue of MIL-PRF-6106.






FIGURE 1. Relay, outline drawing.

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.



AXIS DESCRIPTION
ACCELERATION



CIRCUIT DIAGRAM

Inches	mm	Inches	mm	Inches	mm
.045	1.14	.30	7.62	1.250	31.75
.055	1.40	.31	7.87	1.300	33.02
.06	1.52	.312	7.92	1.406	35.71
.100	2.54	.32	8.13	1.500	38.10
.170	4.32	.380	9.65	2.000	50.80
.218	5.54	.40	10.16	2.100	53.34
.22	5.59	.500	12.70	2.400	60.96
.224	5.69	.600	15.24	2.750	69.85
.250	6.35	.625	15.88	3.400	86.36
		1.200	30.48		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance are ±.010 (0.25 mm) for three place decimals and ±.03 (0.8 mm) for two place decimals.
4. The main contact terminals shall be designed so that two number 6 MS25036 terminal lugs may be attached back to back on each terminal without contacting the relay case.
5. Terminal protection: The relay shall have a terminal cover with integral barriers.
6. Repairability: All functional parts shall be capable of being removed and replaced.
7. Shelf life: The unit shall have a shelf life of 5 years, providing that the unit is cycled 25 times at rated inductive load in accordance with MIL-PRF-6106 before use in the aircraft.
8. Terminal numbers need not appear on relay headers, provided a legible circuit diagram is affixed to the relay that positively and permanently identifies each terminal.
9. Coil and auxiliary contact pins shall have equivalent positions to those of MS27400-2.

FIGURE 1. Relay, outline drawing - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Coil data:

Coil data: See table I.

Duty rating: Continuous.

Operational data:

Rated contact load: See table II.

Operate time: See table I.

Release time: See table I.

Physical:

Dimensions and configuration: See figure 1.

Weight (maximum): 1.25 pounds, 567 grams.

Terminal type: See figure 1.

Strength of terminals and mounting studs: Applicable.

ENVIRONMENTAL CHARACTERISTICS:

Temperature rating: -54°C to +74°C.

Maximum altitude: 30,000 feet.

Shock g-level: 6 g.

Duration: 11 ±1 milliseconds.

Crash safety g-level: 15 g, one impact in each direction.

Duration: 11 ±1 milliseconds.

Vibration-sinusoidal:

G-level: .036 inch double amplitude to 50 Hz, thereafter 4.5 g.

Frequency range: 5 Hz to 2,000 Hz.

Vibration-random: Not applicable.

Acceleration: See figure 1.

X plane: +1.3 g.

Y plane: ±2.5 g.

Z plane: 7.1 g down, 3.7 g up.

Duration: 15 seconds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.

ELECTRICAL CHARACTERISTICS:

Magnetic effect: A magnetic compass with a horizontal intensity of 0.18 ±0.1 gauss shall have its needle deflected 5° or less when the relay is energized or deenergized.

Voltage transient:

Generation: No greater than 70 volts, decreasing to 50 volts within 20 milliseconds and to 10 volts within 40 milliseconds.

Insulation resistance, initial: 100 megohms.

After life or environmental tests: 50 megohms.

Dielectric withstanding voltage (sea level):

	Initial	After life tests
Coil to case	1250 V rms, 60 Hz	1250 V rms, 60 Hz
Auxiliary contacts	1500 V rms, 60 Hz	1250 V rms, 60 Hz
All other points	1500 V rms, 60 Hz	1250 V rms, 60 Hz

Dielectric withstanding voltage (altitude): Not applicable.

Maximum contact drop, initial: 0.150 volt.

After life tests: 0.175 volt.

Overload current: Not applicable.

Rupture current: 400 amperes dc (3 V dc maximum voltage drop).

RFI specification (applicable to coil circuits of ac operated relays): Not applicable.

Part or identifying number (PIN): M6106/14-001.

Qualification testing: Qualification testing shall be in accordance with MIL-PRF-6106, table VIII. No qualification testing is required for sample numbers 1, 2, 4, 9, or 12. Sample 7 shall have humidity test added between steps 4 and 5. Sample 11 shall have the magnetic effect and voltage transient generation tests, specified by this specification sheet performed between steps 4 and 5. Sample 6 shall not require sand and dust, vibration, or minimum current testing.

Retention of qualification: To retain qualification, the manufacturer shall submit group A acceptance reports on a yearly basis to the qualifying activity.

Quality conformance inspection: Performance of groups B and C tests are not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.

TABLE I. Operating characteristics.

Dash No	Type	Coil data											Time (milliseconds-maximum)					
		Coil	Nominal			Max		Max pick-up voltage			Hold voltage 2/	Drop out voltage 2/	Oper-ate	Re-lease	Bounce			
			Volts 1/	Freq. Hz	Res. Ω	Volts	Amp-eres	Norm 2/	High temp test	Cont. curren t test					Main		Aux	
															NO	NC	NO	NC
-001	I	X1, X2	28	dc		30	0.6	18	19.8	22.5	7.0	1.5	25	10				

1/ CAUTION: Use of any coil voltage less than nominal coil voltage will compromise the operation of the relay.
2/ Over the temperature range.
3/ With nominal coil voltage.
4/ From nominal coil voltage.

TABLE II. Rated contact load (amperes per pole) case grounded.

Type of load	Life operating cycles X 10^3	28 V dc				115 V ac, 1 phase				115/200 V ac, 3 phase 1/				See appropriate notes
		Main		Aux		Main		Aux		Main		Aux		
		NO	NC	NO	NC	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz	
Resistive	50	50	50	5	5									
Inductive	30	25	25	5	5									
Motor														
Lamp	50	10	10	.5	.5									
Transfer load														2/
Mechanical life reduced current	100	12.5	12.5											
Mixed loads														

1/ Absence of value indicates relay is not rated for 3-phase applications.
2/ Transfer load indicates relay suitable for transfer between unsynchronized ac power supplies at rating indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.

Custodian:
Air Force - 11
DLA - CC

Review activities:
Air Force - 99

Preparing activity:
DLA - CC

(Project 5945-1113-06)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:23Z
Check the source to verify that this is the current version before use.