MIL-D-12957C (PA)
31 January 1974
SUPERCEDING
MIL-D-12957B (MU)
20 July 1971

MILITARY SPECIFICATION

DESTRUCTOR, HE, UNIVERSAL, M10 ASSEMBLY PARTS, LOADING, ASSEMBLING AND PACKING

*This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the parts, loading, assembling and packing for one type of destructor designated as Destructor, HE, Universal, M10 Assembly.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition, General Specification For

STANDARDS

FEDERAL

FED-STD-151 - Metals, Test Methods

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-650 - Explosive: Sampling, Inspection and Testing
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

9216189 - Destructor, HE, Universal, M10 Assembly
9215526 - Container, Ammunition, Fiber, M346, for Destructor, HE, Universal, M10
9215527 - Box, Packing, Ammunition for Destructor, HE, Universal, M10

PUBLICATIONS

*AMERICAN SOCIETY FOR TESTING MATERIALS

ASTM-A575-67-T - Merchant Quality Hot Rolled Carbon Steel Bars

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

3. REQUIREMENTS

3.1 Material. - The material and parts shall be in accordance with the applicable drawings and specifications.

3.2 The Destructor, HE, Universal, M10, Assembly shall comply with all requirements specified on Drawing (dwg) 9216189 and all drawings referenced thereon, and with all requirements specified in applicable specifications.

3.3 Functioning. - Detonation of the destructor shall cause an indentation of 0.1 inch, minimum (min), depth at the deepest point and a diameter of 1.25 inches, min on a one inch steel plate.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.

3.4 Workmanship. - All parts and assemblies shall be fabricated and loaded in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, chips, cracks, dirt, grease, rust, corrosion products and other foreign material. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

3.5 First Article Inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of Product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted.

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.

b. Drawing and specification number and date, together with identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.

d. Number of items in the lot.
e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agents authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First Article Inspection

4.2.1 Submission.-Prior to the start of regular production the contractor shall submit a first article sample (see 6.1c) to a Government approved facility as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2 and 4.2.3. The first article sample shall consist of ten (10) loaded destructor assemblies, ten (10) destructor assemblies less explosives, and ten (10) complete sets of parts (i.e., 10 each of every component and sub-assembly) which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials including packaging and packing shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including a certificate of conformance for materials. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer. A first article sample, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be performed. - Assemblies, subassemblies and components will be subjected by the Government to any or all of the examinations specified in this specification, and any or all requirements of the applicable drawings. All the destructor assemblies shall be subjected by the Government to the following tests as specified in 4.3.3 of this specification. Ten (10) des-

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.

tructor assemblies less explosive components will be subjected to the pull test as specified in 4.4.3, and 10 destructor assemblies will be functioned as specified in 4.4.4.

4.2.3 Rejection. - If any component or subassembly fails to comply with any or all of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an inert component or subassembly to comply with any of the stated requirements.

4.3 Inspection provisions

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer in one unchanged process using the same materials and methods in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specifications, or drawings not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each lot of loaded destructors shall contain:

a. Parts or part assemblies from not more than one (1) lot interfix number from one manufacturer.
b. Composition A-3 from one lot interfix number and not more than two lots from within the interfix.

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.3.1) of the components or assemblies designated in the appli-

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.

cable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable sub-paragraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

*4.3.2.1 Bushing, cap, blasting (see dwg. 9216196 covering a detail of dwg. 9216189).

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:	None defined		
Major:	AQL 1.0 percent		
101.	True position of inside diameter with pitch diameter of cavity	Gage	01001
102.	Pitch diameter of external thread, min.	Gage	01002
103.	Major diameter of external thread, min.	Gage	01003
104.	Pitch diameter of internal thread, maximum (max)	Gage	01004
105.	Minor diameter of internal thread, max.	Gage	01005
106.	Length of internal thread, min.	Gage	01006
107.	Inside diameter, min.	Gage	01007
108.	Outside diameter at small end	Gage	01008
109.	Evidence of crack or split	Visual	01009
Minor:	AQL 1.0 percent		
201.	Depth of large cavity	Gage	01010
202.	Evidence of poor workmanship other than crack or split (see 3.4)	Visual	01011

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.

4.3.2.2 Bushing activator (see dwg. 9216198 covering a detail of dwg. 9216189).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 1.0 percent		
101.	Total length	Gage	02001
102.	Inside diameter of threaded end	Gage	02002
103.	Major diameter of external thread, min.	Gage	02003
104.	Internal pitch improper	Gage	02004
105.	Length of external thread	Gage	02005
106.	Evidence of crack or split	Visual	02006
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship other than crack or split (see 3.4)	Visual	02007

4.3.2.3 Bushing, ammunition (see dwg. 9216199 covering a detail of dwg. 9216189).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 1.0 percent		
101.	Pitch of large external thread functional	Gage	03001
102.	Pitch of small external thread functional	Gage	03002
103.	Pitch of internal thread, functional	Gage	03003
104.	Length of large external thread	Gage	03004
105.	Length of small external thread	Gage	03005
106.	Evidence of crack or split	Visual	03006

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.

Minor:	AQL 1.0 percent		
201.	Total length	Gage	03007
202.	Evidence of poor workmanship other than crack or split (see 3.4)	Visual	03008

4.3.2.4 Cup, booster (see dwg. 9216193 covering a detail of dwg. 9216189).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 1.0 percent		
101.	Pitch of large external thread, functional	Gage	04001
102.	Pitch of small external thread, functional	Gage	04002
103.	Minor diameter of large internal thread, max.	Gage	04003
104.	Length of small external thread	Gage	04004
105.	Total length	Gage	04005
106.	Evidence of crack, split, or perforation	Visual	04006
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship other than crack or split (see 3.4)	Visual	04007

4.3.2.5 Pellet, Booster, Lower (see dwg. 9216195 covering a detail of dwg. 9216189).

Categories	Defects	Method of Inspection	Code NO.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Pellet diameter	Gage	05001
102.	Charge length, max.	Gage	05002
103.	Evidence of poor workmanship (see 3.4)	Visual	05003

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.

Minor: None defined

4.3.2.6 Pellet, Booster, Upper (see dwg. 9216194 covering a detail of 9216189).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Outside diameter	Gage	06001
102.	Charge length, max.	Gage	06002
103.	Depth to step	Gage	06003
104.	Evidence of poor workmanship (see 3.4)	Visual	06004
Minor:	AQL 1.00 percent		
201.	Large inside diametem.....	Gage	06005
202.	Small inside diameter	Gage	06006

4.3.2.7 Destructor, HE, Universal, M10 Assembly (see dwg. 9216189).

Categories	Defects	Method of Inspection	Code No.
Major:	AQL 0.65 percent		
101.	Component missing or loose	Visual/ Manual	07001
102.	Component unable to be assembled by hand or improperly assembled.	Visual/ Manual	07002
103.	Protective finish missing or incomplete	Visual	07003
104.	Base not painted yellow	Visual	07004
Minor:	AQL 1.0 percent		
201.	Marking missing, illegible or incorrect	Visual	07005
202.	Evidence of poor workmanship (see 3.4)	Visual	07006

4.3.2.8 Container, Ammunition, Fiber, M346, for Destructor, HE, Universal, M10 (see dwg. 9215526).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Container cut or damaged through all impregnated layers	Visual	08001
102.	Tape inadequate or badly wrinkled	Visual	08002
103.	Metal end loose or distorted	Visual	08003
104.	Contents move when container is tilted	Manual	08004
Minor:	AQL 1.00 percent		
201.	Marking missing, illegible or incorrect	Visual	08005
202.	Evidence of poor workmanship (see 3.4)	Visual	08006

4.3.2.9 Box, packing, ammunition, for Destructor, HE, Universal, M10 prior to sealing (see dwg. 9215527).

Categories	Defects	Method of Inspection	code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Incorrectnumber of destructors (in containers)	Visual	09001
102.	Containers incorrectly packed	Visual	09002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.4)	Visual	09003

4.3.2.10 Box, packing, ammunition, for Destructor, HE, Universal, M10 (see dwg. 9215527).

Categories	Defects	Method of Inspection	Code No.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.

Critical: None defined

Major:	AQL 0.65 percent		
101.	Box broken or split	Visual	10001
102.	Strapping missing, broken or loose	Visual	10002
103.	ICC nomenclature missing, illegible or incorrect	Visual	10003
104.	Contents move when box is tilted	Manual	10004
Minor:	AQL 1.5 percent		
201.	Marking missing, illegible or incorrect	Visual	10005
202.	Hardware improperly engaged ..	Visual	10006
203.	Car seal omitted, unsealed or improperly positioned	Visual	10007
204.	Evidence of poor workmanship (see 3.4)	Visual	10008

4.3.3 Testing

*4.3.3.1 Specific gravity of booster pellet (see dwg. 9216194 or dwg. 9216195, as applicable) - Major Defect, Code No. 11001. - A sample of five (5) booster pellets of each type shall be selected from each lot for this test. Failure of any booster pellet to comply with the applicable drawing requirement shall cause rejection of the lot. The test shall be performed as specified in 4.4.1 using equipment in accordance with 4.3.4.

4.3.3.2 Hardness of flat of ammunition bushing (see dwg. 9216199), Major Defect, Code No. 12001. - The sampling plan for this test shall be in accordance with MIL-STD-105, Code letter H, and an AQL of 1.0 percent. Any bushing which fails to comply with the applicable drawing requirement, shall be classed defective. The test shall be performed as specified in 4.4.2 using equipment in accordance with 4.3.4.

4.3.3.3 Hardness of flat of activator bushing (see dwg. 9216198), Major Defect, Code No. 12002. - The sampling plan for this test shall be in accordance with MIL-STD-105, Code Letter H, and an AQL of 1.0 percent. Any bushing which fails to comply with the applicable drawing requirement shall be classed defective. The test shall be performed as specified in 4.4.2 using equipment in accordance with 4.3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.

4.3.3.4 Pull Test (see dwg. 9216189), Major Defect, Code No. 13001. - The sampling plan for this test shall be in accordance with MIL-STD-105, Code Letter K, using an AQL of 0.40 percent. Any assembly which fails to comply with the applicable drawing requirement shall be classed defective. The test shall be performed as specified in 4.4.3 using equipment in accordance with 4.3.4.

4.3.3.5 Functioning (see 3.3), Major Defect, Code No. 14001. - The sampling plan for this test shall be in accordance with MIL-STD-105, Code Letter K, using an AQL of 0.40 percent. Any destructor assembly which fails to provide an indentation in the steel plate of the required depth or diameter shall be classed defective. The test shall be performed as specified in 4.4.4 using equipment in accordance with 4.3.4.

4.3.4 Inspection Equipment. - Inspection equipment required to perform the inspections prescribed in this specification is identified in the examination (4.3.2) and Test Method (4.4) paragraphs herein. See 6.3 for details concerning responsibilities for inspection design and approval.

4.4 *Test Methods and Procedures*

4.4.1 Specific gravity of booster pellet. - The pellet shall be weighed on a balance and the weight recorded as dry weight. The pellet shall then be weighed while completely submerged in water, taking care to remove all air bubbles remaining on the surfaces of the pellet. The temperaturtof the water shall be 68 degrees Fahrenheit (F) plus or minus 2 degrees F. This weight shall be recorded as weight under water. (When submerged, the position of the pellet shall be such that no air is entrapped). Specific gravity shall be calculated as follows:

$$\text{Specific Gravity} = \frac{A}{(A-B)}$$

Where:

A = Dry weight
B = Weight under water

4.4.2 Hardness of flat of activator bushing or ammunition bushing. - This test shall be performed in accordance with FED-STD-151, Method 243.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.

4.4.3 Pull Test. - The destructor assembly, less ammunition bushing, blasting cap bushing, and booster pellets, shall be assembled t the pull test fixture in accordance with 4.3.4 and the specified pull applied in the axial direction. Observation shall be made for compliance with the applicable drawing requirements.

4.4.4 Functioning. - A test plate, or grade 1020 flat steel in accordance with ASTM A575-67T and measuring four inches by four inches, one inch thick, shall be used with each destructor assembly for this test. The test shall be conducted on firm flat ground. The test plate shall be positioned so that one of its large surfaces makes good contact with the surface of the earth. A No. 6 or No. 8 commercial blasting cap or military blasting cap shall be assembled to the destructor. The destructor shall be placed in the center of the upper face of the plate with the destructor perpendicular to the plate. The blasting cap shall be fired and the resultant effect of the detonation of the destructor on the plate shall be observed. The maximum depth measured from the original surface and the diameter of the indentation in the plate shall be measured and recorded.

5. PREPRATION FOR DELIVERY

5.1 Preservation, packing, packaging and marking shall be in accordance with dwg. 9215526 and 9215527.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Data cards. - Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.
c. Provisions for submission of first article samples.

*6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. They should be cited as references on drawings of equipment designs submitted by the contractor to the Government for approval (see 6.3.3).

*6.3 Inspection Equipment Designs.-Inspection equipment designs are of two types - Government Special Inspection Equip-

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.

ment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers under the "Method of Inspection" headings in Section 4. Design responsibility for all other inspection equipment is assigned to the contractor. The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3 should he elect to do so.

6.3.1 SIE designs.-SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.

b. A source control drawing or a specification control drawing as defined in MIL-STD-100.

c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detailed design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.3.2 Contractor designs.-Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public). Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment, or with SIE designs if not otherwise covered thereby (see 6.3.1c). Designs shall be of the category and form (per MIL-D-1000) specified in the Contract Data Requirements Lists (DD Form 1423). The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number and the applicable five digit defect code number (or other specific identifying information) from Section 4 of this specification shall be referenced on each contractor design together with the component or assembly drawing number and revision letter to which the specific design applies.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.

6.3.3 Submission of Designs for Approval.-Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval to Picatinny Arsenal, ATTN: SARPA-QA-A-M, Dover, New Jersey 07801 in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423) or in the contract. The contractor must include in his submission of designs a listing of any and all Government SIE designs which will be utilized. Partial submission of inspection designs is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

*6.4 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1375-A-078

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.