MILITARY SPECIFICATION

PUBLIC ADDRESS SET (REPRODUCING EQUIPMENT MC-364-( )) AND PUBLIC ADDRESS SET AN/UIH-2( )

This amendment forms a part of Military Specification MIL-P-12953A 5 March 1955, and has been approved by the Department of Defense and is mandatory for use by the Department of the Army, the Navy, and the Air Force.

Page 1, paragraph 2.1:

(a) Delete the following specifications:

FEDERAL

PPP-B-601 — Boxes; Wood-Cleated-Plywood.

UU-T-111 — Tape, Paper, Gummed (Sealing and Securing)

MILITARY

19-10 — Filler, Interior Packing, Fiberboard, Corrugated, Single and Double Faced, For General Packing Purposes.

(b) Add the following specification:

MIL-M-11101 — Microphones, Dynamic.

(c) Delete the following drawings:

SC-D-15914 — Moisture Resistance Test Cycle For Ground Signal Equipment.

SC-D-25129 — Special Purpose Cable Assembly CX-1207.

(d) Add the following drawings:

SC-C-83335 — Cable Assembly, Special Purpose Electrical CX-2150/U.

SC-D-19999 — Standard Extreme Temperature Cycle.

(e) Add the following standards:

MIL-STD-169 — Extreme Temperature Cycle.

MIL-STD-170 — Moisture-Resistance Test Cycle for Ground Signal Equipment.

FSC 5830
FSC 5835

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.

MIL–STD–252 — Wired Equipment, Classification of Visual and Mechanical Defects For.

Page 2, paragraph 2.2: Add the following:

AMERICAN TRUCKING ASSOCIATION
National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association, 1424 Sixteenth St., N. W., Washington 6, D. C.)

Page 3, paragraph 3.4 and 3.5: Delete "Microphone, Dynamic M–23( )/U" and substitute "Microphone, Dynamic M–43( )/U."

Page 3, paragraph 3.7: "Delete and substitute:

"**3.7 Microphone, Dynamic M–43( )/U.** Microphone, Dynamic M–43( )/U shall be in accordance with Specification MIL–M–11101."

Page 4, paragraph 3: Delete and substitute:

"**3.8 Special Purpose Cable CX–2150/U.** Special Purpose Cable CX–2150/U shall be 20 feet long and shall be in accordance with Drawing SC–C–83335, and shall be provided for connection of the microphone to the amplifier."

Page 4. Add the following paragraph:

"**3.12.1 Microphone input connector.** Reproducer RP–104( )/UIH–2 shall be equipped with a microphone input connector to mate with Cannon type Plug XL–3–125C or equal."

Page 4, paragraph 3.17.2, line 3: Delete "8 db" and substitute "18 db."

Page 9, Table III: Delete "Microphone M–23( )/U and add "Microphone Dynamic M–43( )/U."

Delete "Specification MIL–C–3885" and add "Specification MIL–M–11101."

Page 9, paragraph 4.2: Delete and substitute:

4.2 **Visual and mechanical inspection.** Parts and equipment shall be examined for the defects listed in Standard MIL–STD–252.

Page 10, paragraph 4.5 (8), line 3: Delete "0.1 volt" and substitute "1.0 volt."

Page 11, paragraph 4.12.1: Delete "Drawing SC–D–19999" and substitute "Standard MIL–STD–169."

Page 11, paragraph 4.12.2.2(d): In second sentence, delete "Drawing SC–D–15914" and substitute "Standard MIL–STD–170" and in last sentence, delete "drawing" and substitute "standard."

Page 13, paragraph 4.13: Delete and substitute:

"4.13 Microphone M–43( )/U shall be tested for compliance with paragraph 3.7."

Page 13, Section 5: Delete and substitute:

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 *Level A.* Public Address Set (Reproducing Equipment MC–364( )) and Public Address Set AN/UIH–2( ) shall be preserved and packaged in accordance with the procedures specified for the designated methods as prescribed in Specification MIL–P–116 and described in the following paragraphs:

5.1.1.1 *Technical manual.* Each Technical Manual shall be packaged Method IC–3 as follows: Inclose each technical manual within a close-fitting bag, Type I, Class b, conforming to Specification MIL–B–117. Heat seal to effect closure. Packages prepared as above shall be required to pass the quick leak test prescribed in Specification MIL–P–116.

5.1.1.2 *Tubes.* Remove all operating tubes

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.

over four inches in length not securely clamped in place and package together with spare tubes, individually in accordance with Specification MIL–P–75.

5.1.1.3 *Stowage of electrical spare parts and accessories.* Stow and secure electrical spare parts, accessories, and tubes packaged as specified in 5.1.1.2 within compartments and clips provided within the designated equipment and covers.

5.1.1.4 *Speaker Assembly LS–148( )/U.* Each speaker assembly shall be packaged Method IC–5 as follows: Place speakers together and secure fastenings. Position covers and secure fastenings. Cushion each assembly on all surfaces with cells or pads or both fabricated of double-faced corrugated, fiberboard having a minimum dry bursting strength of 275 pounds, designed to absorb the shock of impact encountered in handling and transmit. Place the cushioned assembly within a close-fitting, regular slotted Style W5c fiberboard box conforming to Specification JAN–P–108. Closure shall be in accordance with the appendix of the box specification. In addition, seal all seams and joints with water-resistant, pressure-sensitive tape, Type II, Grade B, Olive Drab conforming to Specification JAN–P–127.

5.1.1.5 *Turntable MX-932( )/U and Reproducer, Sound RP–104( )/UIH–2.* Each turntable and reproducer shall be packaged individually Method IC–5 as follows: Position cover and secure all fastenings. Continue packaging as specified in 5.1.1.4.

5.1.2 *Level C.* Public Address Set (Reproducing Equipment MC–364( )) and Public Address Set AN/UIH–2( ) shall be packaged in accordance with commercial practice and in a manner that will afford protection against corrosion, deterioration, and physical damage during direct shipment to the first receiving activity.

5.2 **Packing.**

5.2.1 *Level A.* Place one each Speaker Assembly LS–148 and one each Turntable MX–932 or one each Speaker Assembly LS–148 and one each Reproducer RP–104, packaged as specified in 5.1.1.4 and 5.1.1.5 together within a close fitting, Style 4, nailed wood box conforming to Specification JAN–P–106. Place the packaged technical manual between the contents and the lid of the shipping container. Close the box in accordance with the appendix of the box specification. Completed packs prepared as above shall be required to pass the water spray test and the rough handling test prescribed in Specification MIL–P–116.

5.2.1.1 *Metal Strapping.* Shipping containers shall be strapped in conformance with the requirements of the appendix of the container specification only for direct shipment to ports.

5.2.2 *Level B.* Each Public Address Set (Reproducing Equipment MC–364–( )) and Public Address Set AN/UIH–2( ) shall be packed and tested as specified in 5.2.1, except that the Style 4, nailed wood box shall conform to Specification NN–B–621..

5.2.3 *Level C.* Each Public Address Set (Reproducing Equipment MC–364–( )) and Public Address Set AN/UIH–2( ) shall be packed for shipment in a manner conforming to the requirements of Uniform Freight Classification for rail shipment, National Motor Freight Classification for truck shipment, Parcel Post Regulations, and regulations of other carriers as applicable to the mode of transportation employed at the lowest transportation rate.

5.3 **Marking.** Interior packages and exterior shipping containers shall be marked in accordance with the applicable provisions of Standard MIL–STD–129.

Custodians:
Army—Signal Corps
Air Force

Preparing Activity:
Army—Signal Corps □

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.

PROCUREMENT DATA DIVISION
PRODUCTION ENGINEERING DEPARTMENT
U. S. ARMY SIGNAL EQUIPMENT SUPPORT AGENCY
FORT MONMOUTH, NEW JERSEY

Date: 18 March 196

ADDENDUM NUMBER 1

To Accompany: Specification MIL-P-12953A and Amendment 1, dated 29 May 1957

For: Public Address Set (Reproducing Equipment MC-364-( )) and Public Address Set AN/UIH-2( )

---

1. Page 2 Section 2.1, Drawings: Add the following: "SC-DL-157544 - Reproducer, Sound RP-104( )/UIH-2."

2. Page 2 Delete paragraph "3.1, 3.1.1, 3.1.2 and 3.1.3."

3. Page 4 Paragraph 3.12 Delete "the procurement model" and replace with "Drawing SC-DL-157544."

Sheet 1 of 1 sheet

FSC 5835

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:53Z
Check the source to verify that this is the current version before use.