INCH POUND

MIL-C-3098/115B
5 May 1993
SUPERSEDING
MIL-C-3098/115A
2 November 1983


MILITARY SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR136/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirement for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-3098.

Pertinent characteristics: 8 to 10 MHz; fundamental; noncontrolled; antiresonance.



Inches	mm
.002	.05
.008	.20
.017	.43
.150	3.81
.183	4.65
.192	4.88
.402	10.21
.435	11.05
.50	12.7
.530	13.46

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-C-3098.

FIGURE 1. Crystal unit - CR136/U.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-16T16:55Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Holder: HC-18/U (MIL-H-10056/9) or HC-43/U.

Dimensions, marking, and configuration: See figure 1.

Frequency range: 8 to 10 MHz, inclusive.

Capacitance, shunt: 6.0 +0.5, -1.0 pF.

Mode of oscillation: Fundamental.

Rated drive level: 10.0 mW, maximum.

Antiresonance, load capacitance: 32.0 ±0.5 pF.

Operating temperature ranges:

Room temperature: +25°C to +30°C, inclusive.

Primary: +10°C to +25°C and +30°C to +80°C, inclusive.

Secondary: -40°C to +10°C and +80°C to +90°C, inclusive.

Frequency tolerances:

Room temperature: ±10 ppm.

Primary operating temperature range: ±25 ppm.

Secondary operating temperature range: ±50 ppm.

Equivalent resistance: 35 ohms, maximum.

Shock (specified pulse):

Frequency change permitted: ±5 ppm.

Equivalent resistance: ±10 percent.

Vibration: Method 204 of MIL-STD-202, test condition A.

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Thermal shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Aging:

Frequency change permitted: ±5 ppm.

NOTE: These crystal units are for use in the AN/ARC-101 equipment.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 202610-16T16:55Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:

Army - ER
Navy - EC
Air Force - 85

User activities:

Air Force - 17, 84

Preparing activity:

Army - ER

Agent:

DLA - ES

(Project 5955-0678-10)

Source: https://assist.dla.mil -- Downloaded: 202610-16T16:55Z
Check the source to verify that this is the current version before use.