INCH-POUND
MIL-PRF-3098/115D
27 July 2005
SUPERSEDING
MIL-PRF-3098/115C
27 August 1997

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR136/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-3098.

Pertinent characteristics: 8 MHz to 10 MHz; fundamental; noncontrolled; antiresonance.



Inches	mm
.002	.05
.008	.20
.017	.43
.150	3.81
.183	4.65
.192	4.88
.402	10.21
.435	11.05
.500	12.70
.530	13.46

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Crystal unit - CR136/U.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:54Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 8 MHz to 10 MHz, inclusive.

Capacitance, shunt: 6.0 pF +0.5 pF, -1.0 pF.

Mode of oscillation: Fundamental.

Rated drive level: 1.0 mW, maximum.

Antiresonance, load capacitance: 32.0 pF ±0.5 pF.

Operating temperature ranges:

Room temperature: +25°C to +30°C, inclusive.

Primary operating temperature range: +10°C to +25°C and +30°C to +80°C, inclusive.

Secondary operating temperature range: -40°C to +10°C and +80°C to +90°C, inclusive.

Frequency tolerances:

Room temperature: ±10 ppm.

Primary operating temperature range: ±25 ppm.

Secondary operating temperature range: ±50 ppm.

Equivalent resistance: 35 ohms, maximum.

Shock (specified pulse):

Frequency change permitted: ±5 ppm.

Equivalent resistance: ±10 percent.

Vibration: Method 204, MIL-STD-202, test condition A.

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Thermal shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Aging:

Frequency change permitted: ±5 ppm.

* Reference documents. In addition to MIL-PRF-3098, this document references the following:

MIL-STD-202

* The margins of this specification sheet are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:54Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Air Force - 99

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5955-0811-03)

* NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:54Z
Check the source to verify that this is the current version before use.