INCH-POUND
MIL-PRF-3098/115E
11 July 2011
SUPERSEDING
MIL-PRF-3098/115D
27 July 2005


PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR136/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-3098.

Pertinent characteristics: 8 MHz to 10 MHz; fundamental; noncontrolled; antiresonance.



Ltr	Inches		mm	
	Min	Max	Min	Max
A	---	.402	---	10.21
B	---	.183	---	4.65
C	---	.435	---	11.05
D	.184	.200	4.67	5.08
E	---	.530	---	13.46
F	.50	---	12.7	---
G	---	.150	---	3.81
H	.015	.019	0.38	0.48

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Crystal unit - CR136/U.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:54Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 8 MHz to 10 MHz, inclusive.

Capacitance, shunt: 6.0 pF +0.5 pF, -1.0 pF.

Mode of oscillation: Fundamental.

Rated drive level: 1.0 mW, maximum.

Antiresonance, load capacitance: 32.0 pF ±0.5 pF.

Operating temperature ranges:

Room temperature: +25°C to +30°C, inclusive.

Primary operating temperature range: +10°C to +25°C and +30°C to +80°C, inclusive.

Secondary operating temperature range: -40°C to +10°C and +80°C to +90°C, inclusive.

Frequency tolerances:

Room temperature: ±10 ppm.

Primary operating temperature range: ±25 ppm.

Secondary operating temperature range: ±50 ppm.

Equivalent resistance: 35 ohms, maximum.

Shock (specified pulse):

Frequency change permitted: ±5 ppm.

Equivalent resistance: ±10 percent.

Vibration: Method 204, MIL-STD-202, test condition A.

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Thermal shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Aging:

Frequency change permitted: ±5 ppm.

Part or Identifying Number (PIN): For Product Level B, PIN shall be CR136/U or CR136B/U (followed by specified frequency). For Product Level S, PIN shall be CR136S/U (followed by specified frequency), see 1.2 of MIL-PRF-3098.

Reference documents. In addition to MIL-PRF-3098, this document references the following:

MIL-PRF-202

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:54Z
Check the source to verify that this is the current version before use.

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 99
DLA - CC

Review activities:
Air Force - 84

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5955-2011-005)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:54Z
Check the source to verify that this is the current version before use.