INCH-POUND
MIL-PRF-3098/129B
1 October 1997
SUPERSEDING
MIL-C-3098/129A (USAF)
7 April 1975

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR148/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-3098.

Pertinent characteristics: 10 MHz to 61 MHz; third mechanical overtone; noncontrolled; series resonance.



INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM
.002	.05	.020	.51	.050	1.27	.486	12.34
.005	.13	.025	.64	.108	2.74	.725	18.42
.008	.20	.030	.76	.238	6.05	.757	19.23
.010	.25	.035	.89	.317	8.05	.775	19.69
.015	.38	.040	1.02	.352	8.94		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Crystal unit - CR148/U.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:57Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 10.0 MHz to 61.0 MHz, inclusive.

Capacitance, shunt: 7.0 pF, maximum.

Mode of oscillation: Third mechanical overtone.

Rated drive level: 1.0 mW, maximum.

Calibration values:

Equivalent resistance: 51 ohms.

Resistor voltage drop: 0.32 volt.

Resonance: Series.

Operating temperature range (noncontrolled): -55°C to +105°C, inclusive.

Frequency tolerance: ±0.0005 percent.

Equivalent resistance: 40 ohms, maximum.

Unwanted modes: Minimum unwanted-to-main mode resistance ratio of 2:1.

Shock:

Frequency change permitted: ±0.0005 percent.

Equivalent resistance change permitted: ±15 percent or 2 ohms, whichever is greater.

Vibration: Method 201, MIL-STD-202.

Frequency change permitted: ±0.0005 percent.

Equivalent resistance change permitted: ±15 percent or 2 ohms, whichever is greater.

Temperature cycling:

Frequency change permitted: ±0.0005 percent.

Equivalent resistance change permitted: ±15 percent or 2 ohms, whichever is greater.

Aging:

Frequency change permitted: ±0.0005 percent.

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - CR
Navy - EC
Air Force -85

Preparing activity:
DLA - CC

(Project 5955-0697-83)

Review activities:
Air Force - 11, 17, 19, 99

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:57Z
Check the source to verify that this is the current version before use.