INCH-POUND
MIL-PRF-3098/131F
28 July 2011
SUPERSEDING
MIL-PRF-3098/131E
27 July 2005


PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR150/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-3098.

Pertinent characteristics: 45 MHz to 100 MHz; fifth mechanical overtone; controlled; series resonance.



Ltr	Inches		mm	
	Min	Max	Min	Max
A	---	.757	---	19.23
B	---	.352	---	8.94
C	.750	.775	19.05	19.69
D	.223	.248	5.66	6.30
E	.478	.494	12.14	12.55
F	.175	.185	4.45	4.70
G	.030	.037	0.76	0.94
H	.015	.025	0.38	0.64
J	.048	.052	1.22	1.32

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.
4. The pin undercut may be omitted.

FIGURE 1. Crystal unit - CR150/U.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:58Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 45.0 MHz to 100 MHz, inclusive.

Operable temperature range: +55°C to +70°C, inclusive.

Operating temperature range (controlled): +70°C to +80°C, inclusive.

Frequency and equivalent resistance:

Equivalent resistance: 40 ohms, maximum.

Reference temperature: 75°C ±1°C.

Frequency tolerance: ±5 ppm.

Mode of oscillator: Fifth mechanical overtone.

Temperature ranges:

Primary: -40°C to +90°C, inclusive.

Secondary: -55°C to -40°C and +90°C to +105°C, inclusive.

Rated drive level: 1.0 mW, maximum.

Resonance: Series.

Capacitance, shunt: 3.0 pF, maximum.

Shock (specified pulse):

Frequency change permitted: ±2.5 ppm.

Equivalent resistance change permitted: ±40 ohms, maximum.

Vibration: Method 201, MIL-STD-202.

Frequency change permitted: ±2.5 ppm.

Equivalent resistance change permitted: ±40 ohms, maximum.

Thermal shock:

Frequency change permitted: ±2.5 ppm.

Equivalent resistance change permitted: ±40 ohms, maximum.

NOTE: CR150/U is similar to CR143/U except for a wider frequency tolerance.

Part or Identifying Number (PIN): For Product Level B, PIN shall be CR150/U or CR150B/U (followed by specified frequency). For Product Level S, PIN shall be CR150S/U (followed by specified frequency, see 1.2 of MIL-PRF-3098.

Reference documents. In addition to MIL-PRF-3098, this document references the following:

MIL-STD-202

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:58Z
Check the source to verify that this is the current version before use.

The margins of this specification sheet are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
AF - 99
DLA - CC

Review activities:
Army - AR, MI

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5955-2011-011)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:58Z
Check the source to verify that this is the current version before use.