INCH-POUND
MIL-PRF-3098/132C
27 August 1997
SUPERSEDING
MIL-C-3098/132B
24 September 1992

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR151/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-3098.

Pertinent characteristics: 50 MHz to 100 MHz; fifth mechanical overtone; noncontrolled; series resonance.

Inches	mm
.001	.03
.002	.05
.008	.20
.017	.43
.150	3.81
.183	4.65
.192	4.88
.402	10.21
.435	11.05
.500	12.70
.530	13.46



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Crystal unit - CR151/U.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:58Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 50.0 MHz to 100 MHz, inclusive.

Frequency tolerance:

Room temperature: ±20 ppm.

Primary operating temperature range: ±35 ppm.

Secondary operating temperature range: ±50 ppm.

Equivalent resistance: 50 ohms, maximum.

Mode of oscillator: Fifth mechanical overtone.

Operating temperature ranges (noncontrolled):

Room temperature: +25°C to +30°C, inclusive.

Primary: -30°C to +25°C and +30°C to +70°C, inclusive.

Secondary: -40°C to +30°C and +70°C to +90°C, inclusive.

Rated drive level: 1.0 mW, maximum.

Resonance: Series.

Capacitance, shunt: 6.0 pF +0.5 pF, -1.0 pF.

Shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Vibration: Method 204, MIL-STD-202, test condition A.

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Thermal shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Aging:

Frequency change permitted: ±5 ppm.

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:58Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force -85

Review activities:
Air Force - 17, 19, 80

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5955-0697-86)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:58Z
Check the source to verify that this is the current version before use.