INCH-POUND

MIL-V-10908C
13 May 1993
SUPERSEDING
MIL-V-10908B
12 March 1968

MILITARY SPECIFICATION

VALVE, DRIP, ADJUSTABLE FEED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type and size of drip valve with sight glass and brass body.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

DD-G-511	-	Glass Tubing, Round
HH-C-576	-	Cork Sheet (Gaskets, Sheets, and Strips)
QQ-C-390	-	Copper Alloy Castings (Including Cast Bar)
WW-T-791	-	Tube, Brass, Seamless
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5017 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4520

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:33Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWING

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

2-9-88 - Valve, Drip, Adjustable Feed

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-UXT, Natick, MA 01760-5017.)

2.2 Non-Government publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM A 276 - Stainless and Heat Resisting Steel Bars and Shapes
ASTM B 121 - Leaded Brass Plate, Sheet, Strip, and Rolled Bar
ASTM D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:33Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.2.1 Brass.

3.2.1.1 Casting. The brass casting shall conform to copper alloy No. C84400 or C85400, Type I of QQ-C-390.

3.2.1.2 Tubing. The seamless brass tubing shall conform to grade A or B, type II of WW-T-791.

3.2.1.3 Bar. The brass bar shall conform to copper alloy No. C34200 or C35300, Temper H02 of ASTM B 121.

3.2.2 Steel, corrosion-resisting. Corrosion-resisting steel shall conform to type 302, condition A, of ASTM A 276.

3.2.3 Glass, sight. The sight glass shall conform to DD-G-511.

3.2.4 Gasket, sight glass. The cork gasket shall conform to type I-B of HH-C-576.

3.2.5 Packing, valve stem. The valve stem packing shall be noncorrosive, gasoline and oil resistant, high temperature packing manufactured from a combination of asbestos, powdered aluminum, graphite and neoprene, molded into accurately sized rings in accordance with the manufacturer's current commercial practice.

3.3 Design and construction. The design and construction of the drip valve shall conform to Drawing 2-9-88 and the requirements specified herein. The sight glass shall be held firmly between the gaskets. The valve, with stem open, shall not leak when tested as specified in 4.4.5. The stem and valve seat shall be smooth and shall not leak when the stem is seated and tested as specified in 4.4.5.

3.4 Finish. The body of the valve may be unfinished except for machined portions as shown on Drawing 2-9-88.

3.5 Marking. Each valve shall be legibly marked with the supplier's name or trademark.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:33Z
Check the source to verify that this is the current version before use.

3.6 Workmanship. The finished valve shall be clean. Metal components shall be free of splinters, sharp edges, burrs, pits, or cracks. The glass shall be free of cracks, splinters, blowholes, waviness, and chipped edges. The end item shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4 and shall be tested for the characteristics specified in 4.4.5. The presence of any defect or failure to pass any test shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:33Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.2 In-process inspection. Inspection of subassemblies shall be made to ascertain that construction details which cannot be examined in the finished product are in accordance with specified requirements. The Government reserves the right to exclude from consideration for acceptance, any material or service for which in-process inspection has indicated nonconformance.

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of valves. The sample unit shall be one valve. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE I. End item visual examination

Examine	Defect	Classification Major	Minor
Construction and workmanship	Component missing, broken, split fractured, cracked, or punctured	101	
	Sharp edges, burrs, or pits	102	
	Glass gage loose, free of cracks, splinters, blowholes, waviness, and chipped edges	103	
Marking	Missing or not legible		201

4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on Drawing 2-9-88. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of valves. The sample unit shall be one valve. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.5 End item testing. The end items shall be tested for the characteristics listed in table II. The lot size shall be expressed in units of

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:33Z
Check the source to verify that this is the current version before use.

valves. The sample unit shall be one valve. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 1.5.

TABLE II. End item tests

Characteristics	Specification reference: Requirement	Specification reference: Test method	Number of determinations: per sample unit	Results reported as: pass or fail
Valve leakage with stem open	3.3	4.5.1(1)	1	X
Valve leakage with stem closed	3.3	4.5.1(2)	1	X

4.4.6 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

4.4.7 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:33Z
Check the source to verify that this is the current version before use.

Palletization	Pallet pattern not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

4.5 Methods of inspection.

4.5.1 Leak test. The drip valve shall be tested for leaks as follows:

(1) With the valve stem opened and one opening blocked, the valve shall be pressurized with a minimum of 5 psi (pounds per square inch) air pressure and submerged in water to determine compliance with the valve leakage requirements of 3.3.

(2) From an open position, the stem shall be closed until the stem barely makes contact with the valve seat. The valve in this condition shall be pressurized with a minimum of 5 psi air pressure and then submerged in water to determine compliance with the valve stem and seat leakage requirements of 3.3.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A preservation. Each valve shall be closed fingertight and an inlet provided with a thread protector. Ten valves shall then be packaged in a paperboard box.

5.1.2 Commercial preservation. Valves shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing. Two hundred valves, preserved as specified in 5.1, shall be packed in a shipping container conforming to style RSC, grade V2s of PPP-B-636. Each box shall be closed, waterproofed, and reinforced in accordance with the appendix of PPP-B-636.

5.2.2 Level B packing. Two hundred valves, preserved as specified in 5.1, shall be packed in a shipping container conforming to style RSC, grade 275 of PPP-B-636. Each box shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:33Z
Check the source to verify that this is the current version before use.

5.2.3 Commercial packing. Valves, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. Valves, packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with straps in accordance with bonding means C and D or film bonding means F or G. Pallet pattern shall be in accordance with the appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The drip valve covered by this specification is intended for use as a component of Heater, Space (Yukon, M-1950, with Accessories), MIL-H-12340.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Levels of preservation and packing required (see 5.1 and 5.2).
e. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.5 Subject term (key word) listing.

Control device
Regulator

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:33Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians:

Army - GL
Air Force - 99

Review activities:

Air Force - 84
DLA - CS

User activity:

Navy - MC

Preparing activity:

Army - GL

(Project 4520-0355)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:33Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-V-10908C	93-05-13

3. DOCUMENT TITLE

Valves, Drip, Adjustable Feed

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

[redacted]

7. PREPARING ACTIVITY

NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON
U.S. Army Natick RD&E Center	508-651-4531	256-4531

c. ADDRESS (Include Zip Code)

Commander, U.S. Army Natick RD&E Center
ATTN: SATNC-UXT
Natick, MA 01760-5017

IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:
Defense Quality and Standardization Office
5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466
Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2020-10-17T14:33Z
Check the source to verify that this is the current version before use.