MIL-B-29378(MC)
22 March 1979
SUPERSEDING
(See Section 6)

MILITARY SPECIFICATION

BELT, MAN'S: CEREMONIAL, OFFICERS

This specification is approved for use by U. S. Marine Corps, Department of the Navy, and is available for use by all Department and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the minimum requirements for a poromeric waist belt with detachable and adjustable shoulder strap.

1.2 Classification. The belt shall be of one type in the following classes, and sizes (see 6.2):

1.2.1 Class.

Class 1 - Standard (Poromeric)
Class 2 - Optional (Poromeric and Leather)

1.2.2 Sizes.

Schedule of waist sizes

32	40
34	42
36	44
38	46

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to the Commandant of the Marine Corps (LMA-1), Headquarters U. S. Marine Corps, Washington, D. C. 20380, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8440

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

SPECIFICATION

FEDERAL

L-P-378	- Plastic Sheet and Strip, Thin Guage, Polyolefin
V-T-276	- Thread, Cotton
V-T-295	- Thread, Nylon
KK-L-271	- Leather, Cattlehide, Strap, Vegetable Tanned
UU-P-553	- Paper, Wrapping, Tissue
PPP-B-676	- Boxes, Setup

MILITARY

MIL-F-10884	- Fasteners, Snap

STANDARDS

FEDERAL

FED-STD-151	- Metal; Test Methods
FED-STD-191	- Textile Test Methods
FED-STD-751	- Stitches, Seams, and Stitching

MILITARY

MIL-STD-105	- Sampling Procedures and Tables For Inspection By Attributes
MIL-STD-129	- Marking for Shipment and Storage
MS27981	- Fastener, Snap; Style 2A (Small Wire Spring Clamp Type)

DRAWINGS

MARINE CORPS

695182A0000	- Belt, Man's: Black, With Shoulder Straps; Ceremonial Troop's (Marine Corps Officers)

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

LAWS AND REGULATIONS

U. S. Postal Service Manual

(Copies of the manual may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402).

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification Rule

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606).

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P. Street, N. W., Washington, D. C. 20026.)

3. REQUIREMENTS

3.1 Standard sample. The standard sample is furnished solely for guidance and information to the contractor (see 6.6). Variation from this specification may appear in the sample, in which case the specification shall govern.

3.2 First article. Unless otherwise specified (see 6.2), before production is commenced a sample of the finished belt (waist belt and shoulder strap with attachments) shall be submitted or made available to the contracting officer or his authorized representative for approval. The approval of the first article authorizes commencement of production, but does not relieve the contractor of responsibility for compliance with all applicable provisions of this specification. The first article shall be manufactured by the contractor in the same facilities to be used for the manufacture of the production items.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

3.3 Materials.

3.3.1 Poromeric. The basic material for all components of the waist belt and shoulder strap except metal components shall be a black poromeric material (see 6.3), 0.055 to 0.065 inch thick with a smooth high gloss finish. Embossing or printing shall not be permitted.

3.3.2 Leather. The leather shall be 4/64 inch thick and shall conform to type IV, class 1 of KK-L-271, except that the thickness tolerance shall be plus 1/64, minus 1/128 inch. The grain and flesh sides of the leather shall be natural in color and shall be a smooth finish. Embossing or printing shall not be permitted.

3.3.3 Sealer. A black shade aqueous solution sealer shall be used after fabrication of the components for finishing the smooth edges of the poromeric/leather material.

3.3.4 Copper base alloys. The buckles and buttons (see 3.5.4) shall be made of a copper base alloy having a chemical composition of 84.0 to 86.0 percent copper, 0.05 percent maximum lead, 0.50 percent maximum iron, 0.15 percent maximum total other elements and the remaining percent zinc. The copper base alloy shall be tested as specified in 4.5.1. The copper base alloy shall be free from pits, scale (including red oxide), dents, nicks, cracks, deep scratches, segregation, and foreign inclusions which cannot be removed in later processing.

3.3.5 Adhesive. The adhesive (see 6.5) shall be a natural or synthetic rubber solvent cement or synthetic resin cement.

3.3.6 Fastener, snap. The snap fasteners shall conform to style 2A, finish 2 of MIL-F-10884 and MS27981 and shall consist of the following components: button - 1B, socket - 3B, stud - 4B, and eyelet - 7B. The buttons shall have a black high gloss finish to match the basic material in 3.3.1.

3.3.7 Thread, cotton. The thread for all stitching operations shall be cotton, glazed finish, ticket No 10, 4-ply conforming to requirements for type III B of V-T-276. As an alternate, nylon thread conforming to type II, class A, size E of V-T-295 may be used.

3.3.7.1 Color and colorfastness. The thread shall be dyed shade black, AA, Cable 66043. The dyed thread shall show good fastness to light when tested as specified in the thread specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

3.4 Design. The belt shall be the U. S. Marine Corps design shown on Drawing No. 695182A0000, consisting of a waist belt and shoulder strap with one buckle (with center bar and two-hook type tongues; two-prong hook) for fastening belt, one buckle (with center bar and single tongue) for attaching the shoulder strap to shoulder strap extension, 3 buttons with washers, two required for attaching shoulder strap and shoulder strap extension to shoulder strap tab and one required for securing end of belt to body of belt and two "Dee" Rings secured to waist belt by waist belt tab for attaching shoulder strap components to waist belt.

3.5 Construction. The construction shall conform in all respects to Drawing No. 695182A0000 and as specified herein.

3.5.1 Class 1. The class 1 belt shall consist of two plies of the poromeric material specified in 3.3.1 cemented together back-to-back with the adhesive specified in 3.3.5. All poromeric components shall have rounded edges. The adhesive is required for cementing together plies of the poromeric material in order to obtain the required thickness (see 3.7).

3.5.2 Class 2. The class 2 belt shall consist of one ply of poromeric material (3.3.1) and one ply of leather (3.3.2), with the flesh side of the leather cemented to the back of the poromeric with the adhesive specified in 3.3.5. All poromeric/leather components shall have rounded edges. The adhesive is required for cementing together the plies in order to obtain the required thickness (see 3.7).

3.5.3 Stitches and stitching. The stitch and stitching type specified herein shall conform to FED-STD-751. The number of stitches per inch as specified indicates the minimum and maximum number permitted. Stitch type 301 and 7 to 8 stitches per inch shall be used for all stitching. Thread breaks in stitching shall be backstitched not less than 1 inch at each break. Stitching shall be backstitched at the ends to prevent raveling. Thread tension shall be maintained properly so that there will be no loose stitching and the lock will be embedded in the center of the sewed material. All thread ends shall be trimmed. Unless otherwise specified herein, edge stitching shall be 1/8 ± 1/32 inch from the edge.

3.5.4 Metal components. The following metal components for the belt and shoulder strap shall be fabricated of the copper base alloys specified in 3.3.4:

Buckle with center bar and two-hook type tongues; two-prong hook (one each required for fastening belt).

Buckle with center bar and single tongue (one required for joining shoulder strap to shoulder strap extension).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

Button with washer (two required for attaching shoulder strap and shoulder strap extension to shoulder strap tab).

Button with washer (one required for securing end of belt to body of belt).

"Dee" ring secured to waist belt by waist belt tab (two required for attaching shoulder strap components to waist belt).

NOTE: See Drawing No. 695182A0000 for design and dimensions of above metal components.

3.5.4.1 Finished requirements. All surfaces and edges of the metal components shall be clean, smooth and free from burrs, drag step, tool marks, roughness, sharp edges and corners. In addition, all outer surfaces and edges of the metal components visible on the outside of the waist belt and shoulder strap shall be highly polished to a mirror-like finish.

3.5.5 Snap fasteners. The hole punched before inserting applicable snap fastener tube shall be smaller than the outside diameter of the tube so that the tube must be forced through the hole. All fasteners shall be securely clinched.

3.6 Marking. The belt size shall be indented in the leather with 3/16 inch high characters, 1 to 1-1/2 inches from the end of the belt.

3.7 Finished measurements. The finished measurements of the waist belt and shoulder strap shall conform to the measurements specified in Drawing No. 695182A0000. The thickness of the cemented 2-ply poromeric or poromeric and leather components shall be 1/8 ± 1/32 inch.

3.8 Workmanship. The finished belt with shoulder strap shall conform to the quality and grade of product established by this specification, and shall be well made and finished free from any defect which may adversely affect appearance or serviceability. The occurrence of defects shall not exceed the applicable acceptable quality levels (AQL's).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification. Components and materials listed below may be accepted on the basis of a contractor's certification of compliance for characteristics indicated.

Component	Characteristic	Rqmt. Para
Poromeric material	Material identification	3.3.1 and 6.3
Sealer	Material identification	3.3.3
Adhesive	Material identification	3.3.5

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When first article is required, inspection shall be made of completely fabricated belt for all provisions of this specification.

4.4 Quality conformance inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105 except where otherwise indicated hereinafter.

4.4.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase documents. Testing shall be performed on components listed in Table I for characteristics noted. The method of testing specified in FED-STD-191 wherever applicable.

4.4.2 End item examination. The end item shall be examined for defects in 4.4.2.1 and 4.4.2.2. The inspection levels and AQL's shall be as specified in 4.4.2.3. The sample unit for these examinations shall be one completely fabricated belt. The lot size shall be expressed in units of one belt.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

TABLE I. - Component Testing

Component and lot expressed in terms of	Characteristic	Reqmt Para	Test Method	Rqmt appl to smpl unit	Rqmt appl to lot avg	Determ per smpl unit	Results Reported as	Sample Unit	Insp Lvl	AQL
Copper base alloy (one pound)	Chemical composition	3.3.4	4.5.1	--	X	2 (Composite) for ea. element	To nearest 0.1 percent	8-ozs. or equivalent	S-1	N/A

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

4.4.2.1 Defects. Defects shall be classified as follows, except when an asterisk appears, the defect shall be classified as Major when seriously affecting serviceability or appearance and Minor when affecting serviceability or appearance but not seriously.

Examine	Defect	Classification		
		Major	Minor	
			A	B
Finish				
Poromeric/ leather components	Not specified color.	X		
	Color not uniform.		X	
	Embossed or printed.	X		
	Face/grain side not smooth finished.	X		
	Tacky or cracky finish.	X		
	Any part refinished after assembly; strap or belt recoated.	*		
Metal components	Not specified finish or areas of no finish.	X		
Material	Any components not fabricated of the specified material.	X		
Construction and Workmanship	Any component or assembly omitted or misplaced, operation omitted or not properly performed (i.e., fastener misplaced so that male portion of fastener is not in alignment with female part to effect closure.	*		
	Any part fractured, ripped, punctured, torn, defective, malformed or damaged.	*		
	Belt not fabricated with face side on exterior of belt.	X		
	Belt not fabricated with grain side on interior of belt (class 2 only).		X	
	Not edged, or irregularly edged, affecting appearance.		*	
Quality of poromeric/ leather	Not high gloss or lightly snuffed. (poromeric only)	X		
	Hole where not required, cut or rupture.	X		
	Brand mark, scar or brittle	*		
	Abraded, scratched, or other finish damage.	*		

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification		
		Major	Minor	
			A	
Quality of Poromeric/ leather (cont'd)	Any wrinkle.	*		
	Any cuts.	*		
Metal Assembly	Snap fastener cap or eyelet not securely affixed, and may become detached in service.	X		
	Snap fastener cap or eyelet not securely attached but will adequately retain assembly.		X	
	Snap fastener does not function.	X		
	Sharp edge, burr or metal sliver.	X		
Marking	Missing, illegible, incorrect, not applied in specified manner, misplaced, or not specified type or size.		X	
	Size marking shows through to face side of belt.	X		
Cleanliness	Any nonremovable stain or spot.	X		
	Any spot or stain removable with cleaning agent.		X	

4.4.2.2 Dimensional examination. The belt shall be examined for defects in dimensions including thickness of poromeric/leather. Any dimension not within the established tolerance shall be classified as a defect.

4.4.2.3 Inspection level and AQL. The inspection levels and AQL's expressed in defects per hundred units (DHU) shall be as follows:

Examination	Inspection Level	AQL	
		Major	Total
For defects applicable to 4.4.2.1	II	2.5	6.5
For defects applicable to 4.4.2.2	S-3	-	4.0

4.4.3 Examination of packaging requirements. An examination shall be made to determine that the packaging, packing, and marking comply with the Section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

fully prepared for delivery with the exception that it need not be closed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 DHU.

Examine	Defects
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence or method of application
Materials	Any component missing or not as specified. Any component damaged, affecting serviceability.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, loose strapping, improper taping, inadequate stapling. Bulged or distorted container.
Content	Number of belts per package is more or less than required. 1/

4.5 Tests.

4.5.1 Chemical composition test. Chemical composition shall be determined in accordance with test method 111 of FED-STD-151. Results shall be evaluated to determine compliance with the requirements specified in 3.3.4.

5. PACKAGING

5.1 Preservation and packaging. Preservation and packaging shall be level A or commercial as specified (see 6.2).

1/ For this defect one package shall be examined from each shipping container in the sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. Each belt shall be coiled to approximately 7 inches in diameter. The shoulder strap shall be coiled and placed within the coiled belt and together they shall be wrapped in a double thickness of antitarnish tissue paper conforming to type II of UU-P-553. The wrapped belt shall then be placed within a close fitting polyethylene bag conforming to type I, class 1 of L-P-378. Heat seal to effect closure. Prior to heat sealing excess air shall be evacuated from the bag. The bagged belt shall be placed within a close fitting set-up paper board box conforming to type I, variety 1 of PPP-B-676. Closure shall be in accordance with the appendix to the box specification.

5.1.2 Commercial. Commercial packaging shall afford adequate protection against deterioration and physical damage during shipment from the supply source to the first receiving activity. The contractor may use his standard practice provided it meets the requirements specified for commercial packing.

5.2 Packing.

5.2.1 Commercial. Belts shall be packed in a manner to insure carrier acceptance and safe delivery at destination. Containers shall be in accordance with Uniform Freight Classification Rules, National Motor Freight Classification Rule and U. S. Postal Service Manual or regulations of other carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, the shipping containers shall be marked in accordance with the requirements of MIL-STD-129 and the following:

NSN
Size
Contract Number
Name of Contractor

Each box (see 5.1.1) shall have the nomenclature, the stock number, the size and contract number packaged therein, legibly printed or stamped in black directly across the center side of the box or on a white paper label attached to the side of box so that it is readable on the outside of box.

6. NOTES

6.1 Intended use. The belt with shoulder strap is intended for use by Marine Corps male officers assigned to ceremonial duty, or as an item of general wear.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

6.2.1 Procurement requirements.

(a) Title, number and date of this specification.
(b) Class and size required (see 1.2).
(c) When a first article is not required (see 3.2).
(d) Selection of applicable levels of packaging (see 5.1).

6.2.2 Contract data requirements. Data conforming to Data Item Description DI-R-4803, DI-R-4805, DI-T-4901, DI-T-4902, DI-T-4903 and DI-T-4904 will usually be required for delivery in connection with this specification. When so required, such data will be specified for delivery on DD Form 1423 included in the contract.

6.3 Poromeric material. The poromeric material produced by Inmont Corporation, under the trade name "Porvair Plus .059", product designation Hi-Gloss black smooth, has proved to be satisfactory for the purpose for which it is intended.

6.4 Metal components. The metal hardware components listed in 3.5.4 are commercially known as "Deluxe Hardware:.

6.5 Adhesive. Metroband shoe adhesive No. C-273 has proved satisfactory for the purpose for which it is intended.

6.6 Standard sample. The standard sample and color sample may be obtained from the procuring activity or as directed by the contracting officer.

6.7 First article. Examination, tests and approval shall be as specified by the contracting officer, (see 3.2).

6.8 Personal identification marking. The belt upon being designated as an item of general wear shall show the officer's name on a card inserted under the plastic name plate located as shown on Drawing No. 695182A0000.

6.9 Supersession data. This specification includes the requirements of Purchase Description PD-113A (MCSA) of 27 Sep 1971.

Preparing Activity
Navy - MC
Project No. 8440-N152

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-B-29378(MC) Belt, Man's: Ceremonial, Officers

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED S/N 0102-LF-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Navy
Headquarters U. S. Marine Corps
Washington, D. C. 20380

POSTAGE AND FEES PAID
Department of the Navy
DOD 317

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commandant of the Marine Corps
Headquarters U. S. Marine Corps
Code LMA-1
Washington, D. C. 20380

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.