INCH-POUND

MIL-B-29378A(MC)
28 February 1994
SUPERSEDING
MIL-B-29378(MC)
22 March 1979

MILITARY SPECIFICATION

BELT, MAN'S: CEREMONIAL, OFFICERS

This specification is approved for use by the U. S. Marine Corps and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the minimum requirements for a poromeric waist belt with detachable and adjustable shoulder strap.

1.2 Classification. The belt shall be of one type in the following classes, and sizes, as specified (see 6.2).

1.2.1 Class.

Class 1 - Standard (Poromeric)

Class 2 - Optional (Poromeric and Leather)

1.2.2 Sizes.

Schedule of waist sizes

32	40
34	42
36	44
38	46

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to the Commander, Marine Corps Systems Command, PSE-C, Quantico, VA 22134-5010 by using the self addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 8440

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

A-A-52094	- Thread, Cotton
L-P-378	- Plastic Sheet and Strip, Thin Gage, Polyolefin
V-T-295	- Thread, Nylon
KK-L-271	- Leather, Cattlehide, Strap, Vegetable Tanned
UU-P-553	- Paper, Wrapping, Tissue
PPP-B-676	- Boxes, Setup

MILITARY

MIL-F-10884	- Fasteners, Snap

STANDARDS

FEDERAL

FED-STD-151	- Metal, Test Methods
FED-STD-191	- Textile test Methods
FED-STD-751	- Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	- Sampling Procedures and Tables For Inspection By Attributes
MIL-STD-129	- Marking for Shipment and Storage
MS27981	- Fastener, Snap; Style 2A (Small Wire Spring Clamp Type)

DRAWINGS

MARINE CORPS

695182A0000	- Belt, Man's: With Shoulder Straps; Ceremonial Troop's (Marine Corps Officers)

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

2.2 Non-Government publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of documents which are DoD adopted shall be those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TEST MATERIALS

ASTM D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services).

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Guide sample. Guide samples are furnished solely for guidance and information to the contractor (see 6.3). Variations from this specification may appear in the sample, in which case the specification shall govern.

3.2 First article. When specified (see 6.2), before production is commenced, the first article, consisting of the number of belts specified by the procuring activity (see 6.2) shall be submitted, or made available to the contracting officer or his authorized representative for inspection. The approval of the first article authorizes the commencement of production, but does not relieve the contractor of responsibility for compliance with all provisions of this specification. The first article shall be manufactured by the contractor in the same facilities to be used for the manufacture of the production items.

3.3 Materials.

3.3.1 Poromeric. The basic material for all components of the waist belt and shoulder strap, except metal components, shall be a black poromeric material (see 6.3), 0.055 to 0.065 inch thick with a smooth high gloss finish. Embossing or printing shall not be permitted.

3.3.2 Leather. The leather shall be 4/64 inch thick and shall conform to type IV, class 1 of KK-L-271, except that the thickness tolerance shall be plus 1/64, minus 1/128 inch. The grain and flesh sides of the leather shall be natural in color and shall be a smooth finish. Embossing or printing shall not be permitted.

3.3.3 Sealer. A black shade aqueous solution sealer shall be used after fabrication of the components for finishing the smooth edges of the poromeric/leather material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

3.3.4 Copper base alloys. The buckles and buttons (see 3.5.4) shall be made of a copper base alloy having a chemical composition of 84.0 to 86.0 percent copper, 0.05 percent maximum lead, 0.05 percent maximum iron, 0.15 percent maximum total other elements and the remaining percent zinc. The copper base alloy shall be tested as specified in 4.5.1. The copper base alloy shall be free from pits, scale, (including red oxide), dents, nicks, cracks, deep scratches, segregation, and foreign inclusions which cannot be removed in later processing.

3.3.5 Adhesive. The adhesive (see 6.5) shall be a natural or synthetic rubber solvent cement or synthetic resin cement.

3.3.6 Fastener, snap. The snap fasteners shall conform to style 2A, finish 2 of MIL-F-10884 and MS27981 and shall consist of the following components: buttons - 1B, socket - 3B, stud - 4B, and eyelet - 7B. The buttons shall have a black high gloss finish to match the basic material in 3.3.1.

3.3.7 Thread, cotton. The thread for all stitching operations shall be cotton, glazed finish, ticket No. 10, 4-ply conforming to requirements for type III B of A-A-52094. As an alternate, nylon thread conforming to type II, class A, size E of V-T-295 may be used.

3.3.7.1 Color and colorfastness. The thread shall be dyed shade black, AA, Cable 66043. The dyed thread shall show good fastness to light when tested as specified in the thread specification.

NOTE: See DoD Standard color Card of Official Standardization Shades for Sewing Threads 1968.

3.4 Design. The belt shall be the U. S. Marine Corps design shown on Drawing No. 695182A0000, consisting of a waist belt and shoulder strap with one buckle (with center bar and two-hook type tongues; two-prong hook) for fastening belt, one buckle (with center bar and single tongue) for attaching the shoulder strap to shoulder strap extension, 3 buttons with washers, two required for attaching shoulder strap and shoulder strap extension to shoulder strap tab and one required for securing end of belt to body of belt and two "Dee" Rings secured to waist belt by waist belt tab for attaching shoulder strap components to waist belt.

3.5 Construction. The construction shall conform in all respects to Drawing No. 695182A0000 and as specified herein.

3.5.1 Class 1. The class 1 belt shall consist of two plies of the poromeric material specified in 3.3.1 cemented together back-to-back with adhesive specified in 3.3.5. the adhesive is required for cementing together plies of the poromeric material in order to obtain the required thickness (see 3.7).

3.5.2 Class 2. The class 2 belt shall consist of one ply of poromeric material (3.3.1) and one ply of leather (3.3.2), with the flesh side of the leather cemented to the back of the poromeric with the adhesive specified in 3.3.5. The adhesive is required for cementing together the plies in order to obtain the required thickness (see 3.7).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

3.5.3 Stitches and stitching. The stitch and stitching type specified herein shall conform to FED-STD-751. The number of stitches per inch as specified indicates the minimum and maximum number permitted. Stitch type 301 and 7 to 8 stitches per inch shall be used for all stitching. Thread breaks in stitching shall be backstitched not less than 1 inch at each break. Stitching shall be backstitched at the ends to prevent raveling. Thread tension shall be maintained properly so that there will be no loose stitching and the lock will be embedded in the center of the sewed material. All thread ends shall be trimmed. Unless otherwise specified herein, edge stitching shall be 1/8 ± 1/32 inch from the edge.

3.5.4 Metal components. The following metal components for the belt and shoulder strap shall be fabricated of the copper base alloys specified in 3.3.4:

Buckle with center bar and two-hook type tongues; two-prong hook (one each required for fastening belt.)

Buckle with center bar and single tongue (one required for joining shoulder strap to shoulder strap extension).

Button with washer (two required for attaching shoulder strap and shoulder strap extension to shoulder strap tab).

Button with washer (one required for securing end of belt to body of belt).

"Dee" ring secured to waist belt by waist belt tab (two required for attaching shoulder strap components to waist belt).

NOTE: See Drawing No. 695182A0000 for design and dimensions of above metal components.

3.5.4.1 Finished requirements. All surface and edges of the metal components shall be clean, smooth and free from burrs, drag step, tool marks, roughness, sharp edges and corners. In addition, all outer surfaces and edges of the metal components visible on the outside of the waist belt and shoulder strap shall be highly polished to a mirror-like finished.

3.5.5 Snap fasteners. The hole punched before inserting applicable snap fastener tube shall be smaller than the outside diameter of the tube so that the tube must be forced through the hole. All fasteners shall be securely clinched.

3.6 Marking. The belt size shall be indented in the leather with 3/16 inch high characters, 1 to 1-1/2 inches from the buckle end of the belt.

3.7 Finished measurements. The finished measurements of the waist belt and shoulder strap shall conform to the measurements specified in Drawing No. 695182A0000. The thickness of the cemented 2-ply poromeric or poromeric and leather components shall be 1/8 ± 1/32 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

3.8 Workmanship. The finished belt with shoulder strap shall conform to the quality and grade of product established by this specification, and shall be well made and finished free from any defect which may adversely affect appearance or serviceability. The occurrence of defects shall not exceed the applicable acceptable quality levels (AQL's).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspection set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification. Components and materials listed below may be accepted on the basis of a contractor's certification of compliance for characteristics indicated.

Component	Characteristic	Rqmt. Para
Poromeric material	Material identification	3.3.1 and 6.3
Sealer	Material identification	3.3.3
Adhesive	Material identification	3.3.5

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When first article is required, inspection shall be made of completely fabricated belt for all provisions of this specification.

4.4 Quality conformance inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105 except where otherwise indicated hereinafter.

4.4.1 End item examination. The end item shall be examined for defects in 4.4.1.1 and 4.4.1.2. The inspection levels and AQL's shall be as specified in 4.4.1.3. The sample unit for these examinations shall be one completely fabricated belt. The lot size shall be expressed in units of one belt.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

4.4.1.1 Defects. Defects shall be classified as follows, except when an asterisk appears, the defect shall be classified as Major when seriously affecting serviceability or appearance and Minor when affecting serviceability or appearance but not seriously.

Examine	Defect	Classification Major	Classification Minor
Finish Poromeric/ Leather components	Not specified color	101	
	Color not uniform		201
	Embossed or printed	102	
	Face/grain side not smooth finished.	103	
	Tacky or crackly finish.	104	
	Any part refinished after assembly; strap or belt	1	
Metal components	Not specified finish or areas of no finish.	105	
Material	Any components not fabricated of the specified material.	106	
Construction and Workmanship	Any component or assembly omitted or misplaced, operation omitted or not properly performed (i.e., fastener misplaced so that male portion of fastener is not in alignment with female part to effect closure.	2	
	Any part fractured, ripped, punctured torn, defective, malformed or damaged	3	
	Belt not fabricated with face side on exterior of belt.	107	
	Belt not fabricated with grain side on interior of belt (class 2 only).		202
	Not edged, or irregularly edged, affecting appearance.		4
Quality of Poromeric/ Leather	Not high gloss or lightly snuffed (poromeric only).	108	
	Hole where not required, cut or rupture.	109	
	Brand mark, scar or brittle.	5	
	Abraded, scratched, or other finish damage.	6	
	Any wrinkle.	7	

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

Examine	Defects	Classification Major	Classification Minor
Quality of Poromeric/ Leather (cont'd)	Any cuts.	8	
Metal Assembly	Snap fastener cap or eyelet not securely affixed, and may become detached in service.	110	
	Snap fastener cap or eyelet not securely attached but will adequately retain assembly.		203
	Snap fastener does not function.	111	
	Sharp edge, burr or metal sliver.	112	
Marking	Missing, illegible, incorrect, not applied in specified manner, misplaced, or not specified type or size		204
	Size marking shows through to face side of belt.	113	
Cleanliness	Any nonremovable stain or spot.	114	
	Any spot or stain removable with cleaning agent.		205

4.4.1.2 Dimensional examination. The belt shall be examined for defects in dimensions including thickness of poromeric/leather. Any dimension not within the established tolerance shall be classified as a defect.

4.4.1.3 Inspection level and AQL. The inspection levels and AQL's shall be as noted in the contract or order.

4.4.2 Examination of packaging requirements. An examination shall be made to determine that the packaging, packing, and marking comply with the Section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be closed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be as stated in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

Examine	Defects
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence or method of application.
Materials	Any component missing or not as specified.
	Any component damaged, affecting serviceability.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, loose strapping, improper taping, inadequate stapling. Bulged or distorted container.
Content	Number of belts per package is more or less than required. 1/

4.4 Tests.

4.4.1 Chemical composition test. Chemical composition shall be determined in accordance with test method 111 of FED-STD-151. Results shall be evaluated to determine compliance with the requirements specified in 3.3.4.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or commercial as specified (see 6.2).

1/ For this defect one package shall be examined from each shipping container in the sample.

5.1.1 Level A. Each belt shall be coiled to approximately 7 inches in diameter. The shoulder strap shall be coiled and placed within the coiled belt and together they shall be wrapped in a double thickness of antitarnish tissue paper conforming to type II of UU-P-553. The wrapped belt shall then be placed within a close fitting polyethylene bag conforming to type I, class 1 of L-P-378. Heat seal to effect closure. Prior to heat sealing excess air shall be evacuated from the bag. The bagged belt shall be placed within a close fitting set-up paper board box conforming to type I, variety 1 of PPP-B-676. Closure shall be in accordance with the appendix to the box specification.

5.1.2 Commercial. Commercial packaging shall be in accordance with ASTM-D-3951.

5.2 Packing.

5.2.1 Commercial. Belts preserved as specified in 5.1 shall be packed in accordance with ASTM-D-3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

5.3 Marking. In addition to any special marking required by the contract or order, the shipping containers shall be marked in accordance with the requirements of MIL-STD-129 and the following:

NSN
Size
Contract Number
Name of Contractor

Each box (see 5.1.1) shall have the nomenclature, the stock number, the size and contract number packaged therein, legibly printed or stamped in black directly across the center side of the box or on a white paper label attached to the side of box so that it is readable on the outside of box.

6. NOTES

(Information in this section is of a general or explanatory nature which may be helpful, but is not mandatory).

6.1 Intended use. The belt with shoulder strap is intended for use by Marine Corps male officers assigned to ceremonial duty, or as an item of general wear.

6.2 Ordering data. Procurement documents should specify the following:

6.2.1 Procurement requirements.

(a) Title, number and date of this specification.
(b) Class and size required (see 1.2).
(c) When a first article is not required (see 3.2).
(d) Selection of applicable levels of packaging (see 5.1).

6.3 Poromeric material. The poromeric material produced by Inmont Corporation, under the trade name "Porvair Plus .059", product designation Hi-Gloss black smooth, has proved to be satisfactory for the purpose for which it is intended.

6.4 Metal components. The metal hardware components listed in 3.5.4 are commercially known as "Deluxe Hardware".

6.5 Adhesive. Metroband shoe adhesive No. C-273 has proved satisfactory for the purpose for which it is intended.

6.6. Standard sample. The standard sample and color sample may be obtained form the procuring activity or as directed by the contracting officer.

6.7 First article. Examination, tests, and approval shall be as specified by the contracting officer, see 3.2).

6.8 Personal identification marking. The belt upon being designated as an item of general wear shall show the officer's name on a card inserted under the plastic name plate located as shown on Drawing No. 695182A0000.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

6.9 Subject term (key word) listing.

Belt
Ceremonial
Poromeric

Preparing Activity
Navy - MC
Project No. 8440-N210

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-B-29378A(MC)	28 February 1994

3. DOCUMENT TITLE

BELT, MAN'S: CEREMONIAL OFFICERS

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON
COMMANDER	(912) 439-6560	567-6560
c. ADDRESS (Include Zip Code) MARINE CORPS LOGISTICS BASES, CODE 855, 814 RADFORD BOULEVARD ALBANY GA 31704-1128	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.