INCH-POUND

MIL-DTL-29378B(MC)
6 June 2008
SUPERSEDING
MIL-B-29378A(MC)
28 February 1994

MILITARY SPECIFICATION

BELT, MAN'S: CEREMONIAL, OFFICERS (SAM BROWNE)

This specification is approved for use by the U. S. Marine Corps and is available for use by all Departments and Agencies of the Department of Defense.

1. Scope

1.1. Scope. This specification covers the minimum requirements for a poromeric and leather waist belt with detachable and adjustable shoulder strap.

1.2. Classification. The belt should be of one type, poromeric and leather, in the following sizes, as specified.

1.2.1. Sizes.

Schedule of waist sizes		Schedule of shoulder strap sizes	
28	38	30	37
30	40	31	38
32	42	32	39
34	44	33	40
36	46	34	41
		35	42
		36	

Comments, suggestions, or questions on this document should be address to: Marine Corps Systems Command, PM-ICE, 2200 Lester St., Quantico, VA 22134-5010. Since contact information can change, you may want to verify the currency of this address information using the ASSIST online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1. General. The documents listed in this section are specified in section 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort hast been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2. Government documents.

2.2.1. Specifications, standards, and handbooks. The following specifications, standards and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents should be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

A-A-52094	- Thread, Cotton
A-A-3174	- Plastic Sheet and Strip, Polyolefin
V-T-295	- Thread, Nylon
A-A-1249	- Paper, Wrapping, Tissue
PPP-B-676	- Boxes, Setup

MILITARY

MIL-DTL-10884	- Fasteners, Snap
MIL-DTL-32068	- Leather, Cattlehide, Strap Vegetable-tanned

STANDARDS

MILITARY

MIL-STD-1916	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Military Marking for Shipment and Storage

DRAWINGS

THE INSTITUTE OF HERALDRY

4-4-102	- Sam Browne Belt, USMC

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

2.2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are issues of the documents cited in the solicitation.

(Non-government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other information services.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM-E1282 - Metal, Test Methods
ASTM-D-6193 - Stitches, Seams, and Sewing

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103. 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959)

AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA

NASM27981 – Fasteners, Snap, Style 2A (Small Wire Spring Clamp Type)

(Application for copies of NASM publications should be addressed to the Aerospace Industries Association of America, 1250 Eye Street, N.W., Suite 1200, Washington, DC 20005.)

2.3.1 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification will take precedence.

3. REQUIREMENTS

3.1 Guide sample. Guide samples are furnished solely for guidance and information to the contractor. Variations from this specification may appear in the sample, in which case the specification shall govern.

3.2 First article. When specified, before production is commenced, the first article, consisting of the number of belts specified by the procuring activity shall be submitted, or made available to the contracting officer or his authorized representative for inspection. The approval of the first article authorizes the commencement of production, but does not relieve the contractor of responsibility for compliance with all provisions of this specification. The first article shall be manufactured by the contractor in the same facilities to be used for the manufacture of the production items.

3.3 Materials.

3.3.1 Poromeric. The basic material for all components of the waist belt and shoulder strap, except metal components, shall be a black poromeric material (see 6.3), 0.055 to 0.065 inch thick with a smooth high gloss finish. Embossing or printing shall not be permitted.

3.3.2 Leather. The leather shall be 4/64 inch thick and shall conform to type IV, class 1 of KK-L-271, except that the thickness tolerance shall be plus 1/64, minus 1/128 inch. The grain and

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

flesh sides of the leather shall be black or dark brown in color, shall be a smooth finish and shall show good colorfastness . Embossing or printing shall not be permitted.

3.3.3 Sealer. A black shade aqueous solution sealer shall be used after fabrication of the components for finishing the smooth edges of the poromeric/leather material.

3.3.4 Copper base alloys. The buckles and buttons (see 3.5.4) shall be made of a copper base alloy having a chemical composition of 84.0 to 86.0 percent copper, 0.05 percent maximum lead, 0.05 percent maximum iron, 0.15 percent maximum total other elements and the remaining percent zinc. The copper base alloy shall be free from pits, scale, (including red oxide), dents, nicks, cracks, deep scratches, segregation, and foreign inclusions which cannot be removed in later processing. Gold plating is optional.

3.3.5 Adhesive. The adhesive (see 6.5) shall be a natural or synthetic rubber solvent cement or synthetic resin cement.

3.3.6 Fastener, snap. The snap fasteners shall conform to style 2A, finish 2 of MIL-F-10884 and NAS27981 and shall consist of the following components: buttons – 1B, socket – 3B, stud – 4B, and eyelet – 7B. The buttons shall have a black high gloss finish to match the basic material in 3.3.1.

3.3.7 Thread, cotton. The thread for all stitching operations shall be cotton, glazed finish, ticket No. 10, 4-ply conforming to requirements for type III B of A-A-52094. As an alternate, nylon thread conforming to type II, class A, size E of V-T-295 may be used.

3.3.7.1 Color and colorfastness. The thread shall be dyed black. The dyed thread shall show good fastness to light when tested as specified in the thread specification.

3.4 Design. The belt shall be the U. S. Marine Corps design shown on Drawing No. 4-4-102, consisting of a waist belt and shoulder strap with one buckle (with center bar and two-hook type tongues; two-prong hook) for fastening belt, one buckle (with center bar and single tongue) for attaching the shoulder strap to shoulder strap extension, 3 buttons with washers, two required for attaching shoulder strap and shoulder strap extension to shoulder strap tab and one required for securing end of belt to body of belt and two “Dee” Rings secured to waist belt by waist belt tab for attaching shoulder strap components to waist belt.

3.5 Construction. The construction shall conform in all respects to Drawing No. 4-4-102 and as specified herein.

3.5.1 Class 1. The belt shall consist of one ply of poromeric material (3.3.1) and one ply of leather (3.3.2), with the flesh side of the leather cemented to the back of the poromeric with the adhesive specified in 3.3.5. The adhesive is required for cementing together the plies in order to obtain the required thickness (see 3.7).

3.5.2 Stitches and stitching. The stitch and stitching type specified herein shall conform to ASTM-D-6193. The number of stitches per inch as specified indicates the minimum and maximum number permitted. Stitch type 301 and 6 stitches per inch shall be used for all stitching. Thread breaks in stitching shall be backstitched not less than 1 inch at each break. Stitching shall be backstitched at the ends to prevent raveling. Thread tension shall be maintained properly so that there will be no loose stitching and the lock will be embedded in the

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

center of the sewed material. All thread ends shall be trimmed. Unless otherwise specified herein, edge stitching shall be 3/16 ± 1/32 inch from the edge.

3.5.3 Metal components. The following metal components for the belt and shoulder strap shall be fabricated of the copper base allows specified in 3.3.4:

Buckle with center bar and two-hook type tongues; two-prong hook (one each required for fastening belt.)

Buckle with center bar and single tongue (one required for joining shoulder strap to shoulder strap extension).

Button with washer (two required for attaching shoulder strap and shoulder strap extension to shoulder strap tab).

Button with washer (one required for securing end of belt to body of belt).

"Dee" ring secured to waist belt by waist belt tab (two required for attaching shoulder strap components to waist belt).

NOTE: See Drawing No. 4-4-102 for design and dimensions of above metal components.

3.5.4. Finished requirements. All surface and edges of the metal components shall be clean, smooth and free from burrs, drag step, tool marks, roughness, sharp edges and corners. In addition, all outer surfaces and edges of the metal components visible on the outside of the waist belt and shoulder strap shall be highly polished to a mirror-like finish. The highly polished finish does not apply to the button. The button shall be black.

3.5.5 Snap fasteners. The hole punched before inserting applicable snap fastener tube shall be smaller than the outside diameter of the tube so that the tube must be forced through the hole. All fasteners shall be securely clinched.

3.6 Marking. The size, name of manufacturer, NSN or Certification Number and contract number (if applicable) shall be ink stamped or gold leafed on the inside of both the belt and the shoulder strap.

3.7 Finished measurements. The finished measurements of the waist belt and shoulder strap shall conform to the measurements specified in Drawing No. 4-4-102. The thickness of the poromeric and leather components shall be 1/8 ± 1/32 inch.

3.8 Workmanship. The finished belt with shoulder strap shall conform to the quality and grade of product established by this specification, and shall be well made and finished free from any defect which may adversely affect appearance or serviceability. The occurrence of defects shall not exceed the applicable acceptable quality levels (AQL's).

4. VERIFICATION

4.1 Classification of Inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Conformance inspection (see 4.4).

4.2 Inspection conditions. Unless otherwise specified, all inspection shall be performed in accordance with the test conditions specified in 4.4 and 4.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

4.3 First article inspection. When first article is required, inspection shall be made of completely fabricated belt for all provisions of this specification.

4.4 Conformance inspection. Sampling for inspection shall be performed in accordance with MIL-STD-1916 except where otherwise indicated hereinafter.

4.4.1 End item examination. The end item shall be examined for defects in 4.4.1.1 and 4.4.1.2. The inspection levels and AQL's shall be as specified in 4.4.1.3. The sample unit for these examinations shall be one completely fabricated belt. The lot size shall be expressed in units of one belt.

4.4.1.1 Classification of defects. Defects shall be classified as follows, except when an asterisk appears, the defect shall be classified as Major when seriously affecting serviceability or appearance and Minor when affecting serviceability or appearance but not seriously.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification	
		Major	Minor
Finish Poromeric/ Leather components	Not specified color Color not uniform Embossed or printed Face/grain side not smooth finished. Tacky or crackly finish. Any part refinished after assembly; strap or belt	101 102 103 104 1	 201
Metal components	Not specified finish or areas of no finish	105	
Material	Any components not fabricated of the specified material.	106	
Construction and Workmanship	Any component or assembly omitted or misplaced, operation omitted or not properly performed (i.e., fastener misplaced so that male portion of fastener is not in alignment with female part to effect closure. Any part fractured, ripped, punctured torn, defective, malformed or damaged. Belt not fabricated with face side on exterior of belt. Not edged, or irregularly edged, affecting appearance.	2 3 107	 4
Quality of Poromeric/ Leather	Not high gloss or lightly snuffed (poromeric only). Hole where not required, cut or rupture. Brand mark, scar or brittle. Abraded, scratched, or other finish damage. Any wrinkle. Any cuts.	108 109 5 6 7 8	
Metal Assembly	Snap fastener cap or eyelet not securely affixed, and may become detached in service. Snap fastener cap or eyelet not securely attached but will adequately retain assembly. Snap fastener does not function. Sharp edge, burr or metal sliver.	110 111 112	 203
Marking	Missing, illegible, incorrect, not applied in specified manner, misplaced, or not specified type or size.		204

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification	
		Major	Minor
	Size marking shows through to face side of belt.	113	
Cleanliness	Any nonremovable stain or spot.	114	
	Any spot or stain removable with cleaning agent.		205

4.4.1.2 Dimensional examination. The belt shall be examined for defects in dimensions including thickness of poromeric/leather. Any dimension not within the established tolerance shall be classified as a defect.

4.4.1.3 Inspection level and AQL. The inspection levels and AQL's shall be as noted in the contract or order.

4.4.2 Examination of packaging requirements. An examination shall be made to determine that the packaging, packing, and marking comply with the Section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be closed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be as stated in the contract or order.

Examine	Defects
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence or method of application.
Materials	Any component missing or not as specified.
	Any component damaged, affecting serviceability.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, loose strapping, improper taping, inadequate stapling. Bulged or distorted container.
Content	Number of belts per package is more or less than required. 1/

1/ For this defect one package shall be examined from each shipping container in the sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

4.5 Tests.

4.5.1 Chemical composition test. Chemical composition shall be determined in accordance with test method ASTM-E1282. Results shall be evaluated to determine compliance with the requirements specified in 3.3.4.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(Information in this section is of a general or explanatory nature which may be helpful, but is not mandatory.)

6.1 Intended use. The belt with shoulder strap is intended for use by Marine Corps male officers assigned to ceremonial duty, or as an item of general wear.

6.2 Ordering data. Procurement documents should specify the following:

6.2.1 Procurement requirements.
(a) Title, number, and date of this specification.
(a) Class and size required (see 1.2).
(b) When a first article is not required (see 3.2).
(c) Selection of applicable levels of packaging (see 5.1).

6.3 Poromeric material. The poromeric material produced by Inmont Corporation, under the trade name “Porvair Plus .059”, product designation Hi-Gloss black smooth, has proved to be satisfactory for the purpose for which it is intended.

6.4 Metal components. The metal hardware components listed in 3.5.4 are commercially known as “Deluxe Hardware”.

6.5 Adhesive. Metroband shoe adhesive No. C-273 has proved satisfactory for the purpose for which it is intended.

6.6 First article. Examination, tests, and approval should be as specified by the contracting officer (see 3.2).

6.7 Subject term (key word) listing.

Belt
Ceremonial
Poromeric

6.8 Sets. It is suggested that the belt and shoulder strap be sold as a set, but that the sizes of each be interchangeable. (see 1.2.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

CUSTODIAN:
Navy - MC

PREPARING ACTIVITY:
Navy-MC
(Project No. 8440-2007-002)

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FSS

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:39Z
Check the source to verify that this is the current version before use.