INCH-POUND
A-A-59536
February 1, 2000

COMMERCIAL ITEM DESCRIPTION

BODY SHIELD, BALLISTIC

The General Services Administration has authorized the use of this Commercial Item Description for all Federal agencies.

1. SCOPE. This commercial item description covers the requirement for a ballistic body shield to be used by dismounted military personnel.

2. CLASSIFICATION. The ballistic body shield shall be of one type and size.

3. SALIENT CHARACTERISTICS.

3.1 General. The ballistic body shield, hereafter referred to as body shield, shall be the manufacturer's commercial product except for any changes necessary to comply with the government requirements.

3.2 Description. The ballistic body shield shall be of rectangular construction and have both opaque and transparent armor components. The ballistic resistant protective materials used to fabricate these components shall have a ballistic protection level of IIIA or better as defined in the National Institute of Justice's (NIJ) Ballistic Resistant Protective Materials NIJ Standard 0108.01 or current edition (see para. 7.1).

3.3 Item Configuration. The body shield shall meet the following criteria.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Defense Personnel Support Center, Clothing and Textiles Directorate, Attn: DSCP-COET, 700 Robbins Ave, Philadelphia, PA 19111-5096.

AMSC N/A **FSC 8470**

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:17Z
Check the source to verify that this is the current version before use.

3.3.1 Design. The body shield shall be rectangular in shape and comprised of both opaque and transparent armor components. The opaque armor components shall constitute the armor materials utilized in the majority construction of the body shield. The transparent armor shall constitute the armor materials utilized for constructing the body shield's viewport. The viewport will be centered on the upper third of the shield. The viewport will be oriented on the body shield such that the length axis will be parallel to the width of the body shield. The body shield inner panel shall be designed with padded ambidextrous handle system that allows for one or two hand operation. The shield shall have smooth edges and radius corners to prevent injuries. The exterior surface of the body shield is defined as the surface facing the threat environment. The interior surface is defined as the surface facing the user.

3.3.2 Overall Dimensions. The body shield shall be 37 inches high by 23 inches wide +1.0 inch in both directions. The body shield shall be designed with sufficient clearance and/or padding on the interior surface of the body shield for protection to the operator from deformation resulting from projectile impact.

3.3.3 Viewport Dimensions. The viewport shall have a minimum viewing area of 4 inches high by 13 inches long. Viewing area is defined as the minimum observation (look through) area afforded the user during operation. The viewing area is not the physical dimension of the viewport.

3.3.4 Overall Weight. The weight of the body shield shall not exceed 22 pounds.

3.3.5 Body Shield Handles. The body shield shall have an ambidextrous handle carrying and use system. This system shall consist of a secured arm hook and corresponding handle. An additional handle, located below the viewport and parallel to the width of the body shield, shall be provided for use when two hands are required for body shield operations. Positioning of the handles shall be in such a manner that it will facilitate carrying and maneuvering the shield. The ambidextrous system and additional handle shall be made from metal materials covered with a durable elastomeric foam or equal material to ensure a secure handgrip and impact protection to the forearm and hand. The body shield shall also include a trauma pad located in proximity to the handles to ensure impact protection to the forearm and hand. The body shield handles will be removable to facilitate storage and transportation.

3.3.6 Shield Attachment Assembly. The body shield shall be designed in such a manner to allow components (handles and viewport housing) to be assembled and disassembled using nuts and bolts rather than permanent or rivet fixtures with only a standard flat screwdriver and/or hexagonal wrench, and pliers. The bolts shall not protrude more than 0.125 inches from the nut to prevent injuries to the user. The caps from bolts exposed to the exterior surface of the body shield will be flush to the exterior surface.

3.3.7 Viewport to Body Shield Seal/Interface. The viewport shall be seated in the body shield (viewport housing) using a polymer gasket material that is compatible with the viewport and provides a positive liquid seal between the exterior and interior surfaces of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:17Z
Check the source to verify that this is the current version before use.

the body shield. Ballistic protection at the viewport/body shield interface shall be of similar ballistic performance, as that required of the shield (NIJ Standard 0108.01, Ballistic resistant protective materials, NIJ level IIIA).

3.3.8 System Interface Requirements. The body shield will be capable of being used with current weapons, clothing, face shields, and equipment normally, carried, worn or used when carrying out a mission. The body shield shall be designed and balanced to allow the user the ability to control the body shield to maintain the required protection level.

3.3.9 Instructions. An instruction sheet shall be provided, which, at minimum, includes details on how to assemble the body shield if assembly is required, maintenance, and precautions.

3.3.10 Labels. Each body shield shall be individually and permanently labeled with a commercial type identification/care label. The identification/care label shall be located on the inside lower half of the body shield and shall contain the item name, contractor's name, contract number, national stock number (NSN) (if applicable), date of manufacture, lot number, use and care instructions, and ballistic performance level as defined by NIJ Standard 0108.01.

3.3.11 Body Shield Finish. The body shield opaque components shall be finished with an anti-glare matte finish available in flat black. Finish will be specifically designated per contract or purchase order

3.4 Materials.

3.4.1 Protective Treatment. Materials that are subject to scratching, corrosion or degradation in oxygen, salt air, ultraviolet light, or any other atmospheric conditions likely to occur during service usage shall be protected against such elements to minimize the corrosion/degradation effect of the item. Any protective coating that will crack, chip, or scale with age or extremes of atmospheric conditions shall not be used.

3.4.2 Ballistic Protective Material. The ballistic protective material used for the construction of the body shield shall be in compliance with the National Institute of Justice's Ballistic Resistant Protective Materials NIJ Standard 0108.01 (or current edition) for all workmanship and performance requirements.

3.4.3 Ballistic Impact Resistance. The body shield shall meet or exceed an NIJ Level IIIA rating as stipulated in the National Institute of Justice's Ballistic Resistant Protective Materials NIJ Standard 0108.01 (or current edition).

3.4.4 Body Shield Finish. The anti-glare finish shall be of the type that prevents any reflection of visible light.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:17Z
Check the source to verify that this is the current version before use.

3.4.5 Transparent Armor (Viewport). The viewport, if laminated (not monolithic), shall be coated with a suitable polymeric sealant to prevent moisture from migrating into the laminates bond interface. The exterior and interior surfaces, if polymeric, shall be treated with an anti-scratch coating. The interior surface shall produce no spall as a result of a ballistic event with a munition that the body shield is rated to stop.

4. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. QUALITY ASSURANCE PROVISIONS.

5.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and to be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5.1.2 Visual examination. Each item shall be examined for the defects listed below.

Defects. Any component not in accordance with specified requirements, a cracked or broken viewport; bubbles or other inclusions within the viewport, a loose handle system or viewport, a non-ambidextrous handle system, rough or sharp edges, torn elastomeric foam or trauma pad, a viewport with haze or cloudiness; any serious material defects, distorted parts or other evidence of poor workmanship; any component part omitted; label missing, incorrect, or illegible; passing of a liquid in or around viewport housing to the interior surface; any items not packaged in accordance with the contract or purchase order.

5.2 Acceptance criteria. Acceptance criteria shall be as specified in the contract or purchase order.

6. PACKAGING.

6.1 Preservation, packing, and marking. The preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES.

7.1 Source of Government documents. Copies of military and Federal documents are available from:

Standardization Documents Order Desk
Bldg. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:17Z
Check the source to verify that this is the current version before use.

For NIJ Standard 0108.01
National Institute of Justice
Program Manager for Standards
U.S. Department of Justice
Washington, DC 20531

7.2 Products known but not limited to meet this CID.

1. American Body Armor & Equipment
   13386 International Parkway
   Jacksonville FL 32218
   Product name: COMSpec

2. Protech Armor Products
   158 Hubbard Avenue
   Pittsfield MA 01201
   Product name: Entry 1

MILITARY INTERESTS:

Custodians
Army – GL

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FSS

PREPARING ACTIVITY:
DLA-CT

Project Number
8470-0178

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:17Z
Check the source to verify that this is the current version before use.