INCH-POUND
A-A-59537
February 1, 2000

COMMERCIAL ITEM DESCRIPTION

FACE SHIELD, BALLISTIC

The General Services Administration has authorized the use of this Commercial Item Description for all Federal agencies.

1. SCOPE. This commercial item description covers the requirement for a ballistic face shield and attachment assembly intended for use by dismounted military personnel.

2. CLASSIFICATION. The ballistic face shield shall be of one type and size.

3. SALIENT CHARACTERISTICS.

3.1 General. The ballistic face shield and attachment assembly, hereafter referred to as face shield, shall be the manufacturer's commercial product except for any changes necessary to comply with the government requirements.

3.2 Description. The face shield will cover and protect the soldier's face from exposure to flammable liquids, kicks, hand-thrown high-speed projectiles and other hazards such as rocks, sticks, and glass. The face shield's transparent visor shall be fabricated using non-spalling transparent armor materials possessing a ballistic protection level as defined in the National Institute of Justice's (NIJ) Ballistic Resistant Protective Materials NIJ Standard 0108.01 or current edition (see para. 7.1). It is desired that the transparent visor have a multi-hit capability.

3.3 Item Configuration. The face shield shall meet the following criteria.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Defense Personnel Support Center, Clothing and Textiles Directorate, Attn: DSCP-COET, 700 Robbins Ave, Philadelphia, PA 19111-5096.

AMSC N/A **FSC 8470**

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:17Z
Check the source to verify that this is the current version before use.

3.3.1 Design. The face shield shall be designed to fit over the Personnel Armor System Ground Troops (PASGT) helmet; MIL-H-44099 (see para 7.1) and be worn over eyeglasses, M40A1 mask, chemical-biological, protective, field, EA-M-1801 (see para 7.1). It shall consist of a tilting transparent visor and helmet band fastening system that readily fits over and clips to the PASGT helmet. The helmet band shall have attachment points at the top of the helmet rim in proximity to where the user's ears are located. The head band shall be clamped to the helmet by the use of a fit-adjusting locking clip at the rear of the helmet band. The locking clip shall be designed to accommodate various size PASGT helmets.

3.3.2 Operational Configuration. The face shield must be capable of rotation from the full-up to full-down position while worn and have a positive lock in both positions. When in the full-up position the face shield shall not impede the user's visibility and it shall be secured so that the user is able to run without having the visor drop from the full-up position. The user must be able to configure and operate the rotation hardware from either side of the helmet. The user shall also be able to operate the face shield with either hand while wearing work gloves, cold weather gloves, and mitten sets.

3.3.3 Visor. The visor shall be molded of polycarbonate or better material measuring approximate 6 inches by 15 inches. The visor must be clear with no optical distortion and be shaped to curve and conform to the natural curvature of the face. The design of the face shield shall not interfere with the peripheral vision of the wearer.

3.3.4 Seal. The face shield will provide a seal between the helmet and the face shield to prevent liquids from entering the inside surface of the face shield. It is desired that the seal be flame resistant.

3.3.5 Overall Weight. The weight of the face shield system shall not exceed 3.4lbs (1.54Kg). The face shield, when worn with the ballistic helmet and any auxiliary equipment (i.e., eyeglasses, protective mask) shall not place undue burden on the neck, shoulders, and upper back muscles. The system shall be designed to have a low center of gravity and be balanced about the head (front to back, side to side).

3.3.6 System Interface Requirements. The face shield will be capable of being used with current weapons, clothing, and equipment normally, carried, worn, or used when the user is carrying the mission.

3.3.7 Instructions. An instruction sheet shall be provided, which, at minimum, includes instructions on how to assemble the face shield if assembly is required, maintenance, precautions, storing and cleaning procedures.

3.3.8 Labels. Each face shield shall be individually labeled and it shall include, at minimum, the ballistic performance level as defined by NIJ Standard 0108.01 and the contractor's name.

3.4 Materials.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:17Z
Check the source to verify that this is the current version before use.

3.4.1 Protective Treatment. Materials that are subject to corrosion in oxygen, salt air, ultraviolet or any other atmospheric conditions likely to occur during service usage shall be protected against such elements to minimize the corrosion/degradation effect of the item. Any protective coating that will crack, chip, or scale with age or extremes of atmospheric conditions shall not be used.

3.4.2 Visor Material. The visor material shall be polycarbonate or better material with notched Izod impact strength values between 11.3-17.0 ft-lb/in when tested in accordance with ASTM D256, Plastics, determining the Izod pendulum impact resistance of (see para 7.2).

3.4.3 Resistance to Temporary or Permanent Optical Degradation. Maximize the resistance to scratching, abrasion, and fogging so as to minimize interference with vision. Initial haze shall conform to American National Standards Institute (ANSI) ANSI Z87.1, Protection, eye and face, practice for occupational and educational (see para 7.2). No more than six percent (6%) haze shall be added to the baseline as a result of abrasion testing.

3.4.4 Adhesion. If a coating has been applied to the lens, the coating shall not be removed, dislodged, or affected in any way. Removal or loosing of the coating shall be cause for rejection.

3.4.5 Ballistic Impact Resistance. The face shield shall meet or exceed an NIJ Level IIIA rating as stipulated in the National Institute of Justice's Ballistic Resistant Protective Materials NIJ Standard 0108.01 (or current edition).

3.5. Human Factors.

3.5.1 Sizing/Fit. The face shield shall be designed to accommodate (i.e., fit, adjust, and/or successful use) U.S. Army target audience soldiers with 5th percentile female through 95th percentile male while wearing the PASGT Helmet.

3.5.2 Donning/Doffing. The face shield shall be easily and quickly donned and doffed on the helmet without the use of any tools.

4. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. QUALITY ASSURANCE PROVISIONS.

5.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and to be the same product

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:17Z
Check the source to verify that this is the current version before use.

offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5.1.2 Visual examination. Each item shall be examined for the defects listed below:

Defects. Any component not in accordance with specified requirements, a cracked or broken shield; bubbles or other inclusions within the visor, visor/helmet leakage, rough or sharp edges, a visor with haze or cloudiness; any serious material defects, distorted parts or other evidence of poor workmanship; any component part omitted; any items not packaged in accordance with the contract or purchase order.

5.2 Acceptance Criteria. Acceptance criteria shall be as specified in the contract or purchase order.

6. PACKAGING.

6.1 Preservation, packing, and marking. The preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES.

7.1 Source of Government documents. Copies of military and Federal documents are available from:

For (PASGT) helmet; MIL-H-44099
Standardization Documents Order Desk
Bldg. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

For NIJ Standard 0108.01
National Institute of Justice
Program Manager for Standards
U.S. Department of Justice
Washington, DC 20531

For M40A1 Mask, Chemical-Biological, Protective, Field, EA-M-1801
U.S. Army Edgewood Research, Development and Engineering Center
Attn: SCBRD-ENE-S
Aberdeen Proving Ground, MD 21010-5423

7.2 Source of non-Government documents.

For ASTM D256
American Society For Testing And Materials (ASTM) Test Methods

(Applications for copies should be addressed to American Society For Testing and Materials, 100 Barr Harber Drive, West Conshohocken, PA 19428-2959.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:17Z
Check the source to verify that this is the current version before use.

For ANSI Z87.1
American National Standards Institute (ANSI) Test Methods

(Applications for copies should be addressed to American National Standards Institute 11 West 42nd Street, New York, New York 10036

7.3 Products known but not limited to meet this CID.

Protech Armor Products
158 Hubbard Avenue
Pittsfield, MA 01201
Product name:
Ballistic face Shield
Model Number 702MT

MILITARY INTERESTS:

Custodians
Army – GL

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FSS

PREPARING ACTIVITY:
DLA-CT

Project Number
8470-0177

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:17Z
Check the source to verify that this is the current version before use.