INCH-POUND
A-A-59538
February 1, 2000

COMMERCIAL ITEM DESCRIPTION

SHIN GUARD, BALLISTIC, RIGID

The General Services Administration has authorized the use of this Commercial Item Description for all Federal agencies.

1. SCOPE. This commercial item description covers rigid ballistic shin guards to be worn by dismounted military personnel for protection of the knee and shin.

2. CLASSIFICATION. The rigid ballistic shin guards shall be of one type in the following sizes (see 7.4):

Medium
Large
X-Large

3. SALIENT CHARACTERISTICS.

3.1 General. The ballistic shin guards, hereafter referred to as shin guards, shall be the manufacturer's commercial product except for any changes necessary to comply with the government requirements.

3.2 Ballistic Protection Level. The shin guards will meet National Institute of Justice (NIJ) Standard 0108.01, Ballistic resistant protective materials or current edition (see 7.1), Level III-A and it is desired that they meet threat Level III. This protection will be for the knee and shin.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Defense Personnel Support Center, Clothing and Textiles Directorate, Attn: DSCP-COET, 700 Robbins Ave, Philadelphia, PA 19111-5096.

AMSC N/A **FSC 8470**

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:17Z
Check the source to verify that this is the current version before use.

3.3 Material. The shin guards shall be manufactured from ballistic materials to produce a durable, rigid (not soft) ballistic shin guard.

3.4 Area of Coverage. The shin guards will cover and protect the front of the knee and shin (see 7.3).

3.5 Padding. The shin guards will include interior padding to cushion the impact of objects hitting the rigid cover/shell.

3.6 Durability. The shin guards will be made of high quality materials, that are highly resistant to wear and decay and easy to clean and maintain. They will be capable of satisfactory performance after a minimum of five years of storage and transportation in climatic categories stated in paragraph 3.13.

3.7 Flexibility. The shin guards must allow for normal flexibility at the knee and ankle joints. They must provide protection at flexibility points.

3.8 Fasteners. The shin guards will have adjustable fasteners and straps that are simple to operate and should not restrict blood flow. Fasteners must allow for quick removal by medical personnel.

3.9 Utility. The shin guards shall be ambidextrous.

3.10 Shape. The shin guards shall be shaped to curve and conform to the natural curvature of the knee, leg and ankle.

3.11 Color. The shin guards shall be black color compatible with the black color in the Battle Dress Uniform (BDU).

3.12 Weight. The weight shall not exceed twelve pounds for a set (pair) of shin/knee guards.

3.13 Environment. The shin guards will be capable of being stored and will be operational in climatic design types hot, basic, and cold IAW Army Regulation 70-38 Research, Development, Test and Evaluation of Materiel for Extreme Climatic Conditions (see 7.1).

3.14 Labels. Each set of ballistic shin guards shall have a permanently attached identification/instruction label. The identification/instruction label shall contain the item and contractor's name, contract number, national stock number (NSN) (if applicable), date of manufacture, lot number, use and care instructions and ballistic performance level as defined by NIJ Standard 0108.01.

4. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:17Z
Check the source to verify that this is the current version before use.

5. QUALITY ASSURANCE PROVISIONS.

5.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and to be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5.2 Visual examination. Each item shall be examined for the defects listed below.

Defects. Any component not in accordance with specified requirements, any hole, cut, or tear; color deviations not as specified; raw edges, open seams, thread ends, or loose tension resulting in loose seams; any serious material defects, distorted parts or evidence of poor workmanship; any component part omitted; label missing, incorrect, or illegible; physical dimensions not as specified; any items not packaged in accordance with the contract or purchase order.

5.3 Acceptance Criteria. Acceptance criteria shall be as specified in the contract or purchase order.

6. PACKAGING.

6.1 Preservation, Packing, and Marking. The preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES.

7.1 Source of Documents. Copies of military and Federal documents are available from:

Standardization Documents Order Desk
Bldg. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

For (NIJ) Standard 0108.01
National Institute of Justice
Program Manager for Standards
U.S. Department of Justice
Washington, DC 20531

U.S. Army Corps Engineers (USACE) Publication Depot
ATTN: CEIM-IM-PD
2803 52nd Ave.
Hyattsville, MD 20781-1102
Regulation 70-38 may be obtained via the internet at:
http://www.usace.army.mil/inet/usace-docs/army-reg/ar70-38/toc.htm

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:17Z
Check the source to verify that this is the current version before use.

For Technical Report-Natick/TR-89/044
U.S. Army Soldier & Biological Chemical Command
Soldier Systems Center
Kansas Street
Natick, MA 01760-5019 Attn: AMSSB-RIP-S-(N)
Technical Report-Natick/TR-89/044; Titled "1988 Anthropometric Survey of U.S. Army Personnel: Methods and Summary Statistics"; Authors: Claire C. Gordon, Thomas Churchill, Charles E. Clauser, Bruce Bradtmiller, John T. McConville, Ilse Tebbetts, Robert A. Walker.

7.2 Products known but not limited to meet this CID.

Protective Materials Company
14040 N.W. 58th Court
Miami Lakes, FL 33014

Product name: Ballistic Shin Guard, Model: IIIA

7.3 Area of Coverage. Coverage for the instep is also desired.

7.4 Sizing/Fit. The shin guards shall be designed to accommodate (i.e., fit, adjust, and/or successful use) the central 90 percent male and female user U.S. Army target audience soldiers as described in U.S. Army Natick Technical Report (see 7.1).

MILITARY INTERESTS:

Custodians
Army – GL

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FSS

PREPARING ACTIVITY:
DLA-CT

Project Number
8470-0176

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:17Z
Check the source to verify that this is the current version before use.