**INCH-POUND**
**A-A-59539**
**February 1, 2000**

# COMMERCIAL ITEM DESCRIPTION

## BODY SHIELD, NON-BALLISTIC

The General Services Administration has authorized the use of this Commercial Item Description for all Federal agencies.

**1. SCOPE.** This commercial item description covers the requirements for a non-ballistic body shield to be used by dismounted military personnel.

**2. CLASSIFICATION.** The non-ballistic body shield shall be of two types and one size for each type.

Type I – Side-by-side and overhead interlinking capabilities
Type II – Non-interlinking

**3. SALIENT CHARACTERISTICS.**

3.1 General. The non-ballistic body shield, hereafter referred to as body shield, shall be the manufacturer's commercial product except for any changes necessary to comply with the government requirements.

3.2 Description.

3.2.1 Design. Type I - The body shield shall be rectangular in shape with an outer panel and a reinforcing panel of transparent polycarbonate or better materials. The body shield outer panel shall be designed with side moldings to allow for side-by-side interlinking capabilities with not only the same type of body shields but also with virtually any type of shields commercially available for mixed formations or multi-force operation.

**Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Defense Personnel Support Center, Clothing and Textiles Directorate, Attn: DSCP-COET, 700 Robbins Ave, Philadelphia, PA 19111-5096.**

**AMSC N/A** **FSC 8465**

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:17Z
Check the source to verify that this is the current version before use.

The shield shall have smooth edges and radius corners to prevent injuries. The reinforcing panel shall allow for horizontal interlinking capabilities. The term "horizontal" is in reference to the interlinking plane.

Type II – The body shield shall be rectangular in shape consisting of a single curved panel of transparent polycarbonate or better material. The shield shall have smooth edges and radius corners to prevent injuries.

3.2.2 Body Shield Handles. Type I - The body shield shall provide an arm hook or clip and two secured vertical hand loops for easy carrying. The arm hook and hand loops shall be made from metal materials covered with non-slip elastomeric or equal materials for a secure handgrip. The body shield shall also include a pad for impact protection near the forearm.

Type II – The body shield shall provide a vertical hand loop and a breakaway webbing arm strap, which will allow the user to quickly disengage from the body shield. The webbing arm strap shall be made from nylon or equal material with a fungus resistant treatment. The hand loop shall be made from a metal material covered with a non-slip elastomeric or equal material for a secure handgrip. The body shield shall also include a pad for impact protection near the forearm and hand.

3.2.3 Shield Attachment Assembly. The body shield shall be designed in such a manner to allow components (reinforcing panel, breakaway webbing arm straps, hook and loop handles) to be assembled and dis-assembled using nuts and bolts rather than permanent or rivet fixtures with only a standard screwdriver and pliers. The bolts shall not protrude more than 0.125 inches to prevent injuries to the user.

3.2.4 Item Dimensions. Type I - The body shield height (outer panel) shall not be less than 47.0 inches or more than 48 inches high and the width shall be 23 + 1.0 inches wide. The thickness of the outer panel shall be 4mm thick and the reinforcing panel shall not be less than 3mm and measuring approximately 25 1/2 X 17 inches.

Type II – The body shield height (outer panel) shall not be less than 47.0 inches or more than 48 inches high and the width shall be 23 + 1.0 inches wide. The thickness of the panel shall be 6mm thick.

3.2.5 End Item Weight. The weight of the end item (body shield) shall not exceed the following:

Type I - 12.6 $\pm$ 0.1 pounds
Type II - 13.7 $\pm$ 0.1 pounds

3.2.6 System Interface Requirements. The body shield will be capable of being used with current weapons, clothing, face shields, and equipment normally, carried, worn or used when carrying out the mission.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:17Z
Check the source to verify that this is the current version before use.

3.2.7 Instructions. An instruction sheet shall be provided, which, at minimum, includes instructions on how to assemble the body shield if assembly is required, maintenance, precautions and cleaning procedures.

3.3 Materials.

3.3.1 Protective Treatment. Materials that are subject to corrosion in oxygen, salt air, or any other atmospheric conditions likely to occur during service usage shall be protected against such elements to minimize the corrosion/degradation effect of the item. Any protective coating that will crack, chip, or scale with age or extremes of atmospheric conditions shall not be used.

3.3.2 Panel Material. The panel material used for type I and type II shall be polycarbonate or better material with notched Izod impact strength values between 11.3-17.0 ft-lb/in.

3.3.3 Impact Resistance. The body shield shall not break, spall, or crack when hit with a 6 feet 2 inches Tent Pole, ax, or standard riot baton.

**4. REGULATORY REQUIREMENTS.** The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

## 5. QUALITY ASSURANCE PROVISIONS.

5.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and to be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5.1.2 Visual examination. Each item shall be examined for the defects listed below.

Defects. Any component not in accordance with specified requirements, a cracked or broken shield; bubbles or other inclusions within the transparent material, a loose handle system, a non-ambidextrous handle system, rough or sharp edges, torn elastomeric foam or trauma pad, haze or cloudiness; any serious material defects, distorted parts or other evidence of poor workmanship; any component part omitted; any items not packaged in accordance with the contract or purchase order.

5.3 Acceptance Criteria. Acceptance criteria shall be as specified in the contract or purchase order.

## 6. PACKAGING.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:17Z
Check the source to verify that this is the current version before use.

6.1 Preservation, packing, and marking. The preservation, packing, and marking shall be as specified in the contract or order.

## 7. NOTES

7.1 Source of Government documents. Copies of military and Federal documents are available from:

Standardization Documents Order Desk
Bldg. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

7.2 Products known but not limited to meet this CID.

Tactical & Survival Specialties Inc.
1832 South Main Street
Harrisonburg VA 22801

Product name:
Type I – Armadillo
Type II – Jamco

MILITARY INTERESTS:

Custodians
Army – GL

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FSS

PREPARING ACTIVITY:
DLA-CT

Project Number
8465-0291



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:17Z
Check the source to verify that this is the current version before use.