[INCH-POUND]
A-A-2130
November 13, 1995

COMMERCIAL ITEM DESCRIPTION

LIGHT, DESK (FLUORESCENT)

The General Services Administration has authorized the use of this commercial item description (CID), for all Federal agencies.

1. SCOPE

1.1 Scope. This commercial item description (cid) covers two types of freestanding, portable fluorescent desk lights.

2. CLASSIFICATION

2.1 Classification. The desk lights shall be of the following types (see 7.3):

Type I - Standard 15-watt lamps
Type II - Compact energy-efficient lamps

3. SALIENT CHARACTERISTICS

3.1 Fire and casualty hazards. Each contractor shall submit proof that the desk lights they propose to supply under this cid conform to the requirements of Underwriters' Laboratories, Inc., Standard UL 153. Evidence of conformance with UL 153 shall be the Underwriters' Listing Mark affixed to the light. In lieu of the Underwriters' Listing Mark, the contractor may submit a test report from an independent laboratory, acceptable to the Government, indicating that the desk light conforms to applicable requirements of the published standards, including method of tests of UL 153. Compliance with the above preliminary requirements in regard to fire, safety and casualty hazards does not absolve the contractor from complete compliance with the other requirements of this cid in order to secure acceptance of the material or equipment.

3.2 Design.

3.2.1 Current. The desk light shall be designed for operation on 110-125 volt, 60-cycle alternating current.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Engineering Group (7FXEE), 819 Taylor St., Fort Worth, TX 76102

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.

3.2.2 Devices. The desk light shall be furnished complete with reflector, ballast, lampholders, switch, wiring, and all other devices necessary for operation including two fluorescent lamps as specified in 3.2.2.1 or 3.2.2.2.

3.2.2.1 Type I, 15-watt lamps. The type I desk light shall use and be furnished with two 15-watt, 18 inch (45.7 cm), T-8 cool white fluorescent lamps.

3.2.2.2 Type II, Compact energy-efficient lamps. The type II desk light shall use and be furnished with two 9-watt or 13-watt compact T-4 cool white fluorescent lamps as specified.

3.2.3 Construction. The lamp bases, articulated arms, supports, reflector and reflector housing shall be fabricated from one or more of the following: iron, steel, brass, bronze, aluminum alloy, zinc alloy, or magnesium alloy. White-metal castings (lead) shall not be used in any of the product. Each desk light shall consist of a metal base with one or more articulated arms, on the upper end of which shall be mounted a reflector and reflector housing. The luminaire head may be composed of ABS or other suitable plastic. The reflector shall be a separate part of the luminaire head.

3.2.4 Exposed edges. Exposed edges shall be so finished that personal injury due to sharp edges will not occur under any normal use.

3.2.5 Base. The base shall be of cast, pressed, or spun metal. The base area and weight shall be sufficient to cause the light to be freestanding on a horizontal surface. When inclined at an angle of 8 degrees from the horizontal in any direction, the light shall not overturn. The bottom of the base shall be a plane surface and shall be covered with a dark colored felt at least 1/16 inch (1.6 mm) thick or provided with other suitable means to prevent scratching of the surface on which the light rests. If an adhesive is used to attach the felt or other suitable material to the base, there shall be no evidence of penetration or wicking.

3.2.6 Articulated arms. The desk lamp shall have one or more arms (or columns) of cast sheet metal, formed sheet metal, or metal tubing. The arms may be attached at the base and the reflector housing through jointed connections (see 7.2). All arm wiring, springs, and bands shall be housed inside the arms. The wall thickness and the method of attachment to the base and the reflector housing shall be sufficient to provide the strength and rigidity required to successfully fulfill the test requirements of this cid. The length of the arm(s) shall be a minimum of 15 inches (38.1 cm) and a maximum of 34 inches (86.4 cm). The length shall be measured from the base to the reflector housing. The arm shall be such that the light remains in any position it is placed without spontaneous movement due to gravitational pull or spring action of the articulated arm.

Source: https://assist.dla.mil Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.

3.2.7 Reflector housing and reflector. The reflector housing shall be made from metal, ABS, or other suitable impact-resistant plastic. The reflector shall consist of an integral metal piece or separate metal pieces containing the lampholders. The reflecting surfaces shall be provided on a separate metal reflector or directly on the inside surface of the housing. Separate metal reflectors shall be of steel or aluminum with a reflecting surface to provide adequate illumination levels, and shall be held rigidly within the housing. The housing shall be joined to the supporting arm(s) rigidly or by means of a jointed connection.

3.2.8 Ballast. The ballast furnished with the light shall be suitable for operation on the current specified and shall be in accordance with UL 153 and UL 935. The ballast shall be built-in or in-line with quick disconnect capabilities to allow ease of installation.

3.2.9 Lampholders. Each lampholder shall be so constructed and mounted as to permit easy insertion and removal of the appropriate size fluorescent lamp. The lampholders shall be in accordance with the applicable requirements of UL 542.

3.2.10 Switch. Each desk light shall be provided with an operating switch mounted in the base or in the reflector housing. The switch shall be in accordance with the applicable requirements of UL 153.

3.2.11 Electrical Cord. Each light shall be provided with an electrical cord having an exposed length of not less than 9 feet (2.7 m) with a molded on parallel blade, straight-type attachment plug. The cord shall be three conductor type AWG 18, including the equipment grounding conductor. The color of the cord shall be as specified (see 7.2).

3.2.12 Splices. All splice connections shall be made with insulated splice connectors in accordance with UL 486.

3.2.13 Diffuser. At the option of the manufacturer, the light output may be controlled with a parabolic louver diffuser.

3.3 Performance. The desk light shall meet the applicable test requirements of UL 153 in addition to the requirements of 3.3.1 and 3.3.2.

3.3.1 Angle of cutoff. The light shall be so constructed that, with the reflector in the position specified in 5.3.1, no part of the lamps or reflecting surface shall be visible when viewed from a point one foot above the horizontal surface and two feet from a vertical plane though the longitudinal axis of the lamps.

3.3.2 Rigidity. The light shall be so constructed that no permanent deformation shall result when the light is subjected to the test specified in 5.3.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.

3.4 Finish. All exposed metal parts shall be cleaned and free of dirt, oil, grease, and moisture before applying the finish. All surfaces except aluminum reflecting surfaces, shall be covered completely with one or more coats of powder coat paint. Surface colors shall be either black, beige, brown, or gray, as specified (see 7.2). All painted surfaces shall be free from tears, star marks, crazing, blisters, hairlines, chipping, pinholes, and other irregularities or defects.

3.5 Nameplate. Unless otherwise specified, a nameplate meeting the requirements of UL 153 shall be securely attached to the desk light in an inconspicuous location.

3.6 Workmanship. The desk lights shall be free from defects which detract from the appearance or which might impair the serviceability.

3.7 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within tolerances specified and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

3.8 Standard commercial product. The desk light shall, as a minimum, be in accordance with the requirements of this CID and shall be the manufacturer's standard commercial product. A standard commercial product is a product which has been sold or is currently offered for sale on the commercial market through advertisements, manufacturer's catalogs, or brochures, and represents the latest production model.

4. REGULATORY REQUIREMENTS

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. QUALITY ASSURANCE PROVISIONS

5.1 Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

5.2 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.

performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

5.3 Tests.

5.3.1 Lamp positioning. The sample desk light shall be placed on a horizontal surface with the front edge of the reflector horizontal. Samples of desk lights with moveable reflector housings shall be positioned so that the front and back edges of the reflector housing are in a plane parallel to the horizontal surface on which the desk light rests and at a vertical distance of 12 inches (30.5 cm) from the horizontal surface or at the greatest possible vertical distance less than 12 inches (30.5 cm) which satisfies these conditions.

5.3.2 Rigidity.

5.3.2.1 Fixed arms (columns). The sample light shall be placed on its base on a horizontal surface and the two points of the reflector housing farthest from the center of the support of the column(s) shall be measured. A 5-pound weight (2.3 kg) shall be suspended for one minute, first from one of the points and then from the other. The sag of the reflector housing with the weight suspended shall not exceed 1/4 inch (6.4 mm). After removal of the weight, the vertical distance of the two points shall not disclose any permanent deformation or bending of the reflector housing or column(s). Consideration shall be given to the compressibility of the base covering (felt) during the conducting of the test. The base may be clamped as necessary to prevent tilting.

5.3.2.2 Moveable and articulated arms (columns). With the reflector housing and column(s) in the same position used in conducting the lamp positioning test in 5.4.1, the light shall be placed on a horizontal platform and the base securely clamped to the surface. A 1-1/2 pound (0.7 kg) weight shall be suspended from the reflector housing at its midpoint for a period of one minute. Movement of the column(s) shall not cause the reflector to sag more than 1/4 inch (6.4 mm) while the weight is suspended.

6. PACKAGING

6.1 Preservation, packing, and marking. Preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES

7.1 Sources of non-Government association documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.

ASTM standards are available from the American Society for Testing and Materials (ASTM), 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.

Underwriters Laboratories, Inc. standards are available from Underwriters Laboratories, Inc., 333 Pfingsten Road Northbrook, IL 60062.

7.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents (if applicable).

a. Title, number, and date of this commercial item description.
b. Type required (see 3.1)
c. Bulb size for type II lamps (see 3.2.2)
d. Finish required (see 3.4).
e. Preservation, packing, and marking required.
f. Arm requirements (see 3.2.6)
g. Color of cord required (see 3.2.11)

7.3 National Stock Number (NSN). The following NSN corresponds to this commercial item description.

NSN	Nomenclature	Type
6230-00-643-2077	Light, Desk, Fluorescent	I

MILITARY INTERESTS:

NONE: DoD has determined that no military has an official interest in this commercial item description.

PREPARING ACTIVITY:
GSA - 7FXEE

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.