MIL-B-12686 (ORD)
13 May 1953
SUPERSEDING
Army 51-73-44
16 December 1947

MILITARY SPECIFICATION,

BOARD, PLOTTING, M10

This specification consists of this cover sheet, and Specification 51-73-44, dated 16 December 1947, together with Amendment 1, dated 3 March 1949, attached hereto, without modification.

When a request for this specification is received by a supplying activity it will be necessary to attach this cover sheet to the pertinent specification before issue.

Copies of specifications required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.

Custodian:
Army - Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:11Z
Check the source to verify that this is the current version before use.

U. S. ARMY
SPECIFICATION

No. 51-73-44

16 DECEMBER 1947

BOARD, PLOTTING, M10

A. APPLICABLE SPECIFICATIONS

A–1. Ordnance Department Drawing D7692954 titled, "Board, Plotting, M10, Assembled and Sectional Views," lists or indicates all drawings and specifications which form part of this specification.

A–2. All drawings and specifications shall be of the issue in effect on the date of invitation for bids. The issue in effect shall be that issue which the contracting officer shall designate or furnish the bidder.

B. TYPES

B–1. This specification covers one type of plotting board known as Board, Plotting, M10.

C. MATERIAL AND WORKMANSHIP

C–1. *Material* shall be in accordance with the drawings, detail specifications, and general specifications which form a part of this specification.

C–2. *Workmanship* shall be in accordance with U. S. Army specification No. 51–7, Instruments, Fire Control: General Specification Governing the Manufacture and Inspection of.

D. GENERAL REQUIREMENTS

D–1. General requirements and associated tests common to all fire control instruments are contained in U. S. Army Specification No. 51–7 and are mandatory in so far as they are applicable.

E. DETAIL REQUIREMENTS

E–1. See drawings which form a part of this specification.

E–2. The disk shall be removable with normal finger pressure without any looseness. The rivet shall not revolve in the base.

E–3. The disk shall have a matte surface, be translucent, and have no defects such as pits, digs, scratches with depth, stains, or waves on the surfaces or between laminations that may be mistaken for pencil marks or cause distortion of lines and figures. Lines and figures on the base, as seen through the disk, shall be clearly readable. Edges shall be straight and smooth.

E–4. The lines and figures on the base shall be without skips or breaks. Any inclusions between the laminations such as dirt, paper, hair or any other defects which may be mistaken for pencil lines or dots shall be cause for rejection.

E–5. With one extremity of the disk index line in coincidence with either of the diametrical center lines of the base, the other extremity of the index line shall be not more than 5 mils out of coincidence with the corresponding base center line.

E–6. The maximum warp between the edge of the disk and the base shall be not more than 0.032 inch.

751782—47—(53)

E–7. The plotting boards shall show no evidence of excessive warpage, separation of laminations, or cracks, and shall operate satisfactorily immediately after having been subjected to each of the following:

(1) 100 degrees F. at 100 percent relative humidity for 24 hours.
(2) 180 degrees F. for 4 hours.
(3) –60 degrees F. for 4 hours.

E–8. *Spare parts* shall meet the requirements of the drawings, this specification, and the general specification forming part of this specification.

F. METHODS OF INSPECTION AND TESTS

F–1. Unless otherwise specified, each plotting board and extra part shall be inspected for conformance with specification, and the applicable requirements of U. S. Army specification No. 51–7.

F–2. Ten plotting boards out of the first 50 offered for inspection on each contract, three at 25 percent, three at 50 percent, and three at 75 percent completion of the contract, shall be tested for temperature and humidity requirements.

F–2*a*. Failure of any plotting board shall be cause for stopping shipments pending an investigation of the cause. The contractor shall institute an immediate investigation in the presence of a representative of the contracting officer if the representative desires to be present to determine the cause of failure. If the investigation discloses a fault in manufacture, acceptances of plotting boards incorporating this fault shall be stopped pending correction of the faulty manufacture. The contractor shall correct his manufacturing technique and shall correct all faulty plotting boards in his factory. Acceptances and shipments will be resumed when ten consecutive plotting boards have successfully passed the temperature tests.

G. PACKING AND MARKING

G–1. Packaging, packing, and marking shall be as specified in U. S. Army Specification No. 51–7.

H. NOTES

H–1. This specification replaces Frankford Arsenal Tentative Specification FXS–990.

H–2. The use of this specification whenever applicable is mandatory on all procuring agencies of the Army.

Notice.—This specification, together with specifications and drawings pertaining to it and bearing a "Notice" of similar restrictions, is intended for use only in connection with procurement by the United States Government and shall not be reproduced either wholly or in part except when authorized in connection with Government procurement, nor be used for any other purpose except when specifically authorized by the Chief of Ordnance.

Note.—Copies of this specification may be obtained from the Chief of Ordnance, Department of the Army, Washington 25, D. C.

[51–73–44]

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:11Z
Check the source to verify that this is the current version before use.