MIL-B-12719C (AR)
27 December 1973
SUPERSEDING
MIL-B-12719B (MU)
9 August 1968

MILITARY SPECIFICATION

BAG, CANVAS, CARRYING FOR DEMOLITION EQUIPMENT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a canvas bag for use in carrying Demolition Equipment.

2. APPLICABLE DOCUMENTS

*2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-636	- Box, Fiber
PPP-B-585	- Boxes, Wood, Wirebound
PPP-B-621	- Boxes, Wood Nailed and Lock Corner
PPP-T-45	- Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing

MILITARY

MIL-P-116	- Preservation, Methods of
MIL-B-117	- Bags, Interior Packaging

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:14Z
Check the source to verify that this is the current version before use.

MIL-A-2550 - Ammunition, General Specification For
MIL-F-50449 - Filler, Sheet Form (For use in Ammunition Containers)

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

9204775 - Bags, Canvas, Carrying, Demolition Equipment, Assembly

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material. - Materials shall be in accordance with applicable drawings and specifications.

3.2 Bag. - The canvas carrying bag shall comply with all requirements specified on Drawing (dwg.) 9204775 and with all requirements specified in applicable specifications.

3.3 Workmanship. - All components shall be fabricated and finished in a thorough, workmanlike manner. The canvas carrying bag shall be uniform in color, appearance, finish and physical properties and shall be free of dirt, oil, grease and other contamination, and other defects affecting serviceability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:14Z
Check the source to verify that this is the current version before use.

3.4 First Article Inspection. - This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

*4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of Product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted.

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with identification and date of changes thereto.
c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.
d. Number of items in the lot.
e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agents authority

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:14Z
Check the source to verify that this is the current version before use.

will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First Article Inspection

4.2.1 Submission.-Prior to the start of regular production the contractor shall submit a first article sample (see 6.1c) to a Government approved facility as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2 and 4.2.3. The first article sample shall consist of 10 completely assembled carrying bags which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials including packaging and packing shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including a certificate of conformance for materials. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer. A first article sample, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be performed.-Assemblies and components will be subjected by the Government to any or all of the examinations and tests specified in this specification and any or all requirements of the applicable drawings.

4.2.3 Rejection.-If any assembly fails to comply with the applicable requirements, the first article sample shall be rejected. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article sample or portion thereof. Until a first article sample is accepted, the contractor is, in no way, authorized by the Government to initiate regular production unless otherwise directed by the contracting officer.

4.3 Inspection provisions

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:14Z
Check the source to verify that this is the current version before use.

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer in one unchanged process using the same materials and methods in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specifications, or drawings not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168.

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable sub-paragraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Assembly (see dwg. 9204775).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:14Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major: None defined			
Minor:	AQL 2.50 percent		
201.	Width, minimum. (min.)	Gage	01001
202.	Depth, min.	Gage	01002
203.	Height of bag, min.	Gage	01003
204.	Any component missing, insecure, mislocated or damaged to the extent that the bag is rendered unusable	Visual/ Manual	01004
205.	Stitching incomplete or improperly located	Visual	01005
206.	Marking misleading or unidentifiable	Visual	01006
207.	Evidence of poor workmanship (see 3.3)	Visual	01007

4.3.2.2 Packaging (prior to sealing carton). (see 5.1)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major: None defined			
Minor:	AQL 1.50 percent		
201.	Carton damaged	Visual	02001
202.	Bag incorrectly folded (see 5.1.1)	Visual	02002
203.	Bag missing	Visual	02003
204.	Marking misleading or unidentifiable	Visual	02004

4.3.2.3 Packaging (prior to packing in wooden box). (see 5.1)

Categories	Defects	Method of Inspection	Code No.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:14Z
Check the source to verify that this is the current version before use.

Critical: None defined

Major: None defined

Minor:			AQL 0.65 percent
201.	Sealing strip torn, badly wrinkled or incomplete	Visual	03001

4.3.2.4 Packing (see 5.2)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major: None defined			
Minor:	AQL 1.50 percent		
201.	Box broken or board split	Visual	04001
202.	Box top improperly assembled or strapping missing, broken, loose or improperly located ..	Visual/ Manual	04002
203.	Marking misleading or unidentifiable	Visual	04003

4.3.4 Inspection Equipment. - Inspection equipment required to perform the inspections prescribed in this specification is identified in the Examination (4.3.2) and Test Methods (4.4) paragraphs herein. See 6.3 for details concerning responsibilities for inspection equipment design and approval.

5. PREPARATION FOR DELIVERY

*5.1 Packaging

5.1.1 Level A. - The bags shall be laid flat, back down and front flap open. The side pockets shall be folded in toward the center of the bag on top of the front pocket. The four tie tapes shall be folded over the front flap. The carrying strap shall be folded in half, flattened and laid on the center of the front pocket overlapping the two folded side pocket flaps. Starting from the front cover toward the bottom of the bag, the bag shall be rolled into a package approximately 10 inches long by 4 1/2 inches in diameter and shall be secured by tying the two billets

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:14Z
Check the source to verify that this is the current version before use.

around the roll with a single overhand knot. Fifteen bags shall be packaged into fiberboard box conforming to PPP-B-636, Type CF, Class Domestic, Variety SW, Grade 200. Closure shall be by application of 2 inch wide gummed, kraft tape, PPP-T-45 Type III, Grade B over the full length of the top and bottom center seam of the box with an approximate 2 inch extension onto the end panels. Each box shall be inserted into a barrier bag, MIL-B-117 Type I, Class E, Style 1. All excess air shall be exhausted from the bag and the opening closed by means of heat sealing. Seals shall comply with the heat seal test contained in MIL-P-116.

5.1.2 Level C. - The canvas bags shall be packed in boxes as specified in 5.1.1 with the exception that the barrier bag is not required.

*5.2 Packing

5.2.1 Level A. - Four fiberboard boxes packaged as specified in 5.1.1 shall be overpacked in a wooden box complying with PPP-B-621, Style 2, 2 1/2 or 4, Class 2, or PPP-B-585, Style 2 or 2A for overseas use.(Fillers sheet form MIL-F-50449) shall be placed against the interior sides, ends and bottom of the box and on top of the box contents. Filler size shall be equal to the inside dimensions of the end, side or bottom of the box less 1/2 inch. Additional fillers shall be added as required to prevent excessive movement of the contents. The box shall be closed and strapped in accordance with Appendix of the box specification.

5.2.2 Level B. - Packing shall be the same as Level A except boxes shall comply with domestic class requirements and fillers shall consist of commercial chipboard.

5.2.3 Level C. - Packing shall be in accordance with MIL-STD-1169 requirements. When the unit fiberboard box is used as the shipping container, closure of the boxes shall conform to Rule 41 of the Uniform Freight Classification Regulations.

5.3 Marking. - Interior packages and shipping containers shall be marked in accordance with MIL-STD-1169.

*6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:14Z
Check the source to verify that this is the current version before use.

a. Title, number and date of this specification.
b. Data cards. - Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.
c. Provisions for submission of first article samples.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. They should be cited as references on drawings of equipment designs submitted by the contractor to the Government for approval (see 6.3.3).

6.3 Inspection Equipment Designs.-Inspection equipment designs are of two types - Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers under the "Method of Inspection" headings in Section 4. Design responsibility for all other inspection equipment is assigned to the contractor. The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3 should he elect to do so.

6.3.1 SIE designs.-SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.
b. A source control drawing or a specification control drawing as defined in MIL-STD-100.
c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detailed design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.3.2 Contractor designs.-Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public.) Contractor designs shall include appropriate

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:14Z
Check the source to verify that this is the current version before use.

operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment, or with SIE designs if not otherwise covered thereby (see 6.3.1c). Designs shall be of the category and form (per MIL-D-1000) specified in the Contract Data Requirements Lists (DD Form 1423). The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number and the applicable five digit defect code number (or other specific identifying information) from Section 4 of this specification shall be referenced on each contractor design together with the component or assembly drawing number and revision letter to which the specific design applies.

6.3.3 Submission of Designs for Approval.-Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval to Picatinny Arsenal, ATTN: SARPA-QA-A-M, Dover, New Jersey 07801 in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423) or in the contract. The contractor must include in his submission of designs a listing of any and all Government SIE designs which will be utilized. Partial submission of inspection designs is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

6.4 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army- (AR)

Preparing Activity:
Army-(AR)

Project Number: 1375-A-067

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:14Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:14Z
Check the source to verify that this is the current version before use.