INCH-POUND
MIL-C-12684D(AR)
24 April 1989

SUPERSEDING
MIL-C-12684C(AR)
15 August 1984

MILITARY SPECIFICATION

CANNON, 155MM HOWITZER: M1A1

CANNON, 155MM HOWITZER: M1A2

This specification is approved for use by the Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification supports the acquisition of the Cannon, 155MM Howitzer: M1A1 and M1A2 consisting of the tube and the breech mechanism. This specification includes the minimum essential Engineering and Packaging Requirements and the necessary Quality Assurance Provisions to determine that these requirements have been met.

1.2 Classification. The two howitzer cannon are classified as follows:

Type I. Cannon 155MM Howitzer: M1A1 with a rifling twist of 1 turn per 25 calibers and is only used with the 155MM M114A1 towed medium howitzer system.

Type II. Cannon 155MM Howitzer: M1A2 with a rifling twist of 1 turn per 20 calibers and is only used with the 155MM M114A2 towed medium howitzer system.

1.3 International Standardization Agreement Code Number. This specification is subject to the requirements of QSTAG-57, Howitzer, 155MM, M1A1; Carriage, Howitzer, 155MM, M1A2 with ammunition and fire control equipment.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Armament Research, Development and Engineering Center, US Army Armament, Munitions and Chemical Command, ATTN: SMCAR-CCB-SAS, Watervliet, N.Y. 12189-4050 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1025

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:11Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

Military

MIL-C-13931	- Cannon, General Specification for
MIL-P-14232	- Parts, Tools and Equipment for Army Material, Packaging of
MIL-I-45607	- Inspection Equipment, Acquisition, Maintenance, and Disposition of

STANDARDS

Military

MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-1189	- Standard Symbology for Marking Unit Packs, Outer Containers, and Selected Documents
MIL-STD-1190	- Minimum Guidelines for Level C Preservation, Packing, and Marking
MIL-STD-1235	- Single and Multi-Level Continuous Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-2073-1	- DOD Material Procedures for Development and Application of Packaging

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:11Z
Check the source to verify that this is the current version before use.

DRAWINGS (see 6.5)

U.S. Army Armament Research, Development and Engineering Center (ARDEC)

D7309248	- Cannon, 155MM: M1A1
P7309248	- Packaging Data Sheet, Cannon, 155MM: M1A1
D11579272	- Cannon, 155MM: M1A2
AM11579272	- Special Packaging Instruction, Cannon, 155MM: M1A2

PUBLICATIONS

QAP-APPENDIX -WVA	- General Quality Assurance Provisions
Master LQAP 7309248	- List of Quality Assurance Provisions for Cannon, 155MM: M1A1
Master LQAP 11579272	- List of Quality Assurance Provisions for Cannon, 155MM : M1A2

(Copies of drawings, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the Procuring Contracting Officer.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

American Society for Testing and Materials (ASTM)

ASTM D 3951 - Commercial Packaging, Practice for

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103-1137.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:11Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General requirements. Cannon and component parts shall be in accordance with the applicable contract, the applicable drawings (D7309248 for the M1A1 and D11579272 for the M1A2), the requirements of this specification, the applicable paragraphs of the General Cannon Specification - MIL-C-13931 as incorporated in this document, and all referenced documents. Any conflicts are to be resolved by means of the order of precedence (see 2.3).

3.2 First article. The contractor shall submit a first article unless it is specifically waived in the contract (see 4.3 and 6.2). No first article requirements shall be waived without review and approval by the Procuring Contracting Officer (see 6.3).

3.3 Functional characteristics. Each cannon assembly shall perform the firing, pressure sustaining, and projectile launching function of its type howitzer, 155MM: M1A1 or M1A2. The breech mechanism, firing mechanism, and other moving parts shall function smoothly without interference, erratic movement or malfunction.

3.3.1 Breech mechanism. With the breech in the closed position, a rearward and downward pull on the operating lever, after release of the latch and removal of the firing mechanism, shall rotate the breechblock clockwise to disengage the sectored threads. A pull to the right on the operating lever shall cause the breechblock to swing out of the breech ring to the open position. The breechblock shall be retained in the open position by the counterbalance. To close the breech, a push on the operating lever to the left, past the dead center position of the hinge-pin arm, shall swing the breechblock into the breech opening. This closing action enables the roller on the breechblock driver to strike the cam on the breech ring, thereby rotating the breechblock counterclockwise to engage the sectored threads. An upward push on the operating lever shall continue the rotation of the breechblock and lock the breech in the firing position.

3.3.2 Firing mechanism assembly. The firing components consist of the firing mechanism M1 which includes the firing pin and primer holder, and the adapter assembly. The adapter assembly includes the hammer and the housing which receive the firing mechanism. For firing, the primer is inserted in the firing mechanism which is then screwed into the housing. The lanyard is attached to the hammer and when pulled, causes the hammer to pivot and strike the firing pin, detonating the primer. The firing pin spring, which is compressed during forward travel of the firing pin, returns the firing pin to its normal position. After firing, the firing mechanism is unscrewed from the housing, the fired primer is removed, and a new primer inserted in the firing mechanism.

3.3.3 Firing pin operation. The firing pin shall function without binding.

3.3.4 Firing pin protrusion. Firing pin protrusion shall be 0.025 - 0.035 inch as specified on the applicable drawing.

3.4 Performance.

Source: https://assist.dla.mil - Downloaded: 2026-10-17T23:11Z
Check the source to verify that this is the current version before use.

3.4.1 High pressure resistance. The cannon shall be capable of withstanding a chamber pressure of 44,100 plus or minus 1500 psi within its operating temperature range when tested as specified in 4.4.6.

3.4.2 Material soundness. Both prior to and after testing, all parts of the assembled cannon shall comply with the soundness requirements specified on the applicable drawings.

3.4.3 Bore enlargement. The bore diameters, measured across the rifled lands after firing shall not exceed the before firing diameters by more than the amounts specified in Table I.

TABLE I. Bore enlargement.

Distance forward of commencement of rifling	0.1 inch	1 inch	1 cal.	2 cals. to muzzle
Amount (inch)	0.007	0.007	0.006	0.005

NOTE: Interpolate linearly to determine allowable bore enlargement at distance other than those tabulated.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:11Z
Check the source to verify that this is the current version before use.

4.3 First article inspection. Unless otherwise specified in the contract, (see 6.2), first article cannon and specified parts thereof shall be inspected by the contractor and submitted to the Government for approval. Inspection shall be in accordance with applicable Quality Assurance Provisions (QAPs) and QAP-APPENDIX-WVA. QAPs are listed in Master LQAP 7309248 and Master LQAP 11579272, as applicable. First article sample sizes shall be as specified in applicable item QAPs, or the contract, as applicable. First article cannon and parts thereof shall be representative of the production processes to be used during quantity production.

4.3.1 First Article - Initial Production Test (FA-IPT). When specified in the contract, (see 6.2), first article cannon shall be subjected to FA-IPT by the Government or any agency specified by the Government and may be conducted at a Government facility to assure compliance with the requirements of this specification and any additional requirements listed in the contract. FA-IPT procedures and the sample size of first article cannon shall be as specified in the contract. First article cannon and parts thereof shall be representative of the production processes to be used during quantity production.

4.4 Quality conformance inspection. Quality conformance inspection is listed in Table II.

TABLE II. Quality conformance inspection.

Examination	Requirement	Inspection
Firing pin protrusion	3.3.4	4.4.4.1
Material soundness		
Cannon tube	3.4.2	4.4.4.2.1
Breech mechanism (breech ring and breechblock)	3.4.2	4.4.4.2.2
Packaging	5	4.4.4.3
Functional inspection		
Breech mechanism	3.3.1	4.4.5
Firing mechanism, M1	3.3.2	4.4.5
Firing pin operation	3.3.3	4.4.5
Tests		
Proof acceptance	3.4	4.4.6.1
Proof firing		4.4.6.1.1
Proof pressure simulation		4.4.6.1.2

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:11Z
Check the source to verify that this is the current version before use.

4.4.1 Inspection provisions. Cannon and parts thereof shall be inspected for conformance with the requirements of this specification, MIL-C-13931, QAPs listed in Master LQAP 7309248 and Master LQAP 11579272, as applicable, and QAP-APPENDIX-WVA.

4.4.2 Inspection approval stamp. The application of the inspection approval stamp shall be as specified in MIL-C-13931.

4.4.3 Inspection equipment. Special inspection equipment used in the inspection of parts, subassemblies, and assemblies are prescribed in applicable item QAPs.

4.4.3.1 Acquisition, maintenance, and disposition. Unless otherwise specified (see 6.2), responsibility for acquisition, maintenance, and disposition of inspection equipment prescribed in applicable item QAPs, and for all other inspection equipment required to perform inspection prescribed by applicable specifications, or the contract, shall be in accordance with MIL-I-45607.

4.4.3.2 Accuracy of standard measuring equipment. When commercial and modified-commercial inspection equipment is used, it shall be capable of repetitive measurements to an accuracy of 10 percent of the total tolerance of the characteristic being inspected.

4.4.4 Examinations.

4.4.4.1 Firing pin protrusion. Firing pin protrusion shall be gaged with inspection equipment prescribed by the applicable item QAP, or with an approved equivalent. One hundred percent inspection shall be used. Failure to comply with the requirements of 3.3.4 shall be cause for rejection.

4.4.4.2 Material soundness.

4.4.4.2.1 Cannon tube. The outer and inner surfaces of each cannon tube shall be magnetic particle inspected in accordance with applicable drawings and specifications. The bore of each cannon tube shall be examined by means of a borescope. Failure to comply with the requirements of 3.4.2 shall be cause for rejection.

4.4.4.2.2 Breech mechanism. The breech ring and breechblock of each breech mechanism shall be magnetic particle inspected in accordance with applicable drawings and specifications. Failure to comply with the requirements of 3.4.2 shall be cause for rejection.

4.4.4.3 Packaging inspection. Unless otherwise specified (see 6.2), inspection to determine compliance with packaging requirements of the applicable Packaging Data Sheet or Special Packaging Instruction for the level designated in the contract shall be as specified in MIL-P-14232 or MIL-STD-2073-1 respectively.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:11Z
Check the source to verify that this is the current version before use.

4.4.5 Functional inspection. The breech mechanism, firing mechanism, M1, and the firing pin of each assembled cannon shall be manually operated to determine proper functioning as specified in 3.3.1, 3.3.2, and 3.3.3. A minimum of two complete cycles of operation shall be performed on each mechanism. Any evidence of binding, scraping, rubbing, looseness, or malfunction of any component shall be cause for rejection.

4.4.6 Tests.

4.4.6.1 Proof acceptance. Cannon shall be proof accepted through proof firing, proof pressure simulation tests, or both. Cannon and replacement tubes to be proof fired shall be fired using the test method of 4.4.6.1.1. Failure to comply with the requirements of 3.4.1 and 3.4.2, shall be cause for rejection. Cannon breech mechanisms to be simulation proof tested shall be proof tested using the test method of 4.4.6.1.2. Failure to comply with the requirements of 3.4.1 and 3.4.2, shall be cause for rejection. Proof firing performed on a sampling basis shall be conducted as follows:

a. Using plan CSP-1 of MIL-STD-1235 and an AQL of 1.0, the Procuring Contracting Officer shall designate the appropriate initial quantity (i) and sample frequency (f), in the contract (see 6.2).

b. The first "i" quantity of cannon or tubes produced in a particular buy shall be proof fired. When the "i" quantity has been satisfied, sampling shall be put into effect using the "f" sampling frequency. If a cannon is rejected during proof acceptance, sampling shall be discontinued and the "i" quantity reinstated. All cannon not proof fired shall have the breech mechanisms simulation proof tested in the Product Assurance weapon test facility at Watervliet Arsenal.

c. Successive production buys shall not require "i" quantities. However, if the time lag between two successive buys exceeds one year, or if a new cannon or tube contractor is utilized, a new "i" quantity shall be proof fired.

d. Proof fired cannon and replacement tubes, and simulation proof tested breech mechanisms shall be furnished with applicable data on DA Form 2408-4 (Weapon Record Data) as specified by Procuring Contracting Officer at Watervliet Arsenal.

e. When specified in the contract (see 6.2), the weapon simulation test facility shall be qualified as follows: a sample of breech mechanisms of cannon to be sent to the proving ground for proof firing shall be subjected initially to simulation proof testing at the weapon simulation test facility.

Source: https://assist.dla.mil Downloaded: 2026-10-17T23:11Z
Check the source to verify that this is the current version before use.

4.4.6.1.1 Proof firing. Proof firing shall be conducted at a Government test site. The procedure shall be as follows:

a. Each cannon or replacement tube shall be proof fired within the proof pressure range specified in 3.4.1. If the lower limit is not attained, additional rounds shall be fired until the minimum value is attained. The number of additional rounds shall not exceed five.

b. A facility mount may be used if necessary.

c. Chamber pressure shall be measured and recorded.

d. After proof firing:

(1) The bore of each tube shall be examined for bore enlargement using an approved gage (see 3.4.3 and TABLE I).

(2) Each tube shall be borescoped and magnetic particle inspected (see 4.4.4.2.1).

(3) Each breech mechanism and firing mechanism shall be examined for looseness or interference of fit and other defects of workmanship and function (see 4.4.5).

(4) Each breech mechanism shall be disassembled and examined for soundness of material. All components shall be examined to assure freedom from cracks and fractures. Each breech ring and breechblock shall be magnetic particle inspected (see 4.4.4.2.2).

(5) All breech mechanism components, including the breech ring and breechblock shall be cleaned. Before shipment it shall function in accordance with 4.4.5.

e. Cannon found to be defective at the proving ground shall be reported to the Product Assurance Directorate, Watervliet Arsenal, Watervliet, NY 12189 and Benet Laboratories, Watervliet Arsenal, NY 12189 within one working day. The test agency shall forward a Test Incident Report (TIR), incident to the deficiency, within three working days.

4.4.6.1.2 Proof pressure simulation. All cannon not proof fired at a proving ground shall have the breech mechanism proof tested in accordance with the following procedure:

a. Each breech mechanism shall be tested by means of suitable hydraulic pressure testing equipment at a pressure within the proof pressure range specified in 3.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:11Z
Check the source to verify that this is the current version before use.

b. Cycle time to achieve test pressure and release shall not exceed three minutes. Test pressure shall be immediately released upon its attainment. Dwell time at test pressure shall not exceed three seconds.

(1) When difficulty is encountered in attaining test pressure, the number of attempts in which 10 percent or less of the test pressure is attained, shall not be counted. The number of attempts in which over 10 percent of the test pressure is attained, shall not exceed five.

(2) If the cause of difficulty is not identified and corrected within five pressure cycles, the breech mechanism shall be subjected to proof firing as part of the cannon (see 4.4.6.1.1). A notification of this condition shall be submitted with the breech mechanism to the proving ground.

c. The peak pressure shall be recorded for each test and attached to inspection records identifiable with the specific breech mechanism undergoing test.

d. After the pressure test, each breech mechanism and firing mechanism shall be examined for looseness or interference of fit and other defects of workmanship and function (see 4.4.5).

e. Each breech mechanism shall be disassembled and examined for soundness of material. All components shall be visually examined to assure freedom from cracks and fractures. Each breech ring and breechblock shall be magnetic particle inspected (see 4.4.4.2.2).

f. All breech mechanism components including the breech ring and breechblock shall be cleaned. Before shipment it shall function in accordance with 4.4.5.

5. PACKAGING

5.1 Cannon - Levels A, B and C. Cleaning, drying, preservation, unit packaging and packing of cannon shall be in accordance with the requirements of Packaging Data Sheet (PDS) P7309248 and MIL-P-14232 for the Cannon, 155MM Howitzer M1A1 or Special Packaging Instruction (SPI) AM11579272 and MIL-STD-2073-1 for Cannon, 155MM Howitzer M1A2 for the level of protection specified in the contract (see 6.2).

5.2 Repair parts - Level A, B and C. Cleaning, drying, preservation, unit packaging and packing of repair parts, shall be in accordance with the applicable repair part PDS and MIL-P-14232 or the applicable repair part SPI and MIL-STD-2073-1 for the level of protection specified in the contract (see 6.2). When Level C requirements are not shown on the PDS/SPI, Level C packaging shall be in accordance with MIL-STD-1190.

5.2.1 Level X - Industrial packaging. Cleaning, drying, preservation, unit packaging and packing of repair parts shall be in accordance with ASTM D3951 when industrial packaging is specified in the contract (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:11Z
Check the source to verify that this is the current version before use.

5.2.1.1 Quantity in Unit Package (QUP). When Level C packaging in accordance with MIL-STD-1190 or industrial packaging of repair parts is specified in the contract, the QUP shall be the same as specified in the contract (see 6.2).

5.3 Marking of packages.

5.3.1 Levels A, B and C. Marking of the unit package, intermediate packages, and exterior shipping containers shall be in accordance with MIL-STD-129. When specified (see 6.2), bar code marking shall be in accordance with MIL-STD-129 and MIL-STD-1189.

5.3.2 Level X - industrial. Marking of the unit package, intermediate packages, and exterior shipping containers shall be in accordance with ASTM D3951. When specified (see 6.2), bar code marking shall be in accordance with MIL-STD-129 and MIL-STD-1189.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The 155MM M1A1 cannon is intended for use with the M114A1 towed medium howitzer system and the 155MM M1A2 cannon is intended for use with the M114A2 towed medium howitzer system.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of the specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1 and 2.2).

c. Requirements for and the number of cannon, components thereof, or both to be submitted for first article by the contractor (see 3.2).

d. The examinations and tests to be performed by the contractor and the examinations and tests to be performed by the Government.

e. All inspection and test data that is required.

f. At whose expense a retest may be performed.

g. Any additional or extended examinations and tests beyond the scope of this specification.

h. Serial numbers for the cannon and repair tube assemblies.

i. Inspection equipment, responsibility for acquisition, maintenance, and disposition thereof, if other than as specified (see 4.4.3).

j. Availability of inspection equipment from the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:11Z
Check the source to verify that this is the current version before use.

k. Extent of contractor's responsibility for Government furnished and for contractor-required final inspection equipment.

l. Applicable acceptance test procedures.

m. When a proof firing sampling plan is authorized, the proof firing sampling plan parameters: initial consecutive quantity (i), and sampling frequency (f) (see 4.4.6.1).

n. Under what conditions simulated firing may be performed, the test equipment available, and the procedures to be followed.

o. The levels of preservation, packaging, and packing required for cannon assemblies (see 5.1) and repair parts (see 5.2).

p. When applicable, bar code marking requirements (see 5.3).

q. When warranted, the application of MIL-Q-9858 or MIL-I-45208, as appropriate.

r. Unless otherwise specified, the application of MIL-I-45607 and MIL-STD-45662.

6.3 Consideration of Data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DID's) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the DID's are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

Reference Paragraph	DID Number	DID Title	Suggested Tailoring
4.3	DI-T-4902	First Article Inspection Report	

The above DID's were those cleared as of the date of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DID's are cited on the DD Form 1423.

6.4 First article. When first article inspection is required, the Procuring Contracting Officer should provide specific guidance to offerors whether the item(s) should be a preproduction sample, a first article sample, a first production item, a sample selected from the first __ production items, a standard production item from the contractor's current inventory (see 3.2), and the number of items to be tested as specified in 4.4.6. The Procuring Contracting Officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitations for bids should

Source: https://assist.dla.mil - Downloaded: 2026-10-17T23:11Z
Check the source to verify that this is the current version before use.

provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.5 Waivers and deviations. The Procuring Contracting Officer shall coordinate all requests for waiver or deviation to this specification with Benet Laboratories and the Product Assurance Directorate at Watervliet Arsenal.

6.6 Subject term (key word) listing.

Cannon, 155MM: M1A1

Cannon, 155MM: M1A2

Howitzer, Medium, Towed: 155MM, M114A1

Howitzer, Medium, Towed: 155MM, M114A2

6.7 Drawings. Drawings listed in Section 2 of this specification under the heading "U.S. Army Armament Research, Development and Engineering Center" (ARDEC) may also include drawings prepared by, and identified as Watervliet Arsenal, Ordnance Corps, Weapons Command, or U.S. Army Armament Research and Development Command, U.S. Army Armament, Munitions and Chemical Command, etc. Technical data originally prepared by these activities are now under the cognizance of ARDEC.

6.8 Certain provisions of this specification are the subject of international standardization agreement, ABCA-ARMY-STD-57. When amendment, revision, or cancellation of this specification is proposed that will modify the international agreement concerned, the preparing activity will take appropriate action through international standardization channels, including departmental standardization offices, to change the agreement or make other appropriate accommodations.

6.9 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:

Army-AR

Preparing activity:

Army-AR

(Project 1025-A168)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:11Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-12684D (AR)	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:11Z
Check the source to verify that this is the current version before use.