MILITARY SPECIFICATION

QUADRANT, FIRE CONTROL: GUNNER'S M1A1

This amendment forms a part of Military Specification MIL-Q-12713D(MU) dated 10 August 1970, and is approved for use by all Departments and Agencies of the Department of Defense.

Paragraph 4.6.2: Delete and substitute:

"4.6.2 Operating temperature.- The quadrant shall be exposed to the temperature conditions specified in 3.3.2, utilizing testing equipment in accordance with the "Test Facilities" requirements of MIL-F-13926. The quadrant shall be placed in the cold chamber and the temperature of the chamber reduced gradually (see NOTE) to -40°F. The quadrant shall remain at this temperature for a minimum of five hours. At the completion of this five hour period, and while at -40°F the quadrant shall be removed from the test chamber and within a period of one hour the quadrant shall be subjected to the test in 4.6.3, 4.6.4, and 4.6.5. Upon completion of this portion of the test, the quadrant temperature shall be gradually raised to room ambient temperature. The quadrant shall then be placed into an oven chamber and the temperature shall be raised gradually to +150°F. The quadrant shall remain at this temperature for a period of five hours. At the completion of this five hour period, and while at +150°F the quadrant shall be removed from the test chamber and within a period of one hour the quadrant shall again be subjected to the test in 4.6.3, 4.6.4, and 4.6.5. Upon completion of this test, the temperature shall be gradually reduced to room ambient temperature (+60° to +90°F) at which time the quadrant shall be removed from the test chamber, and again subjected to the tests in 4.6.3, 4.6.4, and 4.6.5."

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1290-A330

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:13Z
Check the source to verify that this is the current version before use.