MIL-M-12700 (ORD)
13 May 1953
SUPERSEDING
Army 51-75-53
24 January 1942

MILITARY SPECIFICATION

MOUNT, TELESCOPE, M26, M27, M28, AND M29

This specification consists of this cover sheet and Specification 51-75-53, dated 24 January 1942 attached hereto, without modification.

When a request for this specification is received by a supplying activity it will be necessary to attach this cover sheet to the pertinent specification before issue.

Copies of specifications required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.

Custodian:
Army - Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:12Z
Check the source to verify that this is the current version before use.

U. S. ARMY
SPECIFICATION

No. 51-75-53

JANUARY 24, 1942

MOUNT, TELESCOPE, M26, M27, M28, AND M29

A. APPLICABLE SPECIFICATIONS.

A–1. The following Ordnance Department drawings list or indicate all drawings necessary to complete the manufacture of these telescope mounts:

Mount, Telescope, M26 Drg. Class *90* Div. *83* Drg. *1*.
Mount, Telescope, M27 Drg. Class *90* Div. *84* Drg. *1*.
Mount, Telescope, M28 Drg. Class *90* Div. *85* Drg. *1*.
Mount, Telescope, M29 Drg. Class *90* Div. *86* Drg. *1*.

A–2. All drawings listed on the above drawings and specifications listed on drawing B174522 of the issue in effect on date of invitation for bids, form part of this specification.

B. TYPES.

B–1. This specification covers four types of mount, telescopes known as:

"Mount, Telescope, M26"
"Mount, Telescope, M27"
"Mount, Telescope, M28"
"Mount, Telescope, M29"

B–2. These four types are of similar construction varying as follows: the M26 and M28 mounts are equipped with mounting brackets for attachment to the top carriage on the left side of the gun; whereas the M27 and M29 mounts have brackets for mounting on the right side of the gun cradle. The M26 and M28 mounts also have an elevating worm mechanism, controlled by a hand knob. This mechanism is used to rotate the telescope holder in the elevation plane, in order to keep the azimuth scale of the elbow telescope on the target when the target is above or below the level of the gun.

C. MATERIAL AND WORKMANSHIP.

C–1. *Material and workmanship* shall be in accordance with the drawings, general specifications, and material specifications forming part of this specification.

D. GENERAL REQUIREMENTS.

D–1. See U. S. Army Specification No. 51–7 "General Specification Governing Manufacture and Inspection of Fire Control Instruments."

E. DETAIL REQUIREMENTS.

E–1. *Accuracy.*—

E–1a. *Mount, telescope, M26.*—With the faces of mounting pads of bracket C78089 mounted in a vertical plane and the telescope mounted in place, the optical line of sight shall follow a plumb line within a tolerance of 2.8 mils when the telescope is elevated through 300 mils by means of the elevating knob.

E–1b. *Mount, telescope, M28.*—With the mounting surfaces of the bracket mounted in a true horizontal and vertical position, as shown

443168—42

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:12Z
Check the source to verify that this is the current version before use.

on the assembled view drawing, and with a plumb line target established in line with the optical axis of the elbow telescope mounted in place, the line of sight shall follow the plumb line of the target within a tolerance of 2.8 mils when the telescope is elevated 300 mils by means of the elevating knob.

E–2. *Lubrication* shall be in accordance with U. S. Army Specification No. 51–7 forming part of this specification.

E–3. *Painting and finishing* shall be in accordance with the drawings and U. S. Army Specification No. 51–70–1 "General Specification Governing Painting and Finishing of Fire Control Instruments."

E–4. *Manufacture of extra parts* shall be in accordance with this specification.

E–5. *Serial numbers* for all four types of telescope mounts will be furnished by the contracting officer and shall be inscribed in the manner shown on the drawings.

F. METHOD OF INSPECTION, TESTS, ETC.

F–1. Each mount, telescope, and component part thereof, including extra parts, shall be inspected during process of manufacture and assembly as prescribed in U. S. Army Specification No. 51–7, "General Specification Governing the Manufacture and Inspection of Fire Control Instruments."

F–2. *Mounts, telescope, M26 and M28.*—Each complete mount shall be inspected for accuracy as prescribed in section E of this specification.

G. PACKING AND MARKING.

G–1. *Packing.*—

G–1a. Unless otherwise specified, the mounts shall be packed in quantities as specified by the contracting officer in substantial wooden packing boxes as specified in U. S. Army Specification No. 51–7.

G–2. *Marking* shall be done in accordance with U. S. Army Specification No. 100–2, "Standard Specification for Marking Shipments."

H. NOTES.

H–1. *Extra parts and equipment.*—See section VII, U. S. Army Specification No. 51–7.

H–2. The use of this specification, whenever applicable, is mandatory on all procuring agencies of the Army.

NOTICE.—This specification, together with specifications and drawings pertaining to it and bearing a "Notice" of similar restrictions, is intended for use only in connection with procurement by the United States Government; and shall not be reproduced either wholly or in part except when authorized in connection with Government procurement, nor be used for any purpose except when specifically authorized by the Chief of Ordnance.

NOTE.—Copies of this specification may be obtained from the Office, Chief of Ordnance, Washington, D. C.

[No. 51–75–53]

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:12Z
Check the source to verify that this is the current version before use.