MIL-R-12715 (ORD)
13 May 1953
SUPERSEDING
Army 51-74-15
10 March 1944

MILITARY SPECIFICATION

RULE, SLIDE, M1

This specification consists of this cover sheet and Specification 51-74-15, dated 10 March 1944, attached hereto, without modification.

When a request for this specification is received by a supplying activity it will be necessary to attach this cover sheet to the pertinent specification before issue.

Copies of specifications required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.

Custodian:
ARMY - Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:14Z
Check the source to verify that this is the current version before use.

U. S. ARMY
SPECIFICATION

No. 51-74-15
10 March 1944

RULE, SLIDE, M1

A. APPLICABLE SPECIFICATIONS

A-1. Ordnance Department Drawing Class 22, Division 316, Drawing 1, titled "Rule, Slide, M1, List of Drawings" Lists or indicates all drawings and specifications which form part of this specification.

A-2. All drawings and specifications shall be of the issue in effect on date of invitation for bids. The issue in effect shall be that issue which the contracting officer shall designate or furnish to the bidder.

B. TYPES

B-1. This specification covers one type of instrument known as Rule, Slide, M1, complete with equipment.

C. MATERIAL AND WORKMANSHIP

C-1. Material and workmanship shall be in accordance with the drawings, general specifications, and material specifications forming part of this specification.

C-2. Commercial Material. - Components and materials of commercial nature, for which no requirements are contained herein, or for which no specifications are listed on the list of specifications, shall be of a type and quality most suitable for the purpose.

D. GENERAL REQUIREMENTS

D-1. See U. S. Army Specification No. 51-7, "Instruments, Fire Control, General Specification Governing the Manufacture and Inspection of."

E. DETAIL REQUIREMENTS

E-1. See detail drawings forming part of this specification.

E-2. Circular scales, formulae, grids, and instructions shall be printed on the body by means of metal dies (cuts) developed from masters furnished by Frankford Arsenal.

E-3. Printing shall be sharp, evenly colored, and without any skips or breaks that would detract from the serviceability of the rule.

E-4. Body shall be flat within 1/16 of an inch across the diameter.

E-5. Friction of the arms shall be such that:

E-5a. When the arms are separated to three different positions and at each position the long arm is rotated back and forth several times, the arms shall retain the angular spacing to which they were set before they were rotated back and forth.

E-5b. When arm is held stationary, the other arm shall not move with a jerky motion when alining the index of the moving arm with various graduations of the rule.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:14Z
Check the source to verify that this is the current version before use.

E-6. Equipment shall be in accordance with the drawings.

E-7. Manufacture of Extra Parts shall be in accordance with the drawings and this specification.

E-8. Serial numbers furnished by the contracting officer shall be inscribed as shown on the drawings.

F. METHODS OF INSPECTION AND TESTS

F-1. Each slide rule shall be inspected for conformance with the requirements of section E of this specification, and shall be subject to inspection during the process of manufacture and assembly as specified in U. S. Army Specification No. 51-7.

F-2. After printing, a percentage of the rules, as determined by the inspector, shall be measured for thickness before and after the transparent coating has been applied to determine whether the thickness of the coating is in accordance with the requirements of the drawing.

F-3. Problems. - To determine whether the rule has been properly reproduced from the masters furnished by Frankford Arsenal, a percentage of finished rules, as determined by the inspector, shall be checked by performing, on the rules, the mathematically calculated problems given in the table below. Index lines of the arms shall indicate the calculated values within plus or minus 0.01 inch when the problems are performed in accordance with the directions given in the formulae on the rule.

KNOWN FACTORS		CALCULATED
Angle E - Mils	Hundreds of Yards	Hundred of Yards Read from "E" Scale
"E" Set on "D" Scale	"H" Set on "E" Scale	
1100	1300	1474
500	2200	4667
200	3100	15890
"E" Set on "B" Scale	"D" Set on "E" Scale	
750	1550	1148.5
1200	4500	1722
1445	5500	834
"E" Set on "C" Scale	"H" Set on "E" Scale	
550	7500	12513
270	6200	22839
150	3600	24269.5

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:14Z
Check the source to verify that this is the current version before use.

G. PACKING AND MARKING.

G-1. Packaging and packing shall be in accordance with instructions forming part of the contract or furnished by the contracting officer in connection with the contract.

G-2. Marking for shipment shall be in accordance with U. S. Army Specification No. 100-2, "Standard Specification for Marking Shipments."

H. NOTES

H-1. Extra Parts and Equipment. - See Section VII, Notes, U. S. Army Specification No. 51-7.

H-2. The use of this specification, whenever applicable, is mandatory on all procuring agencies of the Army.

NOTICE: This specification, together with specifications and drawings pertaining to it and bearing a "NOTICE" of similar restrictions, is intended for use only in connection with procurement by the United States Government; and shall not be reproduced either wholly or in part except when authorized in connection with Government procurement, nor be used for any other purpose except when specifically authorized by the Chief of Ordnance.

NOTE: Copies of this specification may be obtained from the Chief of Ordnance, Army Service Forces, Washington, D. C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:14Z
Check the source to verify that this is the current version before use.