MIL-T-12711A(MU)
11 December 1964
SUPERSEDING
MIL-T-12711(Ord)
13 May 1953

MILITARY SPECIFICATION

TELESCOPE, PANORAMIC: M1

1. SCOPE

1.1 This specification covers Panoramic Telescope, M1 which is provided with a rotating elbow and an eyepiece slanted upward to permit the observer to look downward.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

| | |
|---|---|
| MIL-O-13830 | Optical Components for Fire Control Instruments; General Specification Governing the Manufacture, Assembly and Inspection of |
| MIL-F-13926 | Fire Control Materiel; General Specification Governing the Manufacture and Inspection of |
| MIL-P-14232 | Parts, Equipment and Tools for Ordnance Materiel, Packaging of |
| MIL-I-45607 | Inspection Equipment, Supply and Maintenance of |

STANDARDS

Military

| | |
|---|---|
| MIL-STD-105 | Sampling Procedures and Tables for Inspection by Attributes |
| MIL-STD-109 | Quality Assurance Terms and Definitions |

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:13Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. Army Munitions Command

| | |
|---|---|
| D10189 | Fixture Gage Assy. |
| B121742 | Test Fixture for Azimuth |
| C5549108 | Collimating Telescope |
| A7579933 | Telescope, Panoramic: M1 |
| F7691596 | Fixture, Azimuth Test |

PACKAGING DATA SHEET

MIL-P-14232/P7579933 Packaging of Telescope, Panoramic: M1

(Copies of specifications, standards, drawings, and packaging data sheets required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Fabrication.- The telescope shall be manufactured in accordance with Drawing A7579933 and drawings pertaining thereto.

3.2 General specification.- The contractor shall be responsible for adherence to, and compliance with, the following requirements of MIL-F-13926:

(a) Order of precedence
(b) Dimensions and tolerances
(c) Inorganic protective surface finishes
(d) Part identification and marking
(e) Workmanship

3.3 Environmental.

3.3.1 Storage temperature.- The telescope shall show no evidence of physical failure such as cement separation, glass breakage, or casting failure after having been exposed and thermally stabilized at temperatures of -80° and +160° Fahrenheit (F).

3.3.2 Extreme operating temperature.- The telescope shall meet the applicable requirements of 3.23 while exposed and thermally stabilized at -40° and +150°F.



Source: https://assist.dla.mil -- Downloaded: 202610-17T23:13Z
Check the source to verify that this is the current version before use.

3.3.3 Vibration.- The telescope shall show no evidence of physical failure due to being vibrated at a constant frequency of 30 cycles per second (cps) with an amplitude of 1/16 inch (1/8 inch total excursion) for a period of 5 minutes ± 15 seconds.

3.4 Cleanliness.- The telescope shall meet the cleanliness requirements of MIL-O-13830 when viewed through the eyepiece. The telescope shall show no more than four particles of dirt size 20 dig maximum real diameter in the apparent field. There shall be no other dirt which adversely affects observation and image quality.

3.5 Water resistance (Sealing).- The interior of the telescope shall show no evidence of water penetration or other damage after being subjected to a simulated rainfall for a time duration of 15 minutes ± 15 seconds.

3.6 Collimation.- The telescope shall be positioned with its flat mounting surface in a horizontal plane and the forward line of sight to a target orientated to be perpendicular to the plane of the locating pin holes. From this initial position the requirements of 3.7 to 3.23 shall be met.

3.7 Elevation.- With the telescope positioned as specified in 3.6 and the elevation indexes indicating zero within ± 1/2 width of a graduation line, the line of sight shall be horizontal within 0.5 mil.

3.8 Azimuth.- With the telescope positioned as specified in 3.6 the azimuth scales shall indicate zero within 0.5 mil.

3.9 Open sight.- With the telescope positioned as specified in 3.6 the line of sight of the open sight shall be horizontal within 10 mils and parallel in azimuth to the optical line of sight within 10 mils.

3.10 Image tilt.- The image of a vertical target shall remain vertical within 40 minutes of arc when the azimuth motion is reversed by means of the azimuth worm knob.

3.11 Parallelism of reticle and image.- The vertical line of the reticle shall remain parallel to the image of a vertical target within 20 minutes at any azimuth setting.

3.12 Elevation travel.- The head prism elevating mechanism shall allow a minimum of 3 turns above and 3 turns below a horizontal line of sight.

3.13 Plumb travel.- The line of sight through the geometric axis of the reticle shall follow a plumb line (starting with the line of sight horizontal and in coincidence with the plumb line) within plus or minus 0.5 mil, when the line of sight is elevated and depressed through the full excursion of the head prism at any deflection setting over two full resolutions of the head.



Source: https://assist.dla.mil -- Downloaded: 202640-17T23:13Z
Check the source to verify that this is the current version before use.

3.14 Backlash.- Backlash shall not exceed 1.0 mil in the elevation worm mechanism; nor exceed 0.5 mil in the azimuth worm mechanism.

3.15 Vertical displacement.- Vertical displacement of the line of sight due to reversing the azimuth motion by means of the azimuth worm knob, shall not exceed $\pm$ 0.3 mil.

3.16 Level travel.- With coincidence established with a horizontal target, the line of sight shall not deviate more than 1.0 mil from the target through two full revolutions of the head. This requirement shall be met by utilizing the azimuth worm to rotate the head in azimuth.

3.17 Azimuth error.- The error in any azimuth reading shall not exceed 1.0 mil including backlash.

3.18 Scales.

3.18.1 Elevation.- With the elevation worm knob indicating zero, the index on the ring shall be in coincidence with the zero line on the head within one half the width of the graduation line.

3.18.2 Azimuth.- The index on the body shall be in coincidence with the zero graduation line on the scale within one half the width of a graduation line. The micrometer scale shall be in coincidence with zero index.

3.19 Eyepiece focus.- Eyepiece focus shall be fixed between the limits of -0.75 and -1.0 diopter.

3.20 Parallax.- When viewing a target at 42 to 52 yards, parallax at the center of the field shall be not more than 0.10 mil.

3.21 Resolution.- The resolving power on the optical axis shall be 10 seconds of arc or less.

3.22 Elbow eyepiece rotation.- Movement of the eyepiece elbow from perpendicular to the plane of the locating pin holes to 90° to the left shall meet the requirements of 3.10, 3.11, 3.13, 3.16, 3.19, 3.20 and 3.21.

3.23 Operability.

3.23.1 Knobs.- The running torque required to rotate the head and azimuth adjustment knobs at standard ambient temperature shall not exceed 6 inch pounds for the azimuth worm knob; nor exceed 4 inch pounds for the elevation worm knob. The torque required at the temperatures specified in 3.3.2 shall not exceed the values obtained at standard ambient temperature by more than 50 percent.

3.23.2 Rapid traverse.- The throwout lever shall be manually operable and shall permit manual traverse of the head in azimuth at the temperatures specified in 3.3.2.

4.

Source: https://assist.dla.mil -- Downloaded: 202640-17T23:13Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are considered necessary to assure supplies and services confrom to the prescribed requirements.

4.1.1 General provisions.- The quality assurance provisions of this specification and of other documents referenced herein form the basis for inspection to be performed by the supplier. Inspection of components and sub-assemblies not covered by specifications or Supplementary Quality Assurance Provisions (SQAP) shall be in accordance with 4.2.2. Definitions of inspection terms not otherwise defined herein shall be as listed in MIL-STD-109.

4.2 Inspection provisions.

4.2.1 Inspection lot.- Unless otherwise specified by the contracting officer, inspection lot size, formation, and presentation of lots shall be in accordance with "Submission of Product" as specified in MIL-STD-105.

4.2.2 Examination and tests.- Components and subassemblies shall be inspected in accordance with the inspection provisions contained in Specification MIL-F-13926. Examinations and tests related to Section 3 herein shall be performed on a defect (individual characteristic) basis in accordance with MIL-STD-105, and the inspection level and sampling plans specified in Table I titled "Classification of Defects". Examinations and tests for Packaging, Packing and Marking shall be in accordance with MIL-P-14232 and Section 5 herein. The tabulated classification of defects shall constitute the minimum inspection to be performed by the supplier prior to Government acceptance or rejection by lot. The Government reserves the right to inspect for any applicable requirement, and to reject individual non-conforming items.

TABLE I - CLASSIFICATION OF DEFECTS

Use Inspection Level II of Table I with
Sampling Plan Table II-A of MIL-STD-105

| | REQUIREMENT | TEST PROCEDURES |
|---|---|---|
| CRITICAL: NONE | | |
| MAJOR: AQL .65% Defective | | |
| 101. Post vibration | 3.3.3 | 4.5.3 |
| 102. Cleanliness | 3.4 | 4.5.4 |
| 103. Elevation | 3.7 | 4.5.7 |



Source: https://assist.dla.mil -- Downloaded: 202640-17T23:13Z
Check the source to verify that this is the currentversion before use.

| | | REQUIREMENT | TEST PROCEDURES |
|---|---|---|---|
| 104. | Azimuth | 3.8 | 4.5.8 |
| 105. | Open sight | 3.9 | 4.5.9 |
| 106. | Image tilt | 3.10 | 4.5.10 |
| 107. | Parallelism of image and reticle | 3.11 | 4.5.11 |
| 108. | Elevation travel | 3.12 | 4.5.12 |
| 109. | Plumb travel | 3.13 | 4.5.13 |
| 110. | Backlash elevation & azimuth | 3.14 | 4.5.14 & 4.5.15 |
| 111. | Vertical displacement | 3.15 | 4.5.16 |
| 112. | Level travel | 3.16 | 4.5.17 |
| 113. | Azimuth error | 3.17 | 4.5.18 |
| 114. | Elevation scale | 3.18.1 | 4.5.19 |
| 115. | Azimuth scale | 3.18.2 | 4.5.20 |
| 116. | Eyepiece focus | 3.19 | 4.5.21 |
| 117. | Parallax | 3.20 | 4.5.22 |
| 118. | Resolution | 3.21 | 4.5.23 |
| 119. | Eyepiece rotation | 3.22 | 4.5.24 |
| 120. | Knob operability | 3.23.1 | 4.5.25 |
| 121. | Rapid traverse | 3.23.2 | 4.5.26 |

MINOR: NONE

4.2.3 Disposition of non-conforming product.- Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Disposition of Non-Conforming Product" specified in MIL-STD-105.

4.3 Control tests.

4.3.1 General.- One telescope shall be selected at random from each 100 produced, or from each month's production, whichever occurs first. Control samples shall have successfully met all acceptance tests specified herein prior to conducting the following examinations and tests:

| CONTROL TEST | | REQUIREMENT | TEST PROCEDURE |
|---|---|---|---|
| 301. | Fabrication | 3.1 | Visual & drawings |
| 302. | General specification | 3.2 | MIL-F-13926 |

4.3.2 Environmental.- Three telescopes shall be selected at random from each 100 produced, or from each months production, whichever occurs first, for the following tests:



Source: https://assist.dla.mil -- Downloaded: 202640-17T23:13Z
Check the source to verify that this is the current version before use.

| CONTROL TEST | REQUIREMENT | TEST PROCEDURE |
|---|---|---|
| 303. Storage temperature | 3.3.1 | 4.5.1 |
| 304. Operating temperature | 3.3.2 | 4.5.2 |
| 305. Water resistance (Sealing) | 3.5 | 4.5.5 |
| 306. Operability | 3.23 | 4.5.25 & 4.5.26 |

4.3.3 Control test failure.- Should the control test sample fail to meet the specified test requirements, acceptance of the product will be suspended by the Government until necessary corrections have been made by the contractor and the resubmitted samples have been approved.

4.4 Inspection equipment.- Except as otherwise provided for by the contract, the contractor shall maintain all required measuring and testing equipment in accordance with the applicable requirements specified in MIL-I-45607. The Government reserves the right to use the test equipment for its own independent inspections to the extent that such use will not unduly interfere with the contractor's delivery schedule.

4.4.1 Government furnished inspection equipment.- Where the contract provides for Government furnished test equipment, care and maintenance of test equipment shall be in accordance with the applicable requirements specified in MIL-I-45607.

4.4.2 Contractor furnished inspection equipment.

4.4.2.1 Government design.- All inspection equipment required by drawings forming a part of the contract and not provided by the Government shall be supplied by the contractor in accordance with the requirements of 4.4.

4.4.2.2 Contractor design.- The contractor shall design and supply inspection equipment compatible with the "Test Methods and Procedures" specified in 4.5, and with the "Component Inspection" requirements of MIL-F-13926. Concept, construction, materials, dimensions, and tolerances used in design of test equipment shall be so selected and controlled as to insure that the test equipment will permit positive rejection of a product which exceeds the prescribed tolerance limit, and will reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit. Construction shall be such as to facilitate routine calibration of the equipment.

4.4.2.3 Additional test equipment accuracy requirements.- The accuracy requirements for the test equipment used to perform the temperature test and vibration shall conform to the accuracies outlined under test facilities of MIL-F-13926. Accuracy requirements for the rain test equipment shall conform to those specified in MIL-F-13926.



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:13Z
Check the source to verify that this is the current version before use.

4.5 Test methods and procedures.

4.5.1 Storage temperature.- The telescope shall be exposed to the temperatures specified in 3.3.1 by means of a cold chest and oven capable of maintaining these temperatures until thermal stabilization is reached. Upon return to standard ambient temperature the telescope shall be visually inspected for damage.

4.5.2 Extreme operating temperatures.- This test shall be performed in accordance with the temperatures specified in 3.3.2 by means of a cold chest and oven capable of maintaining these temperatures until thermal stabilization is reached. During thermal stabilization at these temperatures the telescope shall be tested in accordance with 4.5.25 and 4.5.26.

4.5.3 Vibration.- The telescope shall be vibrated on a vibrating machine conforming to the accuracies specified in 4.4.2.3. Subsequent to vibration the telescope shall be thoroughly examined for physical defects resulting from poor workmanship and materials to determine compliance with 3.3.3 prior to being subjected to the remaining tests specified herein. A visual examination shall be made for missing or damaged parts prior to being subjected to the remaining performance tests. Minimum visual examination shall include broken glass, screws, nuts, etc. A tactile examination shall also be conducted to determine excessive looseness or malfunction of the operating knobs and mechansims of azimuth and elevation. Optical characteristics shall be visually examined by observing through the eyepiece and objective to detect excessive dirt, obstructions or interference with the optical system that would be cause for rejection. An audible examination shall be made by holding the telescope close to the ear and vigorously shaking it while listening for loose internal parts such as lens, reticles, prisms, cells, retainers, adapters, bonded elements, etc. Any one of the possible defects defined above shall be cause to consider a telescope as defective, unless separate defects-per-hundred type sampling plans are established and approved by the Government as part of the supplier's inspection system. Telescopes which have passed the above examinations shall be subjected to the tests of 4.5.4 to 4.5.27 inclusive.

4.5.4 Cleanliness.- The optical surfaces of the completed telescope shall be inspected for cleanliness in accordance with MIL-O-13830. Dirt particles which interfere with the legibility or accuracy of the reticle pattern shall be cause for rejection. Dirt particles shall not exceed the quantity and size specified in 3.4.

4.5.5 Water resistance (sealing).- This test shall be performed in accordance with 3.5 and Procedure I of the rain test as specified in MIL-F-13926. There shall be no evidence of water or moisture on the optical elements after this test when viewed through the eyepiece.



Source: https://assist.dla.mil -- Downloaded: 202610-17T23:13Z
Check the source to verify that this is the current version before use.

4.5.6 Collimation.- Using a special test fixture and appropriate wall targets, the telescope shall be mounted as specified in 3.6 to meet the applicable tests of this specification, utilizing Fixture Gage Assembly, Drawing D10189 and or Azimuth Test Fixture Drawing B121742. This equipment may be used in conjunction with Universal Azimuth Test Fixture, Drawing F7691596.

4.5.7 Elevation.- With the elevation indexes set at zero, a line of sight through the horizontal reticle line of the telescope shall be in coincidence with an appropriately marked wall target within the tolerance specified in 3.7.

4.5.8 Azimuth.- With the vertical reticle line in coincidence with an appropriately positioned wall target, the azimuth scales shall indicate zero within the tolerance as specified in 3.8.

4.5.9 Open sight.- Set the line of sight to zero elevation and sight through the open sight to an appropriately marked wall target. The line of sight through the open sight shall be parallel to the optical line of sight within the tolerance specified in 3.9.3.

4.5.10 Image tilt.- Align the vertical crossline of a collimating telescope's reticle with the vertical crossline of an appropriate wall target. Introduce the telescope under test into the line of sight between the target and the collimating telescope. Rotate the head of the telescope until the geometric axis of the reticle is superimposed on the crosslines of the wall target. The vertical crossline of the collimating telescope shall be within the tolerance as specified in 3.10.

4.5.11 Parallelism of reticle and image.- Position one extremity of the center vertical reticle line coincident to a plumb line target image. The opposite extremity of the reticle line shall be coincident to the plumb line image within the tolerance specified in 3.11. This test shall be performed at a minimum of two revolutions of the telescope head.

4.5.12 Elevation travel.- With the telescope mounted on a fixture, and the line of sight through the telescope set at zero elevation on the target, adjust the elevation scale to zero. Rotate the elevation knob for at least 3 full turns in one direction, observe at the index on the telescope. Reverse direction of the knob rotation and return the knob scale to zero, the starting point. Continue the rotation in this direction for at least 3 full turns in accordance with 3.12.

4.5.13 Plumb travel.- This test can be performed in conjunction with 4.5.12 Rotate the elevation knob and adjust the horizontal reticle line to the zero elevation line on the target. Adjust the azimuth knob to align the vertical reticle line with a plumb line target, that will accommodate 3 revolutions in elevation and 3 revolutions in depression from zero elevation. The line of sight through the geometric axis of the telescope reticle shall track the plumb line target through the 3 revolutions in elevation and depression, at any deflection setting over 2 full revolutions of the head assembly in azimuth, as specified in 3.13.



Source: https://assist.dla.mil -- Downloaded: 202640-17T23:13Z
Check the source to verify that this is the current version before use.

4.5.14 Backlash (elevation).- The test for backlash in the elevation mechanism can be accomplished concurrently with the tests indicated in 4.5.12 and 4.5.13. The horizontal reticle line of the telescope shall be brough into coincidence with the horizontal target line, at zero elevation without overtravel, when the elevation knob is rotated in a clockwise direction. The zero scale line of the knob and the index line on the rotating head shall be set in alignment with each other. Rotate the knob clockwise 3 full turns, then reverse direction of the knob and align the zero line on the scale with the index line on the head without overtravel. Observe, through the telescope, the position of the telescope reticle on the target. The telescope reticle shall be within the tolerance specified in 3.14, of the zero level line on the target. This test shall also be conducted in the opposite direction.

4.5.15 Backlash (azimuth).- The azimuth knob shall first be rotated in one direction to bring the vertical line of the telescope reticle in coincidence with the azimuth zero point on the target. Read and record the position of the azimuth scale on the azimuth knob at the knob index. Continue the rotation of the knob in the same direction, then reverse the direction of the knob and while sighting through the telescope, reposition the verticle reticle line of the telescope in coincidence with the azimuth zero point on the target, without overtravel. Read the scale on the azimuth knob and record the readings, then compare them with the original reading. Any difference, is the amount of backlash in the azimuth mechansim. The backlash shall not exceed the tolerance specified in 3.14.

4.5.16 Vertical displacement.- Collimate the geometric axis of the telescope under test to an appropriately marked wall target, and note the reading of the azimuth micrometer scale. Rotate the azimuth knob approximately 200 mils, then reverse direction until the telescope is reset to the initial reading. The horizontal reticle line shall be within the tolerance specified in 3.15. This examination shall be repeated at 1600, 3200, 4800 and zero mil settings of the azimuth scale.

4.5.17 Level travel.- This test shall be performed in conjunction with the test procedure of 4.5.18. During the azimuth error test, the position of the horizontal reticle line of the telescope shall be observed with respect to the zero elevation line on the target. The telescope reticle shall track the zero elevation line of the target within the tolerance specified in 3.16 for at least two full revolutions in azimuth.

4.5.18 Azimuth error.- Position the test equipment to zero in azimuth. Set the azimuth scale on the knob at zero, set the mil scale on the head assembly to zero. The vertical line on the reticle of the telescope shall be coincident with the vertical line of the target, and the horizontal line shall be adjusted into coincidence with the zero elevation line of the target. Azimuth readings shall be made at 800 mil increments through 2 full revolutions in each direction. The level travel reading test in 4.5.17 shall be made concurrent with the azimuth reading. The error in the azimuth reading shall not exceed the tolerance specified in 3.17 including backlash. (Note: The elbow eyepiece assembly shall remain in the normal position when the azimuth knob is rotated for each reading).



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:13Z
Check the source to verify that this is the current version before use.

4.5.19 Elevation scale.- The zero line on the scale of the elevation knob shall be coincident with the index on the head assembly within one half the width of the graduation line specified in 3.18.1 when the horizontal reticle line in the telescope and the zero elevation line of the target are in coincidence.

4.5.20 Azimuth scale.- The zero line on the azimuth scale of the azimuth knob shall be coincident with the index on the housing, within one half the width of the graduation line, specified in 3.18.2, when the vertical line of the telescope reticle and the plumb line of the target are in coincidence.

4.5.21 Eyepiece focus.- The eyepiece focus test shall be performed with the aid of a calibrated dioptometer of at least 3-power. Adjust the dioptometer reticle to the individual user's eye accommodations and set the scale at zero. Position the dioptometer in front of the telescope eyepiece. The telescope reticle shall be in best focus within the limits specified in 3.19 as measured on the diopter scale.

4.5.22 Parallax.- This test shall be accomplished by sighting the telescope to a target at the distance specified in 3.20. Parallax will be recognized as any apparent movement of the reticle line in relation to the target image when the observer's head is moved from side to side and up and down. Parallax is checked at the optical axis and shall not exceed the tolerance at the specified distance as required in 3.20.

4.5.23 Resolution.- This test shall be performed in accordance with the resolution test specified in Specification MIL-O-13830. The telescope shall permit resolution of a target line within the limit specified in 3.21.

4.5.24 Elbow eyepiece rotation.- This test shall be performed concurrently with 4.5.20. After each reading in azimuth the elbow shall be rotated to the left 90° from the normal as illustrated on Drawing 91-35-2. Any deviation of the telescope reticle from the azimuth setting can be measured on the azimuth scale, and it shall not exceed any of the tolerances specified in 3.10, 3.11, 3.13, 3.16, 3.19, 3.20 and 3.21 as required by 3.22. (The eyepiece shall be returned to normal position for each new azimuth reading.)

4.5.25 Knobs.- This test shall be performed using a commercial type inch pound torque wrench with adapters to accommodate the azimuth and elevation knobs. Readings with the torque wrench shall be taken in both directions and while in motion. The running torque required to rotate in the azimuth and elevation knobs at standard ambient temperature and at the temperatures indicated in 3.3.2 shall not exceed the values as specified in 3.23.1.

4.5.26 Rapid traverse.- By actuating the throwout lever the head assembly shall be free to be turned in azimuth in both directions with no binding. This test shall be performed at standard ambient temperature and at the temperatures specified in 3.3.2 as required by 3.23.2.



Source: https://assist.dla.mil -- Downloaded: 202640-17T23:13Z.
Check the source to verify that this is the currentversion before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking.- Packaging, packing and marking shall be in accordance with Specification MIL-P-14232 and Packaging Data Sheet MIL-P-14232/P7579933. The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 Intended use.- The Panoramic Telescope M1 is primarily intended to lay 75mm and 105mm Howitzers in azimuth for indirect fire.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Selection of applicable levels of preservation, packaging, and packing (see 5.1).
(c) Applicable packaging data sheet number (5.1).
(d) Applicable stock number.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1240-A437Y



Source: https://assist.dla.mil -- Downloaded: 202610-17T23:13Z
Check the source to verify that this is the current version before use.

To detach this form, cut along this line

# SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

**INSTRUCTIONS**

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines as shown, staple in corner, and send to preparing activity.

| | | |
|---|---|---|
| SPECIFICATION | | |
| ORGANIZATION | CITY AND STATE | |
| CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT<br>$ |
| MATERIAL PROCURED UNDER A | ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT | |

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

| | |
|---|---|
| SUBMITTED BY *(Printed or typed name and activity)* | DATE |

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 20260-17T23:13Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-5500
Philadelphia, Pa. 19137

FOLD

To detach this form, cut along this line

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:13Z
Check the source to verify that this is the current version before use.