MIL-B-18544B(OS)
15 May 1985
SUPERSEDING
MIL-B-18544A(N Ord)
30 October 1959

MILITARY SPECIFICATION

BOOSTER CANS (FOR BOOSTERS MK 8 AND MK 12)

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for booster cans for Boosters Mk 8 and Mk 12, which are used in the Mk 8 Mod 3 Flexible Linear Demolition Charge.

1.2 Classification. The booster cans shall be of the following types, as specified (see 6.2):

Type I	For Booster Mk 8
Type II	For Booster Mk 12

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards of the issue listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

PPP-B-621	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	Boxes, Fiber

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inpection by Attributes
MIL-STD-129	Marking for Shipment and Storage

2.1.2 Other Government documents, drawings, and publications. The following Government drawings form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

Beneficial comments (recommendations, additions , deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station, Standardization Division (524), Indian Head, Maryland 20640, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:40Z
Check the source to verify that this is the current version before use.

DRAWINGS

Naval Sea Systems Command (Code Ident 10001)

363037	Booster, Mk 8 Mod 0
394947	Booster, Mk 12 Mod 0

PUBLICATIONS

Naval Sea Systems Command

OP 400	General Instructions for the Design, Manufacture, and Inspection of Naval Ordnance Equipment

(Copies of specifications, standards, drawings and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting officer).

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplements thereto, if applicable.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to American Trucking Associations, Attn: Traffic Department, 1616 P Street, Washington, D.C. 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1107, 222 South Riverside Plaza, Chicago, Illinois 60606.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of Precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be submitted for first article inspection (see 4.3 and 6.2).

3.2 Design and construction.

3.2.1 Type I booster cans. Type I booster cans shall conform to Drawing 363037.

3.2.2 Type II booster cans. Type II booster cans shall conform to Drawing 394947.

3.3 Pressure strength. The booster cans shall be capable of withstanding an external hydrostatic pressure of 75 pounds per square inch (psi) without deformation or leakage (see 4.4.1.1).

3.4 General requirements. General requirements for the design and manufacture of this equipment shall be in accordance with OP 400 and this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:40Z
Check the source to verify that this is the current version before use.

3.5 Workmanship. The quality of workmanship shall be such as to assure compliance with all the requirements of the applicable specifications, standards, publications, and drawings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4.1).
b. Quality conformance inspection (see 4.4.2).

4.3 Sampling.

4.3.1 For first article inspection. Unless otherwise specified (see 4.3.1.1), as soon as possible after the award of contract, the contractor shall submit a sample of five completely assembled booster cans, without explosive charges, of the types being purchased. The booster cans shall be submitted to the Govenment inspector for first article inspection at the Government laboratory designated in the contract or order (see 6.2). All containers of first article booster cans shall be plainly marked. In addition each sample shall be plainly identified by a securely attached durable tag that contains the following information:

Title, number and date of this specification
Type (see 1.2) – Type I for Booster Mk 8 and Type II for Booster Mk 12
Sample for first article inspection
Name of manufacturer
Plant address
Reference the procurement contract

Further production of booster cans by the contractor prior to the approval of the procuring activity or completion of inspection on the first article samples shall be at the contractor's risk. Accepted first article samples shall become the property of the procuring activity and will not be included in the quantity of booster cans required in the contract or order.

4.3.1.1 First article sample for subsequent contract or order. If a contractor has previously delivered booster cans in accordance with the requirements of this specification and his product has been found to be satisfactory, the first article sample for any subsequent contract for the specific type of booster cans previously delivered may be waived at the discretion of the procuring activity (see 6.2).

4.3.2 For quality conformance inspection.

4.3.2.1 Inspection. A sample of booster cans shall be selected from each lot in accordance with the procedures of MIL-STD-105, acceptable quality level (AQL) of 2.5 percent defective. A lot shall consist of booster cans of the same type, manufactured under essentially the same conditions, and submitted for acceptance at the same time.

4.3.2.2 Pressure test. A sample of booster cans shall be selected from each lot in accordance with MIL-STD-105, Appendix, Inspection Level L4, AQL 6.5 percent defective.

4.3.3 For packaging, packing and marking inspection. A sample of containers, prepared for shipment, shall be selected from each lot in accordance with MIL-STD-105, Appendix, Inspection Level L4, AQL 6.5 percent defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:40Z
Check the source to verify that this is the current version before use.

4.4 Inspection.

4.4.1 First article inspection. The first article sample specified in 4.3.1 shall be examined as specified in 4.4.2 and subjected to the following test:

4.4.1.1 Pressure test. Each sample booster shall be weighed. The sample can shall then be immersed in water at a temperature of 75° to 85°F and subjected to an external hydrostatic pressure of 75 psi for 10 minutes. After removal, the external surfaces of the cans shall be wiped dry and the can shall be weighed. Any increase in weight of the can shall be attributed to leakage. Any sample can which shows deformation or increase in weight greater than 2 grams shall be classed as defective.

4.4.1.2 Results of inspection. When first article inspection is completed, the Government laboratory shall notify the Government inspector, who in turn shall notify the contractor of the results. The contractor shall take the necessary action to correct any deficiency, and may be required, at the discretion of the laboratory, to submit additional samples until the specified number of satisfactory samples have been submitted. Such samples shall be accompanied by a description of the changes made to correct the deficiencies of the previous submissions.

4.4.2 Quality conformance inpection. The sample booster cans specified in 4.3.2.1 shall be visually and dimensionally inspected to determine compliance with 3.2 and 3.5. Quality conformance lot acceptance shall be in accordance with 4.3.2.1.

4.4.2.1 Pressure test. The sample booster cans specified in 4.3.2.2 shall be completely assembled, without the explosive charge, and tested in accordance with 4.4.1.1. Quality conformance lot acceptance shall be in accordance with 4.3.2.2.

4.4.3 Packaging, packing and marking inspection. The sample containers specified in 4.3.3 shall be inspected to determine compliance with the requirements of section 5. Quality conformance lot acceptance shall be in accordance with 4.3.3.

5. PACKAGING

5.1 Preparation for shipment. The booster cans shall be prepared for shipment in accordance with Levels A, B, or C as specified in the contract or order (see 6.2).

5.2 Packaging.

5.2.1 Level A. Ten (10) booster cans of the same type shall be packaged in a box conforming to type I, class 2, style RSC of PPP-B-636. The booster cans shall be separated by spacers with sufficient cushioning provided to prevent free movement within the package. The end and side spacers shall be the same height as the inside of the box.

5.2.2 Level B. Not applicable.

5.2.3 Level C. Packaging shall be in accordance with the manufacturer's commercial practice which will assure receipt of the booster cans in an undamaged condition at the point of destination.

5.3 Packing.

5.3.1 Level A. Six (6) unit packages, as specified in 5.2.1, shall be packed in snug fitting boxes conforming to type II, class 2, style 2 or 4 of PPP-B-621.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:40Z
Check the source to verify that this is the current version before use.

5.3.2 Level B. Six (6) unit packages, as specified in 5.2.1, shall be packed in snug fitting boxes conforming to type II, class 2, style 2 or 4 of PPP-B-621.

5.3.3 Level C. The booster cans, packaged as specified in 5.2.3, shall be packed to afford protection against damage during direct shipment from the supply source to the first receiving activity for immediate use. Containers shall conform to Unform Freight Classification, National Motor Freight Classification or to rules of other carriers applicable to the mode of transportation.

5.4 Marking. In addition to any special marking required by the contract or order (see 6.2), packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.

6.1.1 Type I booster can. Type I booster cans are intended to be loaded with the explosive charge specified in Drawing 363937, to form Booster Mk 8.

6.1.2 Type II booster can. Type II booster cans are intended to be loaded with the explosive charge specified in Drawing 394947, to form Booster Mk 12.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this specification
b. Type of booster cans (see 1.2)
c. First article waiver, when applicable (see 3.1 and 4.3.1.1)
d. Government test laboratory (see 4.3.1)
e. Required levels of packaging and packing (see 5.1)
f. Special marking, if required (see 5.4).

6.3 Criteria for use of proper level of packaging and packing.

6.3.1 Level A. This level should be used for those items which are to be shipped to temporary destinations or stored under temporary conditions for redistribution elsewhere.

6.3.2 Level B. This level should be used for those items which are subject to multiple domestic shipments, handling, and covered storage.

6.3.3 Level C. This level should be used only when it is definitely known that the packaged item is to be shipped to domestic installations for immediate use at the first receiving activity.

Custodian:
Navy - OS

Preparing activity:
Navy - OS

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:40Z
Check the source to verify that this is the current version before use.