MIL-STD-1323-315
Notice 1
20 March 1986

MILITARY STANDARD

UNIT LOAD FOR UNDERWAY REPLENISHMENT CARTRIDGE, 25 MM, HEI-T, MK 210 MOD 0 (LINKED) AND CARTRIDGE, 25 MM, PGU-25/U (LOOSE) IN CLEATED WOODEN BOX

TO ALL HOLDERS OF MIL-STD-1323-315(NAVY)

Make the following pen and ink changes:

Page 1

a. Wooden Box drawing. "Height dimension should be 12 1/4 max."

b. DIM A block. "Underneath DIM. A add "Max." Change dimensions to read "Mk 12-0 - 40 3/8" and "Mk 12-1 - 40"

Page 2

List of materials. Change height of items 6 and 7 from "36 3/4" to "33 3/4".

Page 3

Detail B. Change height dimensions for locating horizontal battens from "10 1/2, 22 3/4, and 36 3/4" to "10, 21, and 33 3/4." respectively.

DISTRIBUTION STATEMENT A

Approved for public release; distribution is unlimited.

AMSC No. - N/A
Review Activity:
NAVY - OS, AS

Preparing Activity:
NAVY - OS
(Project No. 8140-N711)
FSC 8140

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:59Z
Check the source to verify that this is the current version before use.