MILITARY STANDARD
UNIT LOAD
FOR UNDERWAY REPLENISHMENT
HELLFIRE MISSILE, AGM 114
IN SHIPPING AND STORAGE CONTAINER
CNU-448/E

To all holders of MIL STD-1323-334A (NAVY):

The following optional palletizing procedure may be used to prevent chafing of containers by tiedown straps:

(A) THREAD STRAPPING, ITEM 2, BETWEEN DECK WIRES OF THE PALLET, ITEM 1, AS SHOWN IN DETAIL A, WITH EQUAL LENGTHS OF STRAPPING EXTENDING BEYOND EACH END OF THE PALLET. LAY EACH END OF STRAPPING BACK OVER THE PALLET DECK AS SHOWN IN DETAIL B.

(B) POSITION THE CONTAINERS ON THE PALLET WITH PPP-C-1797 CUSHIONING ON EACH SIDE OF THE CENTER THREE CONTAINERS. THERE SHALL BE EQUAL OVERHANG ON BOTH ENDS AND BOTH SIDES OF THE PALLET.

(C) COVER THE TOP MARKINGS WITH PPP-C-1797 CUSHIONING. DO NOT OBSTRUCT THE STACKING DIMPLES.

(D) CUSHIONING SHALL BE HELD IN PLACE WITH PPP-T-60 (1" X 2" TAPE).

(D) POSITION STRAPPING, ITEM 3, UNDER THE PALLET DECK AND OVER THE CONTAINERS. POSITION PPP-F-320, CLASS WR, GRADE W5S, OR EQUAL EDGE PROTECTORS UNDER THE STRAPPING. TENSION THE STRAPS AND DOUBLE NOTCH THE SEALS, ITEM 4.

(E) POSITION STRAPPING, ITEM 2, OVER THE CONTAINERS. POSITION PPP-F-320, CLASS WR, GRADE W5S, OR EQUAL EDGE PROTECTORS UNDER THE STRAPPING. TENSION THE STRAPS AND DOUBLE NOTCH THE SEALS, ITEM 4.

AMSC No. - NA

Distribution Statement A
Approved for public release;
distribution is unlimited.

Reviewing activity:
Navy - OS

Preparing activity
Navy - OS
(Project No. 8140-N083)
FSC 8140

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:59Z
Check the source to verify that this is the current version before use.