INCH-POUND

MIL-PRF-83532B
SUPPLEMENT 1
18 May 2001

PERFORMANCE SPECIFICATION

DELAY LINES, ACTIVE,
GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-PRF-83532B, dated 6 May 1999.

SPECIFICATION SHEETS

MIL-PRF-83532/1	-	Delay Lines, 14-Pin DIP Compatible, 5 Tap.
MIL-PRF-83532/2	-	Delay Lines, 14-Pin DIP Compatible, 5 Tap.
MIL-PRF-83532/3	-	Delay Lines, 14-Pin DIP Compatible, 10 Tap.
MIL-PRF-83532/4	-	Delay Lines, 14-Pin DIP Compatible, 3 Delay Circuits Per Package.
MIL-PRF-83532/7	-	Delay Lines, Active, 16-Pin DIP Compatible, Programmable 3-Bit, TTL Compatible, With Input Buffer.
MIL-PRF-83532/8	-	Delay Lines, Active, 14-Pin Surface Mount, 5 Tap.

Preparing activity:
DLA - CC

(Project 5999-0383)

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:42Z
Check the source to verify that this is the current version before use.