INCH-POUND

MIL-PRF-83532E
SUPPLEMENT 1
26 August 2013

PERFORMANCE SPECIFICATION

DELAY LINES, ACTIVE, GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-PRF-83532E, dated 26 August 2013

SPECIFICATION SHEETS

MIL-PRF-83532/1	-	Delay Lines, 14-Pin DIP Compatible, 5 Tap.
MIL-PRF-83532/2	-	Delay Lines, 14-Pin DIP Compatible, 5 Tap.
MIL-PRF-83532/3	-	Delay Lines, 14-Pin DIP Compatible, 10 Tap.
MIL-PRF-83532/4	-	Delay Lines, 14-Pin DIP Compatible, 3 Delay Circuits Per Package.
MIL-PRF-83532/7	-	Delay Lines, Active, 16-Pin Compatible, Programmable 3-Bit, TTL Compatible, With Input Buffer.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Review activities:
Navy - AS, CG, MC, SH
Air Force –19, 99

Preparing activity:
DLA - CC

(Project 5999-2013-017)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 5999

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:42Z
Check the source to verify that this is the current version before use.