INCH-POUND

MIL R-83536/10A
AMENDMENT 1
15 December 1995

MILITARY SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, DPDT,
LOW LEVEL TO 10 AMPERES, PERMANENT MAGNET DRIVE, HERMETICALLY SEALED,
ALL WELDED TRANSIENT SUPPRESSED DC COILS

This amendment forms a part of MIL-R-83536/10A, dated 13 May 1994, and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 1

FIGURE 1, side view Delete "SERIAL NUMBER SHALL BE MARKED ON TOP OF RELAYS"

PAGE 10

Delete "Contact voltage drop or resistance " and substitute "Contact voltage drop and resistance "

PAGE 13

Delete "Maximum leakage current" in its entirety and substitute "Maximum leakage current for track mount only 100 microamperes rms "

Vibration (random), first paragraph, line 2 Delete "15 minutes each plane"

CONCLUDING MATERIAL

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities
Air Force - 99
DLA - ES

Preparing activity
Air Force - 85

Agent
DLA - ES

(Project 5945-0964-08)

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:46Z
Check the source to verify that this is the current version before use.