+)))))))))))),
* INCH-POUND *
.)))))))))))-

MIL-R-83536/10A
AMENDMENT 2
30 September 1996
SUPERSEDING
AMENDMENT 1
15 December 1995

MILITARY SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, DPDT,
LOW LEVEL TO 10 AMPERES, PERMANENT MAGNET DRIVE, HERMETICALLY SEALED,
ALL WELDED, TRANSIENT SUPPRESSED DC COILS

This amendment forms a part of MIL-R-83536/10A, dated 13 May 1994, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* FIGURE 1, side view: Delete "SERIAL NUMBER SHALL BE MARKED ON TOP OF RELAYS" and "MARKING (EITHER SIDE)".

PAGE 2

* FIGURE 1, side view: Delete "MARKING (EITHER SIDE)".

PAGE 3

* FIGURE 1, side view: Delete "MARKING (EITHER SIDE)" and substitute "MARKING (SEE NOTES 8 AND 9)".

PAGE 10

Delete "Contact voltage drop or resistance:" and substitute "Contact voltage drop and resistance:".

PAGE 13

Delete "Maximum leakage current" in its entirety and substitute: "Maximum leakage current for track mount only: 100 microamperes rms."

Vibration (random), first paragraph, line 2: Delete "15 minutes each plane".

The margins of this amendment are marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based upon the entire content, irrespective of the marginal notations and relationship to the previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Air Force - 99
DLA - ES

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5945-0993-02)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:45Z
Check the source to verify that this is the current version before use.