S-37-03
MIL-F-45939
19 November 1971
SUPERSEDING
(See Section 6)

MILITARY SPECIFICATION

FEEDER, AUTOMATIC GUN: MAU-57A/A

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of machinegun driven feed mechanism for use on the 7.62 millimeter (mm) aircraft machinegun pods M18, M18A1, SUU-11A/A and SUU-11B/A to convey ammunition from the exit unit assembly into the machinegun. The feeder includes a solenoid operated mechanism for guiding the rounds either into the machinegun or into the ejection chute.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Military		
MIL-P-116	-	Preservation, Methods of.
MIL-W-13855	-	Weapons; Small Arms and Aircraft Armament Subsystem, General Specification for.
MIL-I-45607	-	Inspection Equipment, Acquisition, Maintenance and Disposition of.
MIL-L-46150	-	Lubricating Oil, Semi-Fluid (Automatic Weapons).

STANDARDS

Military		
MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-109	-	Quality Assurance Terms and Definitions.

FSC 1005 A

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:24Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. Army Weapons Command

63E10919	-	Feeder, Ammunition, Aircraft Machine Gun. MAU-57A/A.
IEL-63E10919	-	Index of Inspection Equipment Lists.

(Part drawings referenced in this specification form a part of Drawing 63E10919; inspection equipment drawings form a part of Drawing IEL-63E10919.)

PUBLICATIONS

U.S, Army Weapons Command

P63E10919	-	Packaging Data Sheet for Feeder, Ammunition.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained for the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 First article. Requirement for submission of first article samples shall be as specified in the contract (see 6.1). Samples shall be a representative of material which has been inspected and determined acceptable. One of the feeders shall be considered the pilot pack (see 5.1).

3.2 Materials and construction. Feeders and parts shall conform to the materials and construction requirements specified herein, on Drawing 63E10919 and drawings applicable thereto, and shall be in accordance with the applicable materials and construction provisions of MIL-W-13855.

3.3 Design. Feeders and parts shall conform to the design specified herein, on Drawing 63E10919 and drawings applicable thereto, and shall be in accordance with the applicable design provisions of MIL-W-13855.

3.3.1 Conveyor guide. The conveyor guide shall be securely fastened to the feeder housing by the screws so that there shall be no relative movement.

3.3.2 Conveyor wheel, ball bearing and bevel gear. The conveyor wheel, ball bearing and bevel gear shall be securely fastened together by the screws and spring pin so that there shall be no relative movement. These parts, as a unit, shall be securely fastened to the threaded stud of the sliding wheel support by the self locking nut so that there shall be no relative movement. The bevel gear shall mesh with the pinion gear without binding and the timing marks on both gears shall be in line.

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:24Z
Check the source to verify that this is the current version before use.

3.3.3 Inner guide. The inner guide shall be securely fastened to the feeder housing by the screws and nuts so that there shall be no relative movement.

3.3.4 Nose guide. The nose guide shall be securely fastened to the feeder housing by the screws so that there shall be no relative movement.

3.3.5 Outer guide. The outer guide shall be securely fastened to the feeder housing by the screws so that there shall be no relative movement.

3.3.6 Rim guide. The rim guide shall be securely fastened to the feeder housing by the screws and nuts so that there shall be no relative movement.

3.3.7 Scoop guide. The scoop guide shall be securely fastened to the feeder housing by the screws so that there shall be no relative movement.

3.3.8 Clearing shaft and solenoid group.

3.3.8.1 Clearing guides and clearing cranks. The clearing guides (forward and aft), and the clearing cranks shall be securely fastened to the clearing shaft by the spring pins so that there shall be no relative movement.

3.3.8.2 Clearing springs. The forward clearing spring shall be securely fastened to the solenoid bracket by the screws and nuts so that there shall be no relative movement. The aft clearing spring shall be securely fastened to the feeder housing with the screw, nut and spring pin so that there shall be no relative movement. The springs shall retain the clearing shaft group in the topmost position in the slots of the guide plate and solenoid bracket when the solenoid is deenergized.

3.3.8.3 Solenoid link. The solenoid link shall be connected to the solenoid plunger and the forward clearing crank by the spring pins, and when the solenoid plunger is manually depressed, the clearing shaft group shall rotate through its full range of travel without binding. When the plunger is released, the clearing shaft group shall return to the clearing position by the action of the plunger spring.

3.3.8.4 Solenoid bracket. The solenoid bracket shall be securely fastened to the feeder housing and shoop guide by the screws and spring pins so that there shall be no relative movement.

3.3.8.5 Solenoid. The solenoid shall be securely fastened to the solenoid bracket by the screws and nuts so that there shall be no relative movement.

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:24Z
Check the source to verify that this is the currentversion before use.

3.3.9 Feeder shaft group. The feeder gear, pinion gear, forward sprocket and aft sprocket shall be securely retained on the feeder shaft by the washer and self locking nut on the forward threaded end of the shaft, and by the spring pin on the opposite end of the shaft. The timing marks on the feeder shaft and the feeder gear shall be in line. The feeder shaft, with the attached parts, shall rotate in the bearings in the feeder housing and the sliding wheel support without binding.

3.3.10 Quick release pins. The quick release pins shall be capable of being manually assembled into and disassembled from their respective retaining holes in the feeder housing and the sliding wheel support. When assembled, the pins shall be retained in the retaining holes by the action of the ball detents.

3.3.11 Crossover guide. The crossover guide shall be retained on the conveyor guide by the crossover guide pins and the cotter pins. After assembly, the crossover guide shall pivot on the pins through its full range of travel without binding.

3.3.12 Ejection chute assembly. The ejection chute assembly shall be securely fastened to the feeder housing by the screws so that there shall be no relative movement.

3.3.13 Thrust plate. The thrust plate shall be securely fastened to the sliding wheel support by the screws so that there shall be no relative movement.

3.3.14 Guide plate. The guide plate shall be securely fastened to the feeder housing by the screw, nut and spring pin so that there shall be no relative movement.

3.3.15 Timing pin and spring. The spring shall be assembled on the timing pin and the timing pin assembled into the feeder housing and retained by the spring pins. The timing pin shall move through its full range of travel in the five timing holes of the forward sprocket without binding and shall normally be returned to and held in the extended position by the action of the spring.

3.3.16 Extension helical spring. The extension helical spring shall be assembled around the vertical member of the sliding wheel support and the ends attached to the ejection chute. The spring shall retain the sliding wheel support and its assembled parts in the forward position by the action of the spring. When manually moved to the rearward position and released, the sliding wheel support shall return to the forward position by the action of the spring.

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:24Z
Check the source to verify that this is the current version before use.

3.3.17 Identification plate. The identification plate shall be securely attached to the feeder housing as specified on the applicable drawing.

3.3.18 Lubrication. The needle bearings and the gear teeth shall be lubricated with lubricant conforming to MIL-L-46150. All other surfaces shall be coated with the preservative oil specified on the applicable drawings. All bearings shall be protected against contamination by cleaning solvents during cleaning operations.

3.3.19 Solenoid dielectric withstanding voltage. Solenoids shall withstand 590 to 600 volts root mean square at a frequency of 60 Hertz per second for one second without disruptive discharge or deterioration. Testing shall be as specified in 4.5.3.1 and 4.6.1.

3.3.20 Solenoid operation. The solenoid shall actuate the clearing guides and position them into the feed position when 20 volts direct surrent (vdc) is applied to the solenoid and when the solenoid is deenergized it shall allow the clearing guides to return to the clearing position under spring action of the solenoid plunger spring. Testing shall be as specified in 4.5.3.1 and 4.6.2.

3.3.21 Functioning. The feeder shall operate without stoppage or breakage of parts attributable to the feeder. Testing shall be as specified in 4.5.3.1 and 4.6.3.

3.3.22 Interchangeability. Unless otherwise specified on the drawings, all parts shall be interchangeable. (In normal assembly operations there shall be no objections interposed to preferential assembly of parts provided that all parts are dimensionally acceptable.) Feeders and repair parts shall be capable of meeting the interchangeability tests in accordance with 4.5.3.2 and 4.6.4.

3.3.23 Endurance. Feeders shall be capable of withstanding an endurance test of 30,000 rounds with at least 200 clearing operations without functioning failures (see 3.3.21), or more than one clearing malfunction attributable to the feeder. Testing shall be in accordance with 4.5.3.3 and 4.6.5.

3.4 Marking. Each feeder shall be marked in accordance with the applicable drawings and MIL-W-13855.

3.5 Workmanship. Workmanship shall be in accordance with the workmanship requirements of MIL-W-13855.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:24Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality assurance terms and definitions. Quality assurance terms and definitions used herein are in accordance with MIL-STD-109.

4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article sample inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article sample inspection. Inspection of first article samples (see 3.1) of the feeder, component parts and pilot pack (see 5.1) shall be performed at the designated testing agency. First article samples and pilot pack shall be subjected to the examination and tests specified herein and such other inspection as is necessary to determine compliance with the requirements of the contract (see 6.1).

4.5 Quality conformance inspection.

4.5.1 Inspection lot. The formation, size, and presentation of inspection lots of feeders, parts, and packaging shall be in accordance with MIL-STD-105. Inspection lots shall be as large as practicable, in consideration of quality history, manufacturing conditions, and contractor's delivery schedule, and within the limitations of MIL-W-13855. Feeders shall be assembled from lots of component parts that have met all inspection requirements specified herein. Interchangeability and endurance test lot size shall be as specified in 4.5.3.2.1.1 and 4.5.3.3.1 respectively.

4.5.2 Examination.

4.5.2.1 Component parts and concurrent repair parts. Examination of component parts and concurrent repair parts shall be performed in accordance with the criteria specified in the contract (see 6.1). The contractor's examination of these parts shall be accomplished prior to their assembly into the end item or submission for acceptance as repair parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:24Z
Check the source to verify that this is the current version before use.

4.5.2.2 Feeders. Final examination of each feeder shall be performed after completion of all testing and just prior to preservation and packaging. Each feeder shall be examined as specified below. Feeders failing to meet the requirements shall be rejected. Each step in the examination shall include a visual examination for proper cleaning and presence of the specified protective coating and to determine the general quality, completeness of manufacture, assembly, and workmanship.

4.5.2.2.1 Visually and manually examine the following parts and assemblies to determine compliance with the applicable requirements:

Part or Assembly	Reference Paragraphs
Conveyor guide	3.3.1
Conveyor wheel, ball bearing and bevel gear	3.3.2
Inner guide	3.3.3
Nose guide	3.3.4
Outer guide	3.3.5
Rim guide	3.3.6
Scoop guide	3.3.7
Clearing shaft and solenoid group	3.3.8
Feeder shaft group	3.3.9
Quick release pins	3.3.10
Crossover guide	3.3.11
Ejection chute assembly	3.3.12
Thrust plate	3.3.13
Guide plate	3.3.14
Timing pin and spring	3.3.15
Extension helical spring	3.3.16
Identification plate	3.3.17
Lubrication	3.3.18
Marking	3.4
Workmanship	3.5

4.5.2.2.2 Feeders which have passed all examination after sucessful completion of testing shall be stamped with the Department of Defense complete inspection approval stamp in the area provided on the identification plate. The Government representative will control the stamps used for such stampings to assure successful completion of all required examination and tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:24Z
Check the source to verify that this is the current version before use.

4.5.2.3 Packaging. Examination of packaging of feeders shall be performed in accordance with the classification of defects and acceptable quality levels (AQL's) specified in 4.5.2.3.1 (see 6.1). Sample size shall be in accordance with MIL-STD-105, using inspection level I. The following provisions shall apply:

a. The AQL's are specified as percent defective.
b. An individual AQL is specified for each listed defect, not for a group of defects.
c. Examination for packaging defects specified in 4.5.2.3.1 shall apply to each item of the applicable sample of feeders, interior packages, or exterior containers as applicable.

4.5.2.3.1 Classification of defects for packaging. (Unless otherwise specified in each listed defect, the packaging requirements are specified on Packaging Data Sheet P63E10919.)

Categories	Defect	AQL
Critical:	None defined.	
Major:		
101	Illegible or incorrect marking.	1.0
102	Improper location of marking.	1.0
103	Improper level of packaging and packing (see procurement documents).	1.0
104	Inadequate cleaning and drying.	1.5
105	Missing or inadequate of desiccant.	1.5
106	Improper closure of unit package	1.5
107	Improper assembly of package: position of assembly in pads.	1.5
108	Improper closure of shipping containers.	1.5
Minor:	None defined.	

4.5.2.3.2 Examination of packaging of repair parts shall be performed in accordance with the criteria specified in the contract (see 6.1).

4.5.3 Testing.

4.5.3.1 Solenoid dielectric withstanding voltage, solenoid operation and functioning testing. The contractor shall test each feeder for solenoid dielectric withstanding voltage, solenoid operation, and functioning using the test method specified in 4.6.1, 4.6.2, and 4.6.3 respectively. Feeders failing to meet the requirements shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:24Z
Check the source to verify that this is the current version before use.

4.5.3.2 Interchangeability testing.

4.5.3.2.1 In plant.

4.5.3.2.1.1 Feeders. The contractor shall test a sample of three feeders selected by the Government representative, from each month's production for interchangeability using the test method specified in 4.6.4.1.1. Feeders taken for interchangeability testing shall have been found satisfactory in all other examinations and tests. In addition, the feeders shall be tested for functioning requirement after interchange of parts using the test method specified in 4.6.3. Failure of the interchangeability test shall cause retest or rejection of the represented lot At the discretion of the Government representative, an interchangeability retest may be allowed without reconditioning the lot of feeders. Failure in the retest shall cause rejection of the represented lot subject to reconditioning and further test as a reconditioned lot. A sample of six feeders from each retest or reconditioned lot shall be tested using the same procedure described above.

4.5.3.2.1.2 Concurrent repair parts. The contractor shall subject at least two parts from each inspection lot of concurrent repair parts to the interchangeability test specified in 4.6.4.1.2. Failure of any part to meet the requirements shall be cause for rejection of the represented lot of parts subject to reconditioning and further test as a reconditioned lot. A sample of double the number of parts used in the original test shall be tested from each reconditioned lot using the test method specified in 4.6.4.1.2.

4.5.3.2.2 Interplant. When feeders are manufactured concurrently by more than one contractor, each contractor shall forward monthly three feeders for the interplant interchangeability test specified in 4.6.4.2 (see 6.1). The contractor will be informed of any failure of the feeders to meet prescribed requirements.

4.5.3.3 Endurance testing.

4.5.3.3.1 Lot size. The initial test lot of feeders shall consist of the first month's production. Thereafter, endurance test lots shall each consist of 100 feeders or a month's production, whichever is larger.

4.5.3.3.2 Procedure. One feeder, selected by the Government representative from each endurance lot shall be tested by the contractor for endurance using the test method specified in 4.6.5. If the endurance requirements are not met, the represented lot shall be rejected subject to retest or reconditioning and further test as a reconditioned lot. A retest of two other feeders from the same lot shall be made without reconditioning the represented lot, unless in the opinion of the Government representative the failure indicates serious defects in the item, in which case retest shall be made only when authorized by the procuring

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:24Z
Check the source to verify that this is the current version before use.

agency. Failure of any feeder in the retest to meet the requirements shall cause rejection of the represented lot subject to reconditioning and further testing as a reconditioned lot. Prior to submission of a lot of feeders as a reconditioned lot, the cause of failure shall be determined and contractor correction shall be affected on all feeders and parts in production. Sample size and test method for reconditioned lots shall be the same as for retest.

4.5.3.4 Component parts and concurrent repair parts testing. Raw material testing, part testing, and certification shall be performed in accordance with the criteria specified in the contract (see 6.1). This will include chemical analysis and physical tests of materials, and tests of protective finish, heat treatment, bonding, and function of parts as applicable. The contractor shall accomplish these tests prior to assembly of parts into the end item.

4.5.3.5 Packaging testing.

4.5.3.5.1 Feeders.

4.5.3.5.1.1 The contractor shall furnish the Government representative with certification that the packaging materials conform to the applicable packaging data sheets and specifications.

4.5.3.5.1.2 Determination of cleanliness. The contractor shall test items from each inspection lot for cleanliness using the test methods specified in 4.4.6.1. Sampling shall be in accordance with MIL-P-116.

4.5.3.5.1.3 Heat-sealed seam and vacuum retention. The contractor shall test level A unit packages selected by the Government representative from each inspection lot for heat-sealed seam and vacuum retention using the test methods specified in 4.6.6.2 and 4.6.6.3, respectively. Sampling shall be in accordance with MIL-P-116.

4.5.3.5.2 Repair parts. Testing of packaging of repair parts shall be performed in accordance with the criteria specified in the contract (see 6.1).

4.5.4 Inspection equipment.

4.5.4.1 Unless otherwise specified in the procurement documents (see 6.1), responsibilities for acquisition, maintenance, and disposition of measuring and testing equipment prescribed on lists contained in the Index of Inspection Equipment Lists, IEL-63E10919, and for all other inspection equipment required to perform inspection prescribed herein and by other applicable specifications, shall be in accordance with MIL-I-45607.

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:24Z
Check the source to verify that this is the current version before use.

4.5.4.2 Ammunition (see 6.1). Unless otherwise specified in procurement documents, Government standard M172 inert loaded 7.62mm dummy cartridges shall be used for testing feeders.

4.5.4.3 Unless otherwise specified, Government standard M18A1 Pod Subsystem shall be used for testing feeders. Provisions for loading ammunition, for installations and operation of the feeder in the subsystem shall be as prescribed by the procuring agency.

4.6 Test methods.

4.6.1 Solenoid dielectric withstanding voltage test. Feeders shall be tested for solenoid dielectric withstanding voltage requirement (see 3.3.19) using a current limited high potential tester and electric timer. The high potential voltage shall be applied for one second between either coil terminal (see Drawing C11691127) and grounded metal parts. High potential test voltages shall be reduced 20 percent for retest of solenoids previously tested at the voltages specified in 3.3.19.

4.6.2 Solenoid operation test. Feeders shall be tested for solenoid operation requirement (see 3.3.20) after the solenoid dielectric withstanding voltage test by applying 20 vdc to the solenoid. (Do not energize the solenoid for more than 5 seconds.)

4.6.3 Functioning test.

4.6.3.1 For feeder testing in the pod subsystem, the contractor shall provide equipment for suspending the pod, a 28 vdc power supply capable of 500 amps maximum starting current, instrumentation and control circuitry to accomplish the test.

4.6.3.2 Contractor shall be responsible for relinking dummy cartridges (to load pod) and for inspection or removal of damaged or excessively worn cartridges.

4.6.3.3 Three hundred rounds of dummy ammunition shall be used for testing each feeder. The feeder shall be accelerated up to a minimum feeding speed of 4,000 rounds per minute before power is removed and the clearing action is initiated at approximately the 50th, 100th, 150th, 200th and 250th round until the 300 rounds of dummy ammunition is expended.

4.6.3.4 When specified by the procuring agency, a Government standard drive shall be installed in the pod subsystem to test feeders for Air Force applications at minimum of 6000 rounds per minute. Except for the speed required, all other 4000 rounds per minute test provisions apply.

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:24Z
Check the source to verify that this is the current version before use.

4.6.4 Interchangeability test.

4.6.4.1 In plant.

4.6.4.1.1 Feeders. Feeders shall be tested for interchange of parts (see 3.3.22) by disassembling and then reassembling parts using the parts and pre-arranged system specified below. Interchange of parts shall be accomplished by dividing the parts of each feeder into three groups of non-mating parts as shown below and distributing the groups into three different trays until each tray contains parts for a complete feeder. Groups of parts from the first feeder shall be taken in order and placed in trays 1 through 3; groups of parts from the second feeder shall be taken in order and placed in trays 2,3, and 1; groups of parts from the third feeder shall be taken in order and placed in trays 3, 1, and 2. Parts such as screws, spring pins, etc., shall be placed in the same tray as their mating or associate part. Such parts rendered unserviceable by disassembly shall be replaced without penalty to the interchangeability test. The feeders shall be reassembled using only those parts which are in the same tray. Test the reassembled feeders for functioning (see 4.6.3).

Groups of non-mating parts

Group I

Crank, Clearing, Aft (63C10918)
Guide, Clearing, Aft (63C10935)
Guide, Clearing, Forward (63C10876)
Guide, Crossover (63D10843)
Housing, Feeder (63F10899)
Solenoid (11691127)
Spring, Clearing (63B10913)
Sprocket, Aft (63C10891)
Wheel, Conveyor (63D10797)

Group II

Bracket, Solenoid (63D10916)
Chute, Ejection (63D10917)
Crank, Clearing (63C10888)
Gear, Feeder (63C10812)
Gear, Pinion (63C10815)
Guide, Inner (63C10902)
Guide, Rim (63C10903)
Guide, Scoop (63D10900)
Link, Solenoid (63B10914)
Pin, Quick Release (63B10948)
Sprocket, Fwd. (63C10890)
Support, Wheel, Sliding (63D10802)

Group III

Gear, Bevel (63D10808)
Guide, Conveyor (63E10829)
Guide, Nose (63C10907)
Guide, Outer (63C10904)
Pin, Crossover Guide (63B11134)
Pin, Timing (65B10050-3)
Plate, Guide (63C10920)
Plate, Thrust (63B10872)
Shaft, Clearing (63B10905)
Shaft, Feeder (63D10861)
Spring, Clearing, Aft (65C10026)

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:24Z
Check the source to verify that this is the current version before use.

4.6.4.1.2 Concurrent repair parts. Concurrent repair parts shall be tested for interchangeability requirement (see 3.3.22) by disassembling two feeders, previously tested in 4.5.3.2.1.1, as necessary and then reassembling them using the concurrent repair parts. No hand refinement of parts will be allowed, and the feeders shall operate and function properly. This test may be performed independently of the feeder interchangeability test specified in 4.5.3.2.1.1, and at more frequent intervals using accepted feeders taken from current production.

4.6.4.2 Interplant. Feeders to be subjected to the interplant interchangeability test shall be inspected for functioning using the test method specified in 4.6.3 to assure proper operation before parts are interchanged. Parts shall then be disassembled from the feeder and identified as to manufacturer. Disassembled parts shall be mixed and the feeders shall be reassembled by random selection without altering or hand fitting any part. After assembly, the feeders shall be inspected for functioning using the test method specified in 4.6.3. Before feeders are returned to the contractors, the original parts shall be reassembled to their respective feeders.

4.6.5 Endurance test.

4.6.5.1 Feeders shall be tested for endurance (see 3.3.23) using the test equipment specified in 4.6.3.1.

4.6.5.2 Ammunition shall be in accordance with 4.5.6.2. The feeders shall be accelerated up to a feeding speed of 6,000 to 7,000 rounds per minute before power is removed from the electric drive and the clearing action is initiated at approximately every 150 rounds. Feeders shall be checked after each 1500 rounds for loosening of parts. All loosened parts shall be tightened and recorded. In addition, the feeders shall be lubricated after each 1500 rounds and at the end of each day's testing.

4.6.5.3 Disposition of endurance tested feeders shall be as specified in the contract (see 6.1).

4.6.6 Packaging tests.

4.6.6.1 Determination of cleanliness. The applicable surfaces of each sample unit shall be subjected to the determination of cleanliness test specified in MIL-P-116.

4.6.6.2 Heat-sealed seam. The sample level A unit packages shall be subjected to the heat-sealed seam test specified in MIL-P-116.

4.6.6.3 Vacuum retention. A sufficient vacuum shall be drawn to cause the flexible barrier of level A unit packages to cling snugly to the enclosed item. Care shall be exercised to insure that an excessive amount of vacuum is not applied which might cause puncture or rupture of the barrier.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:24Z
Check the source to verify that this is the current version before use.

4.6.6.3.1 Interpretation of results. After remaining undisturbed at room temperature for two hours, the barrier shall be examined to determine whether it is still taut and retracts against the item when drawn away and quickly released.

5. PREPARATION FOR DELIVERY

5.1 Pilot pack. The pilot pack shall consist of a complete and packaged unit package in accordance with Packaging Data Sheet P63E10919 for the level of protection specified in the contract (see 6.1), packed level C and forwarded in accordance with 3.1.

5.2 Preservation, packaging, packing and marking. Feeders shall be preserved, unit packaged, packed, and marked in accordance with the requirements of Packaging Data Sheet P63E10919 for the level of protection specified (see 6.1).

5.3 Repair parts. Repair parts shall be prepared for delivery in accordance with the applicable packaging data sheets specified in the contract (see 6.1).

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Lists of drawings and specifications pertinent to the feeder showing applicable revision dates.
c. Inspection criteria for components (see 4.3, 4.5.2.1, 4.5.2.3.2, 4.5.3.4 and 4.5.3.5.2).
d. Index of inspection equipment lists pertinent to the feeder, showing applicable revision dates.
e. Number of first article samples required for tests (see 3.1).
f. That packages opened for examination shall be repackaged by the contractor at the contractor's expense.
g. Disposition of endurance tested feeders and parts (see 4.6.5.3).
h. Shipping instructions for first article samples and pilot pack (see 3.1 and 5.1).
i. Selection of applicable levels of preservation, packaging and packing (see 5.2).
j. Packaging instructions for repair parts (see 5.3).
k. Place of final inspection and acceptance (see "Notes" in MIL-W-13855).
l. List of acceptance inspection equipment to be furnished the contractor (see 4.5.4.1) and responsibilitied for other Government property to be furnished the contractor.

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:24Z
Check the source to verify that this is the current version before use.

m. Responsibilities for furnishing ammunition.
n. Shipping instructions for feeders and parts when an interplant interchangeability test is required (see 4.5.3.2.2).
o. Procedures and methods for disposing of rejected material.
p. Disposition of Government furnished property.

6.2 When action by a testing agency is required, work programing will be effected with the testing agency at the earliest practicable date.

6.3 Monthly reports of the results of final examination and functioning, endurance and interchangeability tests shall be made to the Commanding General, U.S. Army Weapons Command, Attn: AMSWE-QA, Rock Island, Illinois 61201.

6.4 Supersession data. This specification includes the requirements of Springfield Armory Purchase Description SAPD-324, dated 5 June 1967.

6.5 When warranted, the contract should specify the application of MIL-Q-9858 or MIL-I-45208, as appropriate, on the Management Control Systems Summary List, DD Form 1660.

6.6 Unless otherwise specified (see 6.1 1), the contract should specify the application of MIL-I-45607 and MIL-C-45662 on the Management Control Summary List, DD Form 1660.

Custodian:
Army - WC
Navy - OS
Air Force - 84

Preparing activity:
Army - WC

Project Number:
1005-0458

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:24Z
Check the source to verify that this is the current version before use.