[INCH-POUND]
A-A-51175A
December 4, 1996
SUPERSEDING
A-A-51175
July 28, 1988

COMMERCIAL ITEM DESCRIPTION

WHEEL, BUFFING (BUFFS), FULL DISC, CLOTH TYPE

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE

1.1 Scope. This commercial item description (CID) covers full disc, cloth type, buffing wheels.

1.2 Intended use. Buffing wheels covered by this CID are intended for use on automatic, semi-automatic, and hand-held machinery in the coloring, cutting, buffing, and finishing of metal and plastic surfaces.

2. CLASSIFICATION

2.1 Classification. Buffing wheels shall be of the following classes, styles, wheel diameters and arbor hole diameters. The class, style, wheel diameter, and arbor hole diameter to be furnished shall be as specified (see 7.1).

Class: Class 1 - Loose sewn
Class 2 - Spiral sewn
Class 3 - Concentric sewn
Class 4 - Bias-cut

Style: Style A - Muslin
Style B - Industrial cotton sheeting
Style C - Domet flannel
Style D - Canton flannel
Style E - Sisal w/ alternating cloth layers (available only for Class 2)

Beneficial comments, recommendations, additions, deletions, clarifications etc., and any data which may improve this document should be sent to: Defense Supply Center Richmond, ATTN: DSCR-VBD, 8000 Jefferson Davis Highway, Richmond, VA 23297-5610.

AMSC N/A FSC 3460

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.

Wheel diameter:	Size 1 - 6 in.	Size 5 - 14 in
	Size 2 - 8 in.	Size 6 - 16 in.
	Size 3 - 10 in.	Size 7 - 18 in.
	Size 4 - 12 in.	Size 8 - 20 in.
Arbor hole diameter:	Size 1 - 1/8 in.	Size 6 - 7/8 in.
	Size 2 - 3/8 in.	Size 7 - 1 in.
	Size 3 - 1/2 in.	Size 8 - 1-1/4 in.
	Size 4 - 5/8 in	Size 9 - 2-1/2 in.
	Size 5 - 3/4 in.	

3. SALIENT CHARACTERISTICS

3.1 General requirements. The wheel shall be new, free from blemishes and defects, and capable of operation in accordance with the requirements herein. The wheel shall have a uniform, balanced, concentric and true finishing surface. Sewn wheels shall be stitched with high quality industrial thread. Unless otherwise specified (see 7.1), hubs or inserts shall be furnished as an integral part of the buff.

3.2 Sewing. Loose sewn buffing wheels (class 1) shall have one row of stitching around the arbor hole. The stitch spacing on class 2 and 3 wheels shall be as specified (see 7.1)

3.3 Ply. Unless otherwise specified (see 7.1), classes 1, 2, and 3 wheels shall be 20 ply. Class 4 wheels shall be 14 ply for wheels under 10 inches in diameter and 16 ply for wheels 10 inches in diameter and greater.

4. REGULATORY REQUIREMENTS

4.1 Recycled, recovered, or environmentally preferable materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Environmental protection. The item shall meet all applicable Environmental Protection Agency restrictions in effect on the date of the contract. These regulations apply to the emission of materials hazardous to the environment or the user's health and shall be met during the manufacturing, service, transportation, storage, and operation/use of the item.

5. QUALITY ASSURANCE PROVISIONS

5.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.

6. PACKAGING

6.1 Packaging requirements. Preservation, packaging, packing and marking shall be as specified in the contract or order (see 7.1).

7. NOTES

7.1 Ordering data. Acquisition documents must specify the following:

a. Title, number, and date of this document.
b. Class, style, wheel and arbor hole diameter of buffing wheel (see 2.1).
c. Hubs or inserts, if different (see 3.1).
d. Stitch spacing, as specified (see 3.2).
e. Ply, if different (see 3.3).
f. Packaging, if different (see 6.1).

7.2 Part identification number (PIN). The following part identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.

AA51175A-XXXX

Arbor hole diameter:	1 - Size 1 (1/8 in.)	6 - Size 6 (7/8 in.)
	2 - Size 2 (3/8 in.)	7 - Size 7 (1 in.)
	3 - Size 3 (1/2 in.)	8 - Size 8 (1-1/4 in.)
	4 - Size 4 (5/8 in)	9- Size 9 (2-1/2 in.)
	5 - Size 5 (3/4 in.)	
Wheel diameter:	1 - Size 1 (6 in.)	5 - Size 5 (14 in)
	2 - Size 2 (8 in.)	6 - Size 6 (16 in.)
	3 - Size 3 (10 in.)	7 - Size 7 (18 in.)
	4 - Size 4 (12 in.)	8 - Size 8 (20 in.)
Style:	A - Style A (Muslin)	
	B - Style B (Industrial cotton sheeting)	
	C - Style C (Domet flannel)	
	D - Style D (Canton flannel)	
	E - Style E (Sisal/Cloth)	
Class:	1 - Class 1 (Loose sewn)	
	2 - Class 2 (Spiral sewn)	
	3 - Class 3 (Concentric sewn)	
	4 - Class 4 (Bias-cut)	
CID number		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians
Army - AL
Air Force - 99

Reviewers
Air Force - 84

PREPARING ACTIVITY:
DLA-GS

(Project 3460-0178)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.