A-A-51180
16 April 1990
SUPERSEDING
MIL-G-80260
15 November 1984

COMMERCIAL ITEM DESCRIPTION

GRINDING MACHINES, UTILITY, PEDESTAL, COMBINATION WET-DRY

The General Services Administration has authorized the use of this commercial item description in preference to type III of Military Specification MIL-G-80260.

Abstract. This description covers electric motor driven, two wheel, utility type, pedestal mounted, wet/dry grinding machines used for off-hand grinding tools and workparts of varying configurations.

Classification. The grinding machines shall be of the sizes listed in table I. The size to be furnished shall be as specified.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Defense Industrial Plant Equipment Center, ATTN: DIPEC-SSM, 2163 Airways Blvd., Memphis, TN 38114-5051.

AMSC N/A FSC 3415

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.

TABLE I. Sizes and capacities .

Characteristics	Size 10	Size 12
Grinding wheel		
diameter, inches	10	12
face width, inches	1	2
distance between wheels, inches	20	22-3/4
Height, base to spindle centerline inches	36	36
Spindle speed, RPM	1725	1725
Spindle shaft diameter, inches	3/4	1-1/4
Spindle drive motor, horsepower	1	2
Coolant pump motor, horsepower	1/10	1/10

NOTE: 1 - Machine sizes and capacities shall be not less than the stated requirements of the size ordered.

SALIENT CHARACTERISTICS

1. Design. The grinding machine shall be new and of the manufacturer's commercial design on the date of the solicitation. The machine shall be arranged with a dry type grinding wheel on one end of the work spindle and a suitable wet grinding abrasive wheel on the other end. The wet grinding side of the machine shall have a splash bowl, coolant tank with settling chamber, pumps, and an adjustable nozzle with valve. The machine shall meet the requirements of ANSI B11.9.

2. Pedestal. The pedestal of the grinding machine shall fabricated of cast iron or a steel weldment.

3. Grinding wheels. Both types of grinding wheels provided shall meet the safety requirements of ANSI B7.1.

4. Drill grinding attachment. When specified in the contract, a drill grinding attachment shall be furnished with all necessary equipment for accurately grinding drill point angles from 90^{0} to 130^{0} on twist drills or flat drills having straight or taper shanks.

5. Wheel dresser. When specified in the contract a wheel dresser of the revolving cutter type shall be supplied.

Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.

characteristics of this commercial item description, and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices. The Government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch pound-units, provided they fall within specified tolerances using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this commercial item description are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request shall be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Preservation, packaging, packing, labeling, and marking. Preservation, packaging, packing, labeling and marking shall be as specified in the contract or purchase order.

Notes

Ordering data. Purchasers should specify the preferred options permitted herein, and include the following information in procurement documents:

a. Title, number, and date of this commercial item description.

b. Size and quantity required.

c. Drill grinding attachment, if required.

d. Wheel dresser, if required.

Federal Standard FED-STD-376 is available from the Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120-5099.

ANSI B7.1 and ANSI B11.9 are available from American National Standards Institute, ATTN. Sales Department, 1430 Broadway, New York, NY 10018-3363.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.

MILITARY INTEREST:

Custodians:

Army - AL
Navy - SH
Air Force - 99

Review Activities:

Army - ME, AL
Navy - SH
Air Force - 84

User Activity:

Navy - MC, YD

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

DLA - IP

Project 3415-0187

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.