A-A-51181
16 April 1990
SUPERSEDING
MIL-G-80260
15 November 1984

COMMERCIAL ITEM DESCRIPTION

GRINDING AND BUFFING MACHINES, UTILITY, BENCH AND PEDESTAL

The General Services Administration has authorized the use of this commercial item description in preference to type IV and type V of Military Specification MIL-G-80260.

Abstract. This description covers electric motor driven, two wheel, utility type, bench and pedestal mounted, grinding and buffing machines used for off-hand grinding or grinding and buffing numerous tools and workparts to varying finishes.

Classification. The grinding machines shall be of the following styles and of the sizes listed in table I. The style and size to be furnished shall be as specified.

Style I - Bench mount.

Style II - Pedestal mount.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Defense Industrial Plant Equipment Center, ATTN: DIPEC-SSM, 2163 Airways Blvd., Memphis, TN 38114-5051.

AMSC N/A

FSC 3415

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.

TABLE I. Sizes and capacities.

Characteristics	Styles I and II			
	Size 8	Size 10	Size 12	Size 14
Grinding wheel				
diameter, inches	8	10	12	14
face width, inches	1	1	2	2-1/2
Buffing Wheel (cloth or wire)				
diameter, inches	8	10	12	14
face, inches	1	1-1/4	2	2-1/2
distance between wheels, inches	22-1/4	24-9/16	29	29
Height, base to spindle centerline				
inches, pedestal mount	<---------- 36 ---------->			
bench mount	5-1/2	6-1/2	14	15-1/4
Spindle speed, RPM	3450	1725	1725	1725
Spindle shaft diameter, inches	5/8	3/4	1	1-1/4
Spindle drive motor, horsepower	3/4	1	2	3

NOTE: 1 - Machine sizes and capacities shall be not less than the stated requirements of the size ordered.

SALIENT CHARACTERISTICS

1. Design. The grinding machine shall be new and of the manufacturer's commercial design on the date of the solicitation. The spindle shaft shall have a grinding wheel on one end and a buffing wheel (cloth or wire) on the other end. The machine shall meet the requirements of ANSI B11.9.

2. Base and Pedestal. The base of the style I machines and the pedestal of the style II machines shall be fabricated of cast iron or a steel weldment.

3. Grinding wheels. Grinding wheels provided shall meet the safety requirements of ANSI B7.1.

4. Drill grinding attachment. When specified in the contract, a drill grinding attachment shall be furnished with all necessary equipment for accurately grinding drill point angles from 90° to 130° on twist drills or flat drills having straight or taper shanks.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.

5. Wheel dresser. When specified in the contract a wheel dresser of the revolving cutter type shall be supplied.

Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this commercial item description, and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices. The Government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch pound-units, provided they fall within specified tolerances using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this commercial item description are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request shall be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Preservation, packaging, packing, labeling, and marking. Preservation, packaging, packing, labeling and marking shall be as specified in the contract or purchase order.

Notes

Ordering data. Purchasers should the preferred options permitted herein, and include the following information in procurement documents:

a. Title, number, and date of this commercial item description.

b. Style, size, and quantity required.

c. Drill grinding attachment, if required.

d. Wheel dresser, if required.

Federal Standard FED-STD-376 is available from the Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120-5099.

ANSI B7.1 and ANSI B11.9 are available from American National Standards Institute, ATTN. Sales Department, 1430 Broadway, New York, NY 10018-3363.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.

MILITARY INTEREST:

Custodians:

Army - AL
Navy - SH
Air Force - 99

Review Activities:

Army - ME, AL
Navy - SH
Air Force - 84

User Activity:

Navy - MC, YD

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

DLA - IP

Project 3415-0188

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.