FED. SUP CLASS
5935





BOTTOM MOUNTED

USE WASHERS SUPPLIED WITH MS25332-1 TO ACCOMPLISH THE INDICATED SPACING





TOP MOUNTED



PIN RECEPTACLE LAYOUT



MOUNTING HOLE LAYOUT



DETAIL A

DASH NO.	MAX WT LB WITHOUT HARDWARE
-4	.040

(A) INSERTION AND WITHDRAWAL FORCES:
MEASURED WITH:
.0390 $^{+.0001}_{-.0000}$ DIA PIN — 1 OZ MIN
(B) VIBRATION, MIL-STD-202, METHOD 204, CONDITION B, WITH MS25325 INSERTED — 10 G, 10 TO 1500 CPS
(C) CONTACT TABS, PARA 3.8, MIL-S-12883 — NOT APPLICABLE
(D) AMBIENT TEMPERATURE RANGE — -65°C TO +120°C
(E) PIN ENTRY — PARA 3.3.1.2, MIL-C-5015
(F) DIELECTRIC, MIN, WITHOUT MATING RELAY ENGAGED
SEA LEVEL — 2500 VRMS
ALTITUDE (80,000 FT) — 500 VRMS
(G) MATING RELAY — MS25325

MATERIAL: BODY, MIL-M-19833, TYPE GDI-30F.
DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS ±.010.

(B) ENTIRE STANDARD REVISED.

FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

APPROVED 12 May 58 REVISED (B) 1 Mar 63

NOTICE—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This standard has been approved by the Dep. (Department of the Navy) and the Department of the USAF and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable.

P.A. Navy - Wep Other Cust USAF - SGEE	TITLE SOCKET, RELAY, ELECTRICAL, 14 CONTACTS, 5 AMP	MILITARY STANDARD MS25326 (ASG)
PROCUREMENT SPECIFICATION MIL-S-12883	SUPERSEDES:	SHEET 1 OF 1

DD FORM 672-1 (Lithographed editions)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23115:08Z
Check the source to verify that this is the current version before use.