MS9821

FED. SUP CLASS 5306



PART NUMBER	L	K	APPROX WEIGHT LB/100
MS9821-03	.750	.105- .125	7.36
MS9821-04	.812	.105- .125	7.66
MS9821-05	.875	.105- .125	7.96
MS9821-06	.938	.105- .125	8.26
MS9821-07	1.000	.105- .125	8.56
MS9821-08	1.062	.105- .125	8.86
MS9821-09	1.125	.105- .125	9.16
MS9821-10	1.188	.105- .125	9.46
MS9821-11	1.250	.105- .125	9.76
MS9821-12	1.312	.105- .125	10.07
MS9821-13	1.375	.105- .125	10.37
MS9821-14	1.438	.125- .188	10.67
MS9821-15	1.500	.190- .250	10.97
MS9821-16	1.562	.252- .312	11.26
MS9821-17	1.625	.315- .375	11.57
MS9821-18	1.688	.378- .438	11.87
MS9821-19	1.750	.440- .500	12.17
MS9821-20	1.812	.502- .562	12.47
MS9821-21	1.875	.565- .625	12.77
MS9821-22	1.938	.628- .688	13.07
MS9821-23	2.000	.690- .750	13.38
MS9821-24	2.125	.815- .875	13.97
MS9821-25	2.250	.940-1.000	14.58
MS9821-26	2.375	1.065-1.125	15.18
MS9821-27	2.500	1.190-1.250	15.79
MS9821-28	2.625	1.315-1.375	16.38
MS9821-29	2.750	1.440-1.500	16.98
MS9821-30	2.875	1.565-1.625	17.59

PART NUMBER	L	K	APPROX WEIGHT LB/100
MS9821-31	3.000	1.690-1.750	18.19
MS9821-32	3.125	1.815-1.875	18.80
MS9821-33	3.250	1.940-2.000	19.39
MS9821-34	3.375	2.065-2.125	20.00
MS9821-35	3.500	2.190-2.250	20.60
MS9821-36	3.625	2.315-2.375	21.20
MS9821-37	3.750	2.440-2.500	21.80
MS9821-38	3.875	2.565-2.625	22.40
MS9821-39	4.000	2.690-2.750	23.01
MS9821-40	4.125	2.815-2.875	23.61
MS9821-41	4.250	2.940-3.000	24.20
MS9821-42	4.375	3.065-3.125	24.81
MS9821-43	4.500	3.190-3.250	25.41
MS9821-44	4.625	3.315-3.375	26.02
MS9821-45	4.750	3.440-3.500	26.61
MS9821-46	4.875	3.565-3.625	27.22
MS9821-47	5.000	3.690-3.750	27.82
MS9821-48	5.125	3.815-3.875	28.42
MS9821-49	5.250	3.940-4.000	29.02
MS9821-50	5.375	4.065-4.125	29.62
MS9821-51	5.500	4.190-4.250	30.23
MS9821-52	5.625	4.315-4.375	30.83
MS9821-53	5.750	4.440-4.500	31.43
MS9821-54	5.875	4.565-4.625	32.03
MS9821-55	6.000	4.690-4.750	32.63

1. SHANK SHALL BE STRAIGHT WITHIN .002 TOTAL PER INCH OF BOLT LENGTH.
2. THE CONCENTRICITY OF THREAD PD IN RELATION TO THE SHANK SHALL BE WITHIN .006 FIR.
3. THE CONCENTRICITY OF THE SHANK IN RELATION TO THE WASHER FACE DIAMETER AND HEXAGON SHALL BE WITHIN .023 FIR.
4. INCOMPLETE THREADS NOT TO ENTER FILLET.
5. MATERIAL: CORROSION RESISTANT STEEL AMS 5643.
6. HARDNESS: ROCKWELL C32-38.
7. MANUFACTURING SPECIFICATION: AMS 7474.
8. FLUORESCENT PENETRANT INSPECTION PER AMS 2645.
9. SURFACE TEXTURE: USAS B46.1-1962. UNLESS OTHERWISE SPECIFIED, SURFACES TO BE 125 MICROINCHES EXCEPT UPSET HEAD.
10. BREAK SHARP EDGES .003-.015 UNLESS OTHERWISE SPECIFIED.
11. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: LINEAR DIMENSIONS ±.010, ANGULAR DIMENSIONS ±5°.
12. DO NOT USE UNASSIGNED PART NUMBERS.

AS & AMS ARE SOCIETY OF AUTOMOTIVE ENGINEERS, INC. PUBLICATIONS.
THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE MILITARY SERVICES BY THE SAE AEROSPACE PART STANDARDS DIV.

APPROVED 11 MAR 70 REVISED

P.A. - USAF-11 Other Cust ARMY-AV NAVY-AS	INTERNATIONAL INTEREST ASCC AIR STD 17/2	TITLE BOLT, MACHINE - HEXAGON HEAD, DRILLED, 1 HOLE, PD SHANK, AMS 5643, .500-20 UNJF-3A	MILITARY STANDARD MS9821
PROCUREMENT SPECIFICATION NONE	SUPERSEDES:		SHEET 1 OF 1

DD FORM 672-1 (Coordinated)

☆ U. S. GOVERNMENT PRINTING OFFICE: 1970-393-094/S-5401

Revise activities: USAF-82

This military standard is approved by the Department of Defense and is mandatory in all activities. Suggestions for all new engineering and design applications and for revisions now should be made from this document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:26Z
Check the source to verify that this is the current version before use.