NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/183E(IH)
16 January 2025
SUPERSEDING
MIL-DTL-3943/183D(IH)
16 March 2020

DETAIL SPECIFICATION SHEET

DECORATION, MERITORIOUS SERVICE, DEFENSE THREAT REDUCTION AGENCY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE



REVERSE

MATERIAL: Nickel Silver 65/35 (UNS Alloy No. C-752)

FINISH: Silver Plated, Oxidized, Buffed Relieved, Matte Finish, Polished Highlights and shall match The Institute of Heraldry Metal Finish Chip Number 15.

DIMENSIONS:
DIAMETER: 1-1/2 inches (REF)
THICKNESS (At thickest point): 0.158 inch ± 0.010 inch

DECORATION SET: Decoration set shall consist of a regular size medal and a lapel button all packaged in a presentation case conforming to MIL-DTL-14633, Type I with a Class 1 or 1A pad.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:19Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The specification slash sheet for the ribbon for the pendant drape and for the service ribbon is MIL-DTL-11589/166.

3. The specification slash sheet for the lapel button is MIL-DTL-11484/204.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2025-051)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:19Z
Check the source to verify that this is the current version before use.